


**Order No.:** 5TR10350H | **GTIN (EAN):** 4039806496355


**Product description:** Mod, trunk.rail, 3lg, L3588, 5x2.5<sup>2</sup>, wh



Modario®, trunking rail, of sheet steel, coated, pure white, 3-length, length: 3.588 mm, width: 58 mm, height: 43mm, through-wiring: 5x 2.5mm<sup>2</sup>, with terminal, 5-pole, max. 2.5mm<sup>2</sup>, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC 10, VDE, standard: EN 60598, packaging unit: 1 piece




Wt. (kg): 4.7  
GTIN (EAN): 4039806496355



Order No.: 5TR10350H | GTIN (EAN): 4039806496355

Detailed technical description: Mod,trunk.rail,3lg,L3588,5x2.5<sup>2</sup>,wh



#### Key data

- Product type: trunking components group (TS)
- Product name: Modario®
- Order No.: 5TR10350H

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lamps:

- Supplement: for electrical and mechanical plug and socket connection of rail elements

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Standard: EN 60598
- Certification, designation: CE, ENEC 10, VDE

#### Material, Colour

- trunking rail: sheet steel, coated, pure white, 3-length
- Colour specification: pure white

#### Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to the ceiling
- Arrangement: single/continuous arrangement

#### Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm<sup>2</sup>
- Through-wiring: 5x 2.5mm<sup>2</sup>

#### Dimensions, Weight

- System units: 12x SE
- Length: 3588mm
- Width: 58mm
- Height: 43mm
- Mounting distance: max. 3.5m
- Weight: 4.7kg

Order No.: 5TR10350H | GTIN (EAN): 4039806496355

Dimensions: Mod,trunk.rail,3lg,L3588,5x2.5<sup>2</sup>,wh

