

**Order No.:** 5TS101A0Q | **GTIN (EAN):** 4039806907042


**Product description:** Modario, trunk.rail, 1lg, L1495, 10x2.5<sup>2</sup>, wh



Modario® IP64, trunking rail, of sheet steel, galvanised, coated, pure white, 1-length, length: 1.495 mm, width: 58 mm, height: 43mm, through-wiring: 10x 2.5mm<sup>2</sup>, with terminal, 10-pole, max. 2.5mm<sup>2</sup>, protection rating (complete): IP64, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, standard: EN 60598, packaging unit: 1 piece



Wt. (kg): 2.4  
 GTIN (EAN): 4039806907042



Order No.: 5TS101A0Q | GTIN (EAN): 4039806907042

Detailed technical description: Mod64, trunk.rail, 1lg, L1495, 10x2.5<sup>2</sup>, wh



#### Key data

- Product type: trunking components group (TS)
- Product name: Modario® IP64
- Order No.: 5TS101A0Q

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lamps:

- Supplement: for electrical and mechanical plug and socket connection of rail elements

#### Certificates, Standards

- Protection rating: IP64
- Insulation class: insulation class I (protective earthing)
- Standard: EN 60598
- Certification, designation: CE, ENEC, VDE

#### Material, Colour

- trunking rail: sheet steel, galvanised, coated, pure white, 1-length
- Colour specification: pure white

#### Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to the ceiling
- Arrangement: single/continuous arrangement

#### Electrical connection

- Connection: terminal, 10-pole, max. 2.5mm<sup>2</sup>
- Through-wiring: 10x 2.5mm<sup>2</sup>

#### Dimensions, Weight

- System units: 5x SE
- Length: 1495mm
- Width: 58mm
- Height: 43mm
- Mounting distance: max. 3.5m
- Weight: 2.4kg

Order No.: 5TS101A0Q | GTIN (EAN): 4039806907042

Dimensions: Mod64, trunk.rail, 1lg, L1495, 10x2.5<sup>2</sup>, wh

