

**Order No.:** 59US1FCMA | **GTIN (EAN):** 4058352363768

**Product description:** LicExInt,extIntMD,lokCtrl



Licross® External Interface, External Interface MD, master,local  
controlinstallation type: surface-mounted, installation location: to the ceiling,  
to the luminaire, of plastic, protection rating (complete): IP54, insulation class  
(complete): insulation class II (safety insulation), certification: CE, VDE,  
voltage: 230V, voltage type: AC, packaging unit: 1 piece

 IP 54  

Wt. (kg): 0.1  
GTIN (EAN): 4058352363768

Order No.: 59US1FCMA | GTIN (EAN): 4058352363768

Detailed technical description: LicExInt,extIntMD,lokCtrl



#### Key data

- Product type: base module
- Product name: Licross® External Interface
- Order No.: 59US1FCMA

#### Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, VDE

#### Material, Colour

- housing: plastic, white, square
- Colour specification: white

#### Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling, to the luminaire

#### Electrical connection

- Nominal voltage: 230V, 50Hz, AC

#### Dimensions, Weight

- Length: 83mm
- Width: 83mm
- Height: 28mm
- Weight: 0.1kg