

Order No.: 5LZ930200 | GTIN (EAN): 4058352385944


**Product description:** Scon11,DALI2term,centCtrl,K-Bus



SITECO Connect 11, DALI-2 terminal, central control installation type: recessed, installation location: in an electrical distributor, protection rating (complete): IP20, certification: CE, voltage: 24V, voltage type: DC, 1 x K-Bus, 2 x digital switching contact, 1 x DALI-2, packaging unit: 1 piece

IP 20 CE

Wt. (kg): 0.1  
GTIN (EAN): 4058352385944



Order No.: 5LZ930200 | GTIN (EAN): 4058352385944

Detailed technical description: Scon11,DALI2term,centCtrl,K-Bus



#### Key data

- System family: Siteco Connect 11
- Product type: lighting management components
- Product name: SITECO Connect 11
- Order No.: 5LZ930200

#### Certificates, Standards

- Protection rating: IP20
- Temperature range (operation): 0..+55°C
- Certification, designation: CE

#### Material, Colour

- Colour specification: grey

#### Mounting

- Mounting method, mounting location: recessed, in an electrical distributor

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Length: 100mm
- Width: 12mm
- Height: 68mm
- Weight: 0.1kg

#### Inputs

##### 1x K-Bus

- Option: system current 55mA

##### 2x digital switching contact

- Option: for easy commissioning

#### Outputs

##### 1x DALI-2

- Connection: plug-in terminal, 2x 2-pole, max. 2.5mm<sup>2</sup>
- Protocol: according to current DALI-2 standard
- Feature: integrated power supply (250mA per DALI line)

Order No.: 5LZ930200 | GTIN (EAN): 4058352385944

Dimensions: Scon11,DALI2term,centCtrl,K-Bus

