


Order No.: 5TR21471V4050 | GTIN (EAN): 4050737970752


Product description: Mod-RS,LI,asy,LED5200lm840,0/1,wh,5su



Modario® RSLuminaire insert, length: 1.495mm, width: 75mm, LED light colour: 840, control gear: ON/OFF, control gear: ECG, with plug, 3-pole, with phase selection, mains connection: 230V, AC/DC, 0/50..60Hz, primary anti-glare with High Definition Prismatics (HDP®), primary optical cover: prismatic diffuser, of PMMA, light emission: direct distribution, primary light characteristic: asymmetric, protection rating (complete): IP20, protection rating (LED compartment): IP40, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, permissible ambient temperature for indoor applications: -30..+55°C, corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, packaging unit: 1 piece

4050737970752  
5TR21471V4050

LED 4000K / CRI ≥ 80    Φ<sub>N</sub> 5200 lm



Lamps: LED  
Wt. (kg): 3.0  
GTIN (EAN): 4050737970752

**siteco** 5TR21471V4050

The luminaire contains built-in LED lamps

A++
A+
A
B
C
D
E

}

LED

The LED-lamps cannot be changed in the luminaire

874/2012

