


Order No. OSRAM: 4058352058695 | Order No. Siteco: 5XA513281C08A5

Product description: DL30,ST1.2c,LED4190lm830,Prem



DL® 30 LED, mast luminaire, primary light control with 3 zone faceted reflector, of plastic, aluminium vaporised, highly specular, primary optical cover: cover, of PMMA, structured, transparent, light distribution: ST1.2c, light emission: direct distribution, primary light characteristic: asymmetric, crossroads, installation type: post-top, LED, LED High Power, rated luminous flux: 4.190lm, luminous efficacy: 80lm/W, light colour: 830, colour temperature: 3000K, control gear: ECG Premium, control: flexible luminous flux parameterisation, time-dependent luminous flux control, power reduction, Street Light Control, overheat protection, optimised constant luminous flux control (CLO 2.0), electronic power reduction, mains connection: 220..240V, AC, 50/60Hz, start of lifetime: 52W, end of lifetime: 62W, reduction: 26W, luminaire housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 600mm, width: 510mm, height: 290mm, spigot size: d x l = 76 x 100mm (post-top) | with reducer (optional accessory) 60 x 100mm, luminaire controller, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, impact resistance: IK08, standard-compliant lighting for roads and squares, packaging unit: 1 piece

4058352058695  
5XA513281C08A5  
LED 3000K / CRI ≥ 80    Φ<sub>h</sub> 4190 lm



Lamps: LED  
Wt. (kg): 8.0  
GTIN (EAN): 4058352058695

**siteco** AN OSRAM BUSINESS    5XA513281C08A5

The luminaire contains built-in LED lamps

A++
A+
A
B
C
D
E

} LED

The LED-lamps cannot be changed in the luminaire

874/2012

