


Order No. OSRAM: 4058352059555 | Order No. Siteco: 5XA5132T1A08A1

Product description: DL30,P1.0a,LED1560lm830,Basic



DL® 30 LED, mast luminaire, primary light control with 3 zone faceted reflector, of plastic, aluminium vaporised, highly specular, primary optical cover: cover, of PMMA, transparent, structured, light distribution: P1.0a, light emission: direct distribution, primary light characteristic: asymmetric, installation type: post-top, LED, LED High Power, rated luminous flux: 1.560lm, luminous efficacy: 92lm/W, light colour: 830, colour temperature: 3000K, control gear: ECG Basic, control: overheat protection, power reduction, electronic power reduction, mains connection: 220..240V, AC, 50/60Hz, start of lifetime: 17W, end of lifetime: 17W, reduction: 9W, luminaire housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 600mm, width: 510mm, height: 290mm, spigot size: d x l = 76 x 100mm (post-top) | with reducer (optional accessory) 60 x 100mm, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, impact resistance: IK08, standard-compliant lighting for roads and squares, packaging unit: 1 piece

4058352059555  
5XA5132T1A08A1  
LED 3000K / CRI ≥ 80     $\Phi_{\text{N}}$  1560 lm



Lamps: LED  
Wt. (kg): 7.7  
GTIN (EAN): 4058352059555

**siteco** AN OSRAM BUSINESS    5XA5132T1A08A1

The luminaire contains built-in LED lamps

A++
A+
A
B
C
D
E

} LED

The LED-lamps cannot be changed in the luminaire

874/2012

