


Order No. OSRAM: 4050737847917 | Order No. Siteco: 5XA5904A1A08P

Product description: SL10mc,ST1.2a,LED3030lm750,Basic



Streetlight 10 micro LED, mast luminaire, primary light control with 3 zone faceted reflector, of plastic, silver coated, primary optical cover: cover, of PMMA, transparent, light distribution: ST1.2a, light emission: direct distribution, primary light characteristic: asymmetric, installation type: side-entry, post-top, LED, LED High Power, rated luminous flux: 3.030lm, luminous efficacy: 107lm/W, light colour: 750, colour temperature: 5000K, control gear: ECG Basic, control: power reduction, overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm<sup>2</sup>, mains connection: 220..240V, AC, 50/60Hz, start of lifetime: 28W, end of lifetime: 28W, reduction: 13W, luminaire housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 481mm, width: 176mm, height: 138mm, spigot size: 42/60/76mm (post-top) and 42/60mm (side-entry), mast flange for spigot size: 42mm: 5XA59000XM4, 60mm: 5XA59000XM2, 76mm: 5XA59000XM1, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, permissible operating ambient temperature for outdoor applications: -25..+50°C, standard-compliant lighting for roads and squares, packaging unit: 1 piece

4050737847917  
5XA5904A1A08P  
LED 5000K / CRI ≥ 70



Lamps: LED  
Wt. (kg): 3.4  
GTIN (EAN): 4050737847917

siteco AN OSRAM BUSINESS 5XA5904A1A08P

The luminaire contains built-in LED lamps

LED

The LED-lamps cannot be changed in the luminaire

874/2012

