


Order No. OSRAM: 4050737956602 | Order No. Siteco: 5XA5904L1A08

Product description: SL10mc,P1.0a,LED1350lm740,Basic



Streetlight 10 micro LED, mast luminaire, primary light control with 3 zone faceted reflector, of plastic, aluminium vaporised, primary optical cover: cover, of PMMA, transparent, light distribution: P1.0a, light emission: direct distribution, primary light characteristic: asymmetric, installation type: post-top, side-entry, LED, LED High Power, rated luminous flux: 1.350lm, luminous efficacy: 102lm/W, light colour: 740, colour temperature: 4000K, control gear: ECG Basic, control: overheat protection, power reduction, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, 50/60Hz, start of lifetime: 13W, end of lifetime: 13W, reduction: 8W, luminaire housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 481mm, width: 176mm, height: 138mm, spigot size: 42/60/76mm (post-top) and 42/60mm (side-entry), mast flange for spigot size: 42mm: 5XA59000XM4, 60mm: 5XA59000XM2, 76mm: 5XA59000XM1, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, permissible operating ambient temperature for outdoor applications: -25..+50°C, standard-compliant lighting for roads and squares, packaging unit: 1 piece

4050737956602
5XA5904L1A08
LED 4000K / CRI ≥ 70 ϕ_h 1350 lm



Lamps: LED
Wt. (kg): 3.4
GTIN (EAN): 4050737956602

siteco AN OSRAM BUSINESS 5XA5904L1A08

The luminaire contains built-in LED lamps

LED

The LED-lamps cannot be changed in the luminaire

874/2012

