


Order No. OSRAM: 4058352079881 | Order No. Siteco: 5XA7662A2C4AB

Product description: FL20mc,PL61,LED3140lm740,Plus,mastad



Floodlight 20 micro LED, floodlight, LED unit, primary light control with lens, of plastic, primary optical cover: protective disc, of toughened safety glass, transparent, light distribution: PL61, light emission: direct distribution, installation type: post-top, side-entry, LED, LED High Power, rated luminous flux: 3.140lm, luminous efficacy: 108lm/W, light colour: 740, colour temperature: 4000K, control gear: ECG Plus, control: flexible luminous flux parameterisation, overheat protection, power reduction, digital communication interface, time-dependent luminous flux control, electronic power reduction, with terminal, 5-pole, max. 1.5mm², mains connection: 220..240V, AC, 50/60Hz, rated input power: 29W, LED unit, luminaire module, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 416mm, width: 222mm, height: 117mm, housing frame, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), mast flange adapter, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), DALI, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, protection symbol: D, permissible operating ambient temperature: -40..+40°C, permissible operating ambient temperature for outdoor applications: -40..+50°C, standard: DIN EN 12944, packaging unit: 1 piece

4058352079881
5XA7662A2C4AB
LED 4000K / CRI ≥ 70 Φ_h 3140 lm



Lamps: LED
Wt. (kg): 4.0
GTIN (EAN): 4058352079881

siteco AN OSRAM BUSINESS 5XA7662A2C4AB

The luminaire contains built-in LED lamps

A++

A+

A

~~B~~

~~C~~

~~D~~

~~E~~

~~F~~

} LED

The LED-lamps cannot be changed in the luminaire

874/2012

