

Order No.: 5XF1C32N08DA | GTIN (EAN): 4058352467978

Product description: SL31mc,ST0.8a,4900lm730,Plus,N,opt.CLO



Streetlight 31, mast luminaire, primary light control with lens, of PMMA, primary optical cover: cover, of toughened safety glass, transparent, light distribution: ST0.8a, light emission: direct distribution, primary light characteristic: asymmetric, installation type: post-top, side-entry, LED High Power LED, rated luminous flux: 4.900 lm, light colour: 730, colour temperature: 3000K, control gear: ECG Plus, control: overheat protection, power reduction, digital communication interface, constant luminous flux control, time-dependent luminous flux control, flexible luminous flux parameterisation, mains connection: 220..240V, AC, 50/60Hz, rated input power: 35W, luminaire housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 448 mm, width: 220 mm, height: 87mm, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, ENEC+, impact resistance: IK08, permissible ambient temperature for outdoor applications: -30..+50°C, standard-compliant lighting for roads and squares, packaging unit: 1 piece

IP 66 IK 08 □ CE

Lamps:	LED
Wt. (kg):	3.6
GTIN (EAN):	4058352467978

