




Photometric test report

Family Licross® 11 Recessed	Order number: 51TL18DN4C5LD EAN: 4058352418314	LP number 58690_15
	Version cover frosted, wide distribution, high visual comfort Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting DC mode (central or group accumulator) initial emergency light level Rated values Net luminous flux = 1990 lm Power consumption = 13.1 W Luminous efficacy = 151.9 lm/W	serial documentation 26.08.2020 

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 785 cd/klm**



Classifications	
DIN 5040	A 6 0
CIE	N1=78 N2=94 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL18DN4C5LD EAN: 4058352418314	LP number 58690_15
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	785.2	785.2	785.2	785.2	785.2	785.2	785.2	4.7	4.7
5°	783.4	781.4	776.6	779.8	781.8	782.1	782.7	37.3	42.0
10°	768.3	766.7	761.5	762.8	763.5	761.1	760.4	72.7	114.7
15°	743.6	742.7	733.7	728.3	720.6	709.9	707.4	103.1	217.8
20°	712.4	708.4	691.4	669.5	643.5	621.3	613.4	124.9	342.7
25°	666.9	659.0	622.8	576.9	532.3	501.9	491.6	134.0	476.7
30°	595.9	578.6	522.8	456.8	403.1	370.2	359.8	128.3	605.0
35°	487.4	465.5	401.4	331.1	278.9	249.4	240.2	109.5	714.5
40°	356.6	334.8	278.6	220.0	182.5	161.7	155.6	84.2	798.7
45°	229.8	212.6	172.5	137.3	118.7	108.8	106.4	59.3	858.0
50°	138.7	127.9	104.9	89.6	83.6	79.2	78.2	41.5	899.6
55°	86.1	79.8	69.3	65.4	63.7	60.2	58.5	30.7	930.3
60°	57.8	53.9	50.5	51.8	50.6	46.1	43.1	24.0	954.3
65°	38.0	36.1	37.7	39.9	40.1	34.9	31.4	18.5	972.8
70°	21.9	21.5	24.3	28.4	29.8	25.8	22.4	13.0	985.8
75°	11.6	11.4	12.7	17.5	19.8	17.4	14.7	8.1	993.9
80°	5.8	5.7	6.1	8.6	10.9	9.9	8.2	4.3	998.3
85°	2.4	2.3	2.4	3.2	4.0	3.9	3.0	1.7	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL18DN4C5LD EAN: 4058352418314	LP number 58690_15
---------------------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.1	17.5	16.5	17.8	18.1	13.5	14.8	13.8	15.1	15.5
	3H	16.4	17.6	16.7	17.9	18.2	14.2	15.4	14.5	15.7	16.1
	4H	16.4	17.5	16.8	17.9	18.2	14.4	15.5	14.8	15.9	16.3
	6H	16.4	17.4	16.8	17.8	18.2	14.6	15.6	15.0	16.0	16.4
	8H	16.5	17.3	16.9	17.7	18.1	14.7	15.6	15.1	16.0	16.4
	12H	16.5	17.3	16.9	17.7	18.1	14.7	15.6	15.1	16.0	16.4
4H	2H	16.2	17.3	16.6	17.7	18.0	13.9	15.0	14.3	15.4	15.7
	3H	16.5	17.5	17.0	17.9	18.3	14.8	15.8	15.3	16.2	16.6
	4H	16.6	17.4	17.1	17.9	18.3	15.2	16.1	15.7	16.5	16.9
	6H	16.6	17.3	17.1	17.8	18.2	15.5	16.2	16.0	16.6	17.1
	8H	16.7	17.3	17.1	17.7	18.2	15.6	16.2	16.1	16.7	17.1
	12H	16.7	17.2	17.2	17.7	18.2	15.6	16.2	16.1	16.6	17.1
8H	4H	16.7	17.3	17.1	17.8	18.2	15.4	16.0	15.9	16.5	16.9
	6H	16.7	17.2	17.2	17.7	18.2	15.8	16.3	16.3	16.8	17.3
	8H	16.7	17.2	17.2	17.7	18.2	15.9	16.3	16.4	16.8	17.4
	12H	16.7	17.1	17.3	17.6	18.1	16.0	16.3	16.5	16.8	17.4
12H	4H	16.7	17.2	17.2	17.7	18.2	15.4	15.9	15.9	16.4	16.9
	6H	16.7	17.2	17.2	17.6	18.2	15.8	16.2	16.3	16.7	17.2
	8H	16.7	17.1	17.3	17.6	18.1	15.9	16.3	16.4	16.8	17.3

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500
			B = 58

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		7434.0	6878.5	5580.1	4440.1	3839.9	3518.7	3443.3	
50°		4934.8	4552.1	3731.7	3188.9	2973.9	2818.2	2781.2	
55°		3434.2	3181.2	2762.2	2610.0	2540.6	2399.8	2333.4	
60°		2644.5	2465.8	2311.5	2367.5	2315.2	2111.0	1971.3	
65°		2055.1	1952.4	2038.2	2158.1	2167.7	1887.8	1700.2	
70°		1467.0	1439.3	1622.5	1896.3	1993.2	1722.2	1495.9	
75°		1028.5	1004.0	1126.1	1550.5	1746.5	1541.8	1302.2	
80°		766.5	744.8	806.1	1126.6	1430.3	1309.6	1074.9	
85°		638.8	609.1	638.8	849.8	1050.6	1036.4	796.0	

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TL18DN4C5LD
EAN: 4058352418314

LP number
58690_15

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

