



Photometric test report

Family Silica® 21	Order number: 51MX21TCTAB EAN: 4058352800119	LP number 59274_111
	Version surface-mounted luminaire, reflector, black, direct distribution, narrow distribution, UGR≤19 (L65≤3000cd/m²), tunable white	serial documentation 03.05.2023
	Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting factory setting Rated values Net luminous flux = 9300 lm Power consumption = 84.6 W Luminous efficacy = 109.9 lm/W	



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 1470 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=85 N2=99 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21	Order number: 51MX21TCTAB EAN: 4058352800119	LP number 59274_111
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	1469.7	1469.7	1469.7	1469.7	1469.7	1469.7	1469.7	8.8	8.8
5°	1425.9	1423.7	1417.2	1426.5	1433.0	1431.2	1434.7	68.2	77.0
10°	1231.5	1233.2	1235.5	1249.4	1249.6	1243.0	1248.1	118.2	195.2
15°	943.7	950.9	962.6	981.4	980.5	965.2	966.6	137.0	332.2
20°	730.3	729.1	721.8	719.8	726.6	719.9	725.4	135.8	468.0
25°	554.7	552.6	536.3	523.0	531.2	537.4	545.0	124.7	592.7
30°	415.7	413.6	392.8	386.6	400.6	405.5	411.7	110.2	702.9
35°	297.0	298.7	284.3	282.2	303.6	308.4	303.5	93.1	796.0
40°	200.5	204.3	201.1	204.4	221.4	223.2	217.2	74.2	870.2
45°	125.8	129.2	131.9	140.1	150.2	148.5	143.7	53.9	924.1
50°	74.7	77.5	82.6	89.5	95.9	91.3	86.7	36.2	960.3
55°	42.1	44.5	49.0	54.2	57.0	52.1	48.8	22.6	982.9
60°	13.9	17.2	26.8	30.8	30.6	21.8	18.2	11.3	994.3
65°	4.2	5.3	8.3	15.7	9.7	6.0	5.5	4.1	998.4
70°	1.8	1.9	1.6	3.1	2.1	2.4	2.5	1.1	999.6
75°	0.4	0.5	0.5	0.7	0.7	0.7	0.5	0.3	999.9
80°	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.1	999.9
85°	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.1	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Silica® 21	Order number: 51MX21TCTAB EAN: 4058352800119	LP number 59274_111
-----------------------------	---	-------------------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	16.6	17.9	17.0	18.2	18.5	17.2	18.5	17.6	18.8	19.1
	3H	16.5	17.6	16.9	17.9	18.3	17.1	18.2	17.5	18.5	18.9
	4H	16.4	17.4	16.8	17.8	18.1	17.0	18.0	17.4	18.4	18.8
	6H	16.4	17.2	16.8	17.6	18.0	17.0	17.9	17.4	18.2	18.6
	8H	16.4	17.2	16.8	17.5	18.0	17.0	17.8	17.5	18.2	18.6
	12H	16.4	17.1	16.8	17.5	17.9	17.0	17.7	17.4	18.1	18.5
4H	2H	16.6	17.6	17.0	17.9	18.3	17.2	18.2	17.6	18.5	18.9
	3H	16.4	17.3	16.9	17.6	18.1	17.0	17.8	17.5	18.2	18.6
	4H	16.4	17.1	16.8	17.5	17.9	16.9	17.6	17.4	18.1	18.5
	6H	16.3	16.9	16.7	17.3	17.8	16.9	17.5	17.3	17.9	18.4
	8H	16.2	16.8	16.7	17.2	17.7	16.8	17.3	17.3	17.8	18.3
	12H	16.2	16.7	16.7	17.1	17.6	16.8	17.2	17.3	17.7	18.2
8H	4H	16.2	16.8	16.7	17.2	17.7	16.8	17.3	17.3	17.8	18.3
	6H	16.1	16.6	16.6	17.0	17.5	16.7	17.1	17.2	17.6	18.1
	8H	16.1	16.4	16.6	16.9	17.5	16.6	17.0	17.1	17.5	18.0
	12H	16.0	16.3	16.6	16.8	17.4	16.6	16.9	17.1	17.4	18.0
12H	4H	16.2	16.7	16.7	17.1	17.6	16.8	17.2	17.3	17.7	18.2
	6H	16.1	16.4	16.6	16.9	17.5	16.7	17.0	17.2	17.5	18.0
	8H	16.0	16.3	16.6	16.8	17.4	16.6	16.9	17.1	17.4	18.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 2940 B = 49
-----------------	---------------------------------	-------------------------------	--------------------

C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
			Luminance in cd/m²					
45°		11481.0	11794.1	12044.7	12792.5	13711.6	13561.9	13115.7
50°		7504.0	7783.0	8297.8	8984.0	9628.1	9169.6	8703.1
55°		4738.3	5006.9	5511.6	6098.8	6410.3	5861.2	5487.0
60°		1797.5	2215.8	3464.6	3982.0	3945.0	2813.8	2344.9
65°		640.5	811.4	1274.4	2400.2	1484.8	922.2	835.6
70°		339.9	362.4	307.5	581.0	394.9	457.7	476.6
75°		90.3	126.0	123.7	164.1	164.1	162.9	133.2
80°		32.0	35.3	42.4	51.3	63.9	78.1	78.1
85°		56.3	56.3	70.4	88.1	112.6	134.1	148.1

Photometric test report

Family Silica® 21	Order number: 51MX21TCTAB EAN: 4058352800119	LP number 59274_111
-----------------------------	---	-------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°

