


Photometric test report

Family Apollon® 31	Order number: 51MP12WD2N42 EAN: 4058352926574	LP number 59515_16
	Version recessed luminaire for lay-in mounting, square M600, wide distribution, adjustable color temperature: 4000 K 5000 K, UGR≤19 (L65≤3000cd/m²)	serial documentation 11.12.2023
	Lamps LED 5000 K CRI ≥ 80 Controlgear ECG-DALI Setting individual position: colour temperature 5000K Rated values Net luminous flux = 4000 lm Power consumption = 27.5 W Luminous efficacy = 145.5 lm/W	

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 472 cd/klm**



Classifications	
DIN 5040	A 5 0
CIE	N1=62 N2=87 N3=97 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Apollon® 31	Order number: 51MP12WD2N42 EAN: 4058352926574	LP number 59515_16
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0°	15° 345°	30° 330°	45° 315°	60° 300°	75° 285°	90° 270°
γ	Luminous intensity in cd/klm						
0°	471.6	471.6	471.6	471.6	471.6	471.6	471.6
5°	470.4	470.1	470.0	470.0	470.0	470.0	470.0
10°	465.6	465.5	465.4	465.1	464.9	464.9	464.9
15°	457.8	457.8	457.6	457.3	456.9	456.8	456.9
20°	445.6	445.7	445.5	445.2	444.7	444.8	445.3
25°	427.7	427.4	427.2	427.1	427.0	427.1	427.3
30°	402.2	401.5	401.3	401.5	401.8	401.9	401.7
35°	365.2	363.5	363.1	364.0	365.5	365.6	364.2
40°	301.7	296.3	295.4	298.8	303.9	304.2	299.6
45°	217.2	205.7	202.8	208.5	217.9	220.2	215.3
50°	179.3	148.1	140.0	155.1	174.5	166.9	132.3
55°	136.8	115.8	111.1	122.8	136.2	129.8	103.4
60°	80.9	88.5	94.7	99.8	96.1	93.7	92.6
65°	49.9	65.2	73.8	75.8	65.2	64.9	74.8
70°	42.0	48.7	53.4	56.3	50.4	48.2	49.6
75°	46.6	41.4	40.0	42.4	43.7	40.7	33.3
80°	29.9	29.2	28.2	26.9	28.8	30.4	31.5
85°	16.1	14.8	14.1	14.0	15.0	15.3	15.1
90°	0.5	0.5	0.4	0.4	0.4	0.3	0.3
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family Apollon® 31	Order number: 51MP12WD2N42 EAN: 4058352926574	LP number 59515_16
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	105° 255°	120° 240°	135° 225°	150° 210°	165° 195°	180°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0°	471.6	471.6	471.6	471.6	471.6	471.6	2.8	2.8
5°	470.0	470.0	470.0	470.0	470.1	470.4	22.5	25.3
10°	464.9	464.9	465.1	465.4	465.5	465.6	44.3	69.6
15°	456.8	456.9	457.3	457.6	457.8	457.8	64.9	134.4
20°	444.8	444.7	445.2	445.5	445.7	445.6	83.5	217.9
25°	427.1	427.0	427.1	427.2	427.4	427.7	99.0	316.9
30°	401.9	401.8	401.5	401.3	401.5	402.2	110.1	426.9
35°	365.6	365.5	364.0	363.1	363.5	365.2	114.6	541.5
40°	304.2	303.9	298.8	295.4	296.3	301.7	105.7	647.2
45°	220.2	217.9	208.5	202.8	205.7	217.2	82.1	729.3
50°	166.9	174.5	155.1	140.0	148.1	179.3	65.8	795.1
55°	129.8	136.2	122.8	111.1	115.8	136.8	55.1	850.2
60°	93.7	96.1	99.8	94.7	88.5	80.9	44.3	894.4
65°	64.9	65.2	75.8	73.8	65.2	49.9	33.7	928.2
70°	48.2	50.4	56.3	53.4	48.7	42.0	26.0	954.1
75°	40.7	43.7	42.4	40.0	41.4	46.6	21.9	976.0
80°	30.4	28.8	26.9	28.2	29.2	29.9	15.7	991.7
85°	15.3	15.0	14.0	14.1	14.8	16.1	8.1	999.8
90°	0.3	0.4	0.4	0.4	0.5	0.5	0.2	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Apollon® 31	Order number: 51MP12WD2N42 EAN: 4058352926574	LP number 59515_16
------------------------------	--	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	15.2	16.7	15.5	17.0	17.4	15.4	17.0	15.8	17.3	17.6
	3H	16.0	17.3	16.3	17.7	18.0	16.3	17.6	16.6	18.0	18.3
	4H	16.6	17.9	17.0	18.2	18.6	16.7	18.0	17.1	18.3	18.7
	6H	17.2	18.4	17.6	18.7	19.1	17.2	18.4	17.6	18.8	19.2
	8H	17.4	18.6	17.9	18.9	19.3	17.5	18.6	17.9	19.0	19.4
	12H	17.7	18.7	18.1	19.1	19.5	17.7	18.8	18.2	19.2	19.6
4H	2H	15.7	17.0	16.1	17.4	17.7	15.9	17.2	16.3	17.5	17.9
	3H	16.7	17.8	17.2	18.2	18.6	16.9	18.0	17.4	18.4	18.8
	4H	17.5	18.5	17.9	18.9	19.3	17.6	18.5	18.0	18.9	19.4
	6H	18.2	19.1	18.7	19.5	20.0	18.3	19.1	18.7	19.6	20.0
	8H	18.6	19.3	19.0	19.8	20.2	18.6	19.4	19.1	19.8	20.3
	12H	18.9	19.5	19.3	20.0	20.5	18.9	19.6	19.4	20.0	20.5
8H	4H	17.8	18.6	18.3	19.0	19.5	17.9	18.6	18.3	19.1	19.6
	6H	18.7	19.3	19.2	19.8	20.3	18.8	19.4	19.2	19.9	20.4
	8H	19.1	19.7	19.6	20.2	20.7	19.2	19.8	19.7	20.3	20.8
	12H	19.5	20.0	20.0	20.5	21.0	19.6	20.1	20.1	20.6	21.1
12H	4H	17.9	18.5	18.3	19.0	19.5	17.9	18.6	18.4	19.1	19.6
	6H	18.8	19.4	19.3	19.8	20.4	18.9	19.4	19.4	19.9	20.4
	8H	19.3	19.7	19.8	20.2	20.8	19.4	19.8	19.9	20.3	20.9

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 555	B = 555
------------------------	---	--------------------------------------	----------------	----------------

C-planes	0°	15° 345°	30° 330°	45° 315°	60° 300°	75° 285°	90° 270°	105° 255°	120° 240°	135° 225°	150° 210°	165° 195°	180°
γ	Luminance in cd/m ²												
45°	3988.1	3777.2	3724.1	3828.7	4002.6	4044.6	3954.9	4044.6	4002.6	3828.7	3724.1	3777.2	3988.1
50°	3622.3	2991.9	2829.0	3133.7	3525.9	3372.2	2672.6	3372.2	3525.9	3133.7	2829.0	2991.9	3622.3
55°	3096.6	2620.9	2515.6	2780.7	3084.2	2937.7	2341.2	2937.7	3084.2	2780.7	2515.6	2620.9	3096.6
60°	2102.3	2297.3	2460.4	2591.7	2496.9	2434.5	2404.5	2434.5	2496.9	2591.7	2460.4	2297.3	2102.3
65°	1532.6	2001.9	2267.5	2329.4	2003.2	1993.0	2298.9	1993.0	2003.2	2329.4	2267.5	2001.9	1532.6
70°	1595.6	1847.2	2027.8	2137.4	1914.0	1829.3	1883.3	1829.3	1914.0	2137.4	2027.8	1847.2	1595.6
75°	2335.6	2076.8	2006.7	2125.3	2194.1	2042.4	1670.3	2042.4	2194.1	2125.3	2006.7	2076.8	2335.6
80°	2234.9	2181.1	2106.8	2012.1	2156.5	2269.9	2352.2	2269.9	2156.5	2012.1	2106.8	2181.1	2234.9
85°	2395.0	2198.8	2098.0	2092.1	2230.3	2281.3	2245.2	2281.3	2230.3	2092.1	2098.0	2198.8	2395.0

Photometric test report

Family Apollon® 31	Order number: 51MP12WD2N42 EAN: 4058352926574	LP number 59515_16
------------------------------	--	------------------------------



Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

