




Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12TNT9XX EAN: 4058352019283	LP number 58689_190
	Version cover frosted, wide distribution, tunable white, high visual comfort Lamps LED 2700 K ... 6500 K CRI ≥ 80 Controlgear ECG-DALI Setting individual position Rated values at 2700 K Net luminous flux = 9050 lm Power consumption = 56.0 W Luminous efficacy = 161.6 lm/W	serial documentation 15.03.2024 

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 575 cd/klm**



Classifications	
DIN 5040	A 5 0
CIE	N1=66 N2=91 N3=98 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12TNT9XX EAN: 4058352019283	LP number 58689_190
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	555.4	555.4	555.4	555.4	555.4	555.4	555.4	3.3	3.3
5°	551.9	549.3	545.0	546.0	548.1	548.0	548.5	26.2	29.5
10°	538.7	535.0	528.7	529.1	532.7	535.9	538.2	50.8	80.3
15°	515.9	510.9	504.6	513.1	530.5	544.7	552.3	74.2	154.5
20°	477.2	471.4	470.1	497.6	537.0	563.7	575.1	95.8	250.2
25°	425.5	419.5	426.9	469.4	521.2	548.6	558.0	111.1	361.3
30°	371.2	364.3	378.4	421.3	459.9	477.2	482.9	115.5	476.8
35°	317.2	309.8	328.6	357.7	367.8	374.7	379.7	109.4	586.2
40°	263.2	255.5	280.4	291.4	277.2	277.7	283.1	97.2	683.4
45°	213.7	204.0	230.1	230.5	202.8	200.2	207.0	82.5	765.9
50°	172.3	160.2	177.2	176.6	149.6	143.3	148.0	67.7	833.6
55°	133.3	121.6	126.4	129.1	111.8	101.0	103.0	53.0	886.6
60°	96.7	87.9	85.2	90.2	83.1	71.0	72.1	39.7	926.3
65°	67.7	61.0	56.3	61.1	60.5	50.8	52.1	29.0	955.3
70°	46.9	41.7	36.5	40.2	42.1	36.4	38.1	20.6	975.8
75°	30.9	26.7	22.6	25.0	27.1	24.7	26.6	13.7	989.5
80°	17.8	14.8	12.0	13.1	14.7	14.1	15.6	7.7	997.1
85°	6.6	5.4	4.4	4.8	5.3	5.4	5.9	2.9	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12TNT9XX EAN: 4058352019283	LP number 58689_190
---------------------------------------	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	22.5	24.0	22.9	24.3	24.7	22.0	23.5	22.4	23.8	24.1
	3H	23.3	24.6	23.6	24.9	25.3	22.6	23.9	23.0	24.2	24.6
	4H	23.6	24.8	24.0	25.1	25.5	22.9	24.1	23.2	24.4	24.8
	6H	23.8	24.9	24.2	25.3	25.7	23.1	24.2	23.5	24.6	25.0
	8H	23.9	24.9	24.3	25.3	25.7	23.2	24.2	23.6	24.6	25.0
	12H	23.9	24.9	24.4	25.3	25.7	23.2	24.2	23.7	24.6	25.0
4H	2H	22.9	24.1	23.3	24.4	24.8	22.4	23.7	22.8	24.0	24.4
	3H	23.7	24.7	24.1	25.1	25.5	23.2	24.2	23.6	24.6	25.0
	4H	24.0	25.0	24.5	25.4	25.8	23.6	24.5	24.0	24.9	25.3
	6H	24.3	25.1	24.8	25.5	26.0	23.8	24.6	24.3	25.1	25.5
	8H	24.4	25.1	24.9	25.6	26.1	23.9	24.6	24.4	25.1	25.6
	12H	24.5	25.1	25.0	25.6	26.1	24.0	24.6	24.5	25.1	25.6
8H	4H	24.1	24.8	24.6	25.3	25.8	23.7	24.4	24.1	24.8	25.3
	6H	24.5	25.0	24.9	25.5	26.0	24.0	24.6	24.5	25.1	25.6
	8H	24.6	25.1	25.1	25.6	26.1	24.2	24.7	24.7	25.2	25.7
	12H	24.7	25.1	25.2	25.6	26.1	24.3	24.7	24.8	25.2	25.7
12H	4H	24.1	24.8	24.6	25.2	25.7	23.7	24.3	24.2	24.8	25.3
	6H	24.5	25.0	25.0	25.5	26.0	24.1	24.6	24.6	25.0	25.6
	8H	24.6	25.0	25.1	25.5	26.1	24.2	24.6	24.7	25.1	25.7

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500 B = 58
------------------------	---	--------------------------------------	----------------------------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		31438.3	30008.8	33844.3	33903.6	29836.3	29447.9	30456.6	
50°		27878.6	25932.1	28679.7	28584.7	24211.2	23190.6	23950.2	
55°		24180.0	22045.4	22916.5	23408.7	20271.2	18322.7	18680.3	
60°		20112.4	18282.5	17731.6	18761.4	17295.3	14773.1	14992.0	
65°		16659.5	15021.4	13864.3	15030.3	14897.6	12514.0	12814.5	
70°		14259.7	12696.1	11104.6	12233.2	12807.5	11077.8	11589.7	
75°		12432.8	10718.6	9071.2	10029.0	10882.2	9914.0	10681.7	
80°		10645.0	8843.7	7174.2	7876.8	8779.6	8469.9	9348.7	
85°		7868.9	6446.3	5243.2	5694.3	6298.3	6406.9	7010.8	

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL12TNT9XX EAN: 4058352019283	LP number 58689_190
---------------------------------------	--	--------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**

