

Photometric test report

Family
Monsun® 21



Order number: 51FB207P480C
EAN: 4069025178367

Version

Lamps

Controlgear

Rated values

prismatic diffuser, opal, polycarbonate,
extremely wide distribution

LED 4000 K | CRI ≥ 80


ECG

Net luminous flux = 7270 lm
Power consumption = 44.5 W
Luminous efficacy = 163.4 lm/W

LP number
59060_112

serial
documentation
08.05.2024

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 1	η_{LB}	100.0%
CIE	N1=45 N2=75 N3=93	ϕ_u	93.7%
	N4=94 N5=100	ϕ_o	6.3%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 21	Order number: 51FB207P480C EAN: 4069025178367	LP number 59060_112
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	319.4	319.4	319.4	319.4	319.4	319.4	319.4	1.9	1.9
5°	319.1	317.8	316.0	317.2	318.6	318.6	318.8	15.2	17.1
10°	313.9	312.8	311.0	312.1	313.5	313.5	313.7	29.8	46.9
15°	305.6	304.7	302.7	303.7	305.0	304.9	305.2	43.2	90.1
20°	294.3	293.5	291.4	292.2	293.3	293.1	293.5	54.9	145.0
25°	280.9	280.2	277.7	277.9	278.8	278.5	278.8	64.6	209.6
30°	265.9	265.3	262.4	261.6	261.9	261.4	261.7	72.0	281.6
35°	249.2	248.5	245.6	243.7	242.9	242.2	242.4	77.0	358.5
40°	231.6	230.8	227.5	224.6	222.7	221.4	221.6	79.5	438.0
45°	212.9	211.8	208.5	204.2	201.3	199.0	199.4	79.5	517.5
50°	193.7	192.3	188.8	183.7	179.4	175.9	176.0	77.3	594.9
55°	174.1	172.4	168.8	162.7	157.2	152.3	152.1	73.1	667.9
60°	153.8	152.1	148.1	141.4	134.9	128.8	127.5	66.9	734.9
65°	133.1	131.4	127.0	119.9	112.8	105.5	102.8	59.2	794.0
70°	112.0	110.4	105.0	98.0	90.2	82.2	78.2	49.9	843.9
75°	90.5	88.8	83.0	75.7	67.3	58.8	53.6	39.3	883.2
80°	69.4	67.4	62.0	54.0	45.3	36.4	30.4	28.3	911.6
85°	51.2	49.1	43.8	35.9	26.7	17.7	11.3	18.6	930.2
90°	40.3	38.3	33.0	25.3	16.4	7.5	1.9	12.9	943.1
95°	36.9	35.1	30.2	22.8	14.1	5.6	1.6	11.6	954.7
100°	33.7	31.9	27.1	20.1	11.9	4.0	1.5	10.1	964.8
105°	30.1	28.5	23.8	17.3	9.5	2.6	1.3	8.6	973.4
110°	26.5	24.6	20.5	14.4	7.3	1.5	1.2	7.1	980.4
115°	22.8	21.1	17.3	11.6	5.2	1.3	1.2	5.7	986.1
120°	19.1	17.5	14.1	8.9	3.4	1.3	1.1	4.4	990.5
125°	15.4	13.9	10.8	6.2	1.7	1.2	1.0	3.2	993.6
130°	11.8	10.5	7.7	3.9	1.4	1.2	1.0	2.2	995.8
135°	8.3	7.2	5.0	2.0	1.4	1.2	1.1	1.4	997.2
140°	5.1	4.3	2.5	1.6	1.3	1.1	1.0	0.8	998.0
145°	2.4	2.0	1.8	1.6	1.4	1.2	1.2	0.5	998.5
150°	1.9	1.9	1.8	1.5	1.4	1.3	1.2	0.4	999.0
155°	1.8	1.8	1.6	1.5	1.4	1.3	1.3	0.4	999.3
160°	1.6	1.6	1.5	1.5	1.4	1.4	1.3	0.3	999.6
165°	1.5	1.5	1.4	1.4	1.4	1.4	1.3	0.2	999.8
170°	1.4	1.4	1.4	1.4	1.4	1.4	1.3	0.1	999.9
175°	1.3	1.3	1.3	1.4	1.4	1.4	1.3	0.1	1000.0
180°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.0	1000.0

Photometric test report

Family Monsun® 21		Order number: 51FB207P480C EAN: 4069025178367							LP number 59060_112	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	21.0	22.7	21.3	23.0	23.3	20.8	22.5	21.2	22.8
	3H	22.8	24.4	23.2	24.7	25.1	22.4	23.9	22.7	24.3
	4H	23.6	25.1	24.0	25.5	25.8	23.0	24.5	23.4	24.8
	6H	24.4	25.7	24.8	26.1	26.5	23.4	24.8	23.8	25.1
	8H	24.7	26.0	25.1	26.4	26.8	23.5	24.8	24.0	25.2
	12H	25.0	26.2	25.4	26.6	27.0	23.6	24.8	24.0	25.2
4H	2H	21.7	23.2	22.1	23.6	23.9	21.6	23.1	22.0	23.4
	3H	23.7	25.0	24.2	25.4	25.8	23.3	24.6	23.8	25.0
	4H	24.7	25.9	25.1	26.3	26.7	24.1	25.2	24.5	25.6
	6H	25.6	26.6	26.0	27.0	27.5	24.6	25.6	25.1	26.0
	8H	26.0	26.9	26.4	27.3	27.8	24.8	25.7	25.2	26.2
	12H	26.3	27.2	26.8	27.6	28.1	24.9	25.7	25.4	26.2
8H	4H	25.0	26.0	25.5	26.4	26.9	24.5	25.4	25.0	25.9
	6H	26.1	26.9	26.6	27.3	27.8	25.2	26.0	25.7	26.4
	8H	26.6	27.3	27.1	27.7	28.3	25.4	26.1	25.9	26.6
	12H	27.1	27.7	27.6	28.2	28.7	25.6	26.2	26.1	26.7
12H	4H	25.1	25.9	25.6	26.4	26.9	24.6	25.4	25.1	25.9
	6H	26.2	26.9	26.7	27.3	27.9	25.3	26.0	25.8	26.5
	8H	26.7	27.3	27.2	27.8	28.3	25.6	26.2	26.1	26.7

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1590 B = 87	H(C0) = 21 H(C90) = 21	H(C180) = 21 H(C270) = 21
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
			Luminance in cd/m²					
45°		12749.8	12732.2	12746.6	12863.7	13212.3	13754.9	14624.2
50°		12300.1	12264.1	12283.4	12368.2	12673.4	13196.7	14164.5
55°		11863.4	11805.2	11822.9	11858.2	12117.2	12600.8	13676.8
60°		11396.6	11339.0	11334.3	11333.0	11540.8	11975.8	13102.9
65°		10905.8	10844.7	10795.0	10760.9	10927.6	11291.7	12425.8
70°		10347.4	10279.9	10136.2	10074.1	10167.0	10461.7	11591.7
75°		9665.4	9579.2	9341.0	9196.1	9153.0	9324.3	10380.4
80°		8869.8	8713.2	8444.7	8080.6	7832.2	7723.5	8572.8
85°		8220.6	8000.7	7623.8	7073.4	6404.0	5723.4	5929.7

Photometric test report

Family
Monsun® 21

Order number: 51FB207P480C
EAN: 4069025178367

LP number
59060_112

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

