

Photometric test report

Family
Round 21 L



Order number: 51MR38FD0421B
EAN: 4058352829998

Version

Lamps

Controlgear

Rated values

surface-mounted and suspended luminaire, cover, opal, PMMA, extremely wide distribution, direct distribution, aluminium housing, black

LED 4000 K | CRI ≥ 80


ECG-DALI

Net luminous flux = 14150 lm
Power consumption = 97.0 W
Luminous efficacy = 145.9 lm/W

LP number
59511_14

serial
documentation
31.07.2024

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 0	η_{LB}	100.0%
CIE	N1=49 N2=80 N3=96	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Round 21 L	Order number: 51MR38FD0421B EAN: 4058352829998	LP number 59511_14
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	375.8	375.8	375.8	375.8	375.8	375.8	375.8	2.2	2.2
5°	373.6	373.6	373.6	373.6	373.7	373.6	373.6	17.8	20.1
10°	367.1	367.0	367.1	367.1	367.2	367.1	367.2	34.9	55.0
15°	356.4	356.5	356.5	356.7	356.7	356.7	356.7	50.6	105.6
20°	342.0	342.1	342.1	342.4	342.4	342.5	342.5	64.2	169.8
25°	324.2	324.6	324.4	324.9	324.8	325.3	324.9	75.2	245.0
30°	303.7	304.3	303.9	304.6	304.5	305.2	304.6	83.4	328.5
35°	280.8	281.7	281.1	282.4	281.8	282.9	282.0	88.6	417.1
40°	256.2	257.4	256.5	258.0	257.2	258.5	257.4	90.7	507.8
45°	230.2	231.7	230.5	232.2	231.4	232.8	231.7	89.8	597.5
50°	203.5	204.9	203.8	205.4	204.7	206.0	204.9	86.0	683.6
55°	176.3	177.6	175.5	178.1	177.3	178.7	177.4	79.6	763.2
60°	148.1	149.5	147.4	150.0	149.0	150.6	149.2	70.8	834.0
65°	119.2	120.8	118.4	121.2	120.0	121.6	120.1	59.7	893.7
70°	89.7	91.5	88.8	91.9	90.4	92.3	90.6	46.8	940.5
75°	60.9	62.5	60.0	63.4	61.5	63.0	61.6	32.8	973.3
80°	34.5	35.9	33.5	36.8	35.0	36.0	35.0	19.1	992.4
85°	13.2	14.6	12.4	14.8	13.6	14.5	13.7	7.6	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Round 21 L			Order number: 51MR38FD0421B EAN: 4058352829998							LP number 59511_14	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	19.5	21.2	19.8	21.5	21.8	19.5	21.2	19.9	21.5	21.8
	3H	21.0	22.6	21.4	22.9	23.2	21.1	22.6	21.5	22.9	23.3
	4H	21.6	23.1	22.0	23.4	23.8	21.7	23.1	22.1	23.5	23.8
	6H	22.1	23.4	22.5	23.7	24.1	22.1	23.4	22.5	23.8	24.2
	8H	22.2	23.4	22.6	23.8	24.2	22.3	23.5	22.7	23.9	24.3
	12H	22.3	23.5	22.7	23.8	24.3	22.4	23.5	22.8	23.9	24.3
4H	2H	20.2	21.6	20.6	22.0	22.4	20.3	21.7	20.7	22.0	22.4
	3H	22.0	23.2	22.4	23.5	24.0	22.0	23.2	22.4	23.6	24.0
	4H	22.7	23.7	23.1	24.2	24.6	22.7	23.8	23.2	24.2	24.6
	6H	23.2	24.1	23.6	24.6	25.0	23.2	24.2	23.7	24.6	25.1
	8H	23.4	24.2	23.8	24.7	25.1	23.4	24.3	23.9	24.7	25.2
	12H	23.5	24.3	24.0	24.7	25.2	23.6	24.3	24.0	24.8	25.3
8H	4H	23.0	23.8	23.4	24.3	24.8	23.0	23.9	23.5	24.3	24.8
	6H	23.6	24.3	24.1	24.8	25.3	23.7	24.4	24.2	24.9	25.4
	8H	23.8	24.5	24.3	25.0	25.5	23.9	24.5	24.4	25.0	25.5
	12H	24.0	24.5	24.5	25.0	25.6	24.1	24.6	24.6	25.1	25.6
12H	4H	23.0	23.8	23.5	24.3	24.7	23.1	23.8	23.6	24.3	24.8
	6H	23.7	24.3	24.2	24.8	25.3	23.8	24.4	24.3	24.8	25.4
	8H	23.9	24.5	24.5	25.0	25.5	24.0	24.5	24.5	25.0	25.6

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 840	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	8311.9	8368.1	8324.2	8384.4	8355.3	8405.2	8366.8
50°	8083.1	8140.6	8096.2	8159.4	8129.7	8184.2	8137.4
55°	7847.4	7907.0	7814.2	7928.6	7890.8	7954.6	7898.6
60°	7564.5	7636.5	7524.8	7661.6	7609.5	7689.7	7618.4
65°	7201.4	7295.9	7150.4	7319.9	7247.4	7346.8	7257.4
70°	6698.5	6834.3	6631.7	6859.7	6750.2	6887.7	6761.2
75°	6012.6	6167.7	5920.8	6258.9	6070.9	6216.6	6078.8
80°	5072.3	5271.9	4927.3	5411.4	5139.4	5293.9	5151.1
85°	3872.4	4280.2	3636.3	4328.5	3989.6	4261.1	4015.9

Photometric test report

Family
Round 21 L

Order number: 51MR38FD0421B
EAN: 4058352829998

LP number
59511_14

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

