


Photometric test report

Family Lunis 21	Order number: 51DB18TF91C EAN: 4069025012975	LP number 59684_7
	Version	recessed luminaire, Combined lens and reflector optics, reflector, white, rotationally symmetrical wide distribution, tunable white, UGR≤19
	Lamps	LED 3000 K ... 6500 K CRI ≥ 80
	Controlgear	ECG Multilumen
	Setting	factory setting: DIP-Step=6, colour temperature 4000K
	Rated values	at 4000 K Net luminous flux = 2410 lm Power consumption = 13.6 W Luminous efficacy = 177.2 lm/W
		serial documentation 27.09.2024
		siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 7 0	η_{LB}	100.0%
CIE	N1=87 N2=97 N3=99	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 21	Order number: 51DB18TF91C EAN: 4069025012975	LP number 59684_7
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	1080.4	0.3	0.3
1°	1077.2	2.1	2.3
2°	1073.1	4.1	6.4
3°	1066.8	6.1	12.5
4°	1058.4	8.1	20.6
5°	1050.1	10.0	30.7
6°	1039.9	11.9	42.6
7°	1028.0	13.7	56.3
8°	1016.5	15.5	71.9
9°	1003.5	17.2	89.1
10°	989.5	18.8	107.9
11°	973.7	20.4	128.3
12°	957.9	21.8	150.1
13°	939.3	23.2	173.3
14°	918.9	24.4	197.7
15°	897.8	25.5	223.2
16°	876.2	26.5	249.6
17°	854.6	27.4	277.0
18°	831.5	28.2	305.2
19°	807.0	28.8	334.0
20°	782.0	29.3	363.4
21°	756.8	29.7	393.1
22°	730.9	30.0	423.1
23°	703.9	30.2	453.3
24°	675.9	30.1	483.4
25°	647.6	30.0	513.4
26°	618.4	29.7	543.2
27°	589.1	29.3	572.5
28°	559.4	28.8	601.3
29°	528.8	28.1	629.4
30°	494.4	27.1	656.5
31°	461.0	26.0	682.6
32°	428.8	24.9	707.5
33°	395.8	23.6	731.1
34°	362.0	22.2	753.3
35°	329.6	20.7	774.0
36°	300.2	19.3	793.4
37°	271.3	17.9	811.3
38°	241.6	16.3	827.6
39°	216.1	14.9	842.5
40°	193.0	13.6	856.1
41°	170.9	12.3	868.4
42°	150.8	11.1	879.5
43°	134.0	10.0	889.5
44°	118.2	9.0	898.5
45°	104.2	8.1	906.6
46°	93.3	7.4	913.9

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	83.3	6.7	920.6
48°	75.5	6.2	926.8
49°	67.8	5.6	932.4
50°	61.0	5.1	937.5
51°	55.4	4.7	942.2
52°	50.2	4.3	946.6
53°	45.4	4.0	950.5
54°	41.5	3.7	954.2
55°	37.7	3.4	957.6
56°	34.5	3.1	960.7
57°	31.5	2.9	963.6
58°	28.8	2.7	966.3
59°	26.4	2.5	968.8
60°	24.1	2.3	971.1
61°	22.1	2.1	973.2
62°	20.3	2.0	975.2
63°	18.7	1.8	977.0
64°	17.2	1.7	978.7
65°	16.0	1.6	980.3
66°	14.9	1.5	981.8
67°	14.1	1.4	983.2
68°	13.5	1.4	984.6
69°	12.9	1.3	985.9
70°	12.4	1.3	987.2
71°	11.8	1.2	988.4
72°	11.2	1.2	989.6
73°	10.6	1.1	990.7
74°	10.0	1.1	991.7
75°	9.4	1.0	992.7
76°	8.8	0.9	993.6
77°	8.2	0.9	994.5
78°	7.6	0.8	995.3
79°	7.0	0.8	996.1
80°	6.4	0.7	996.8
81°	5.8	0.6	997.4
82°	5.1	0.6	998.0
83°	4.4	0.5	998.4
84°	3.7	0.4	998.8
85°	3.1	0.3	999.2
86°	2.6	0.3	999.5
87°	2.1	0.2	999.7
88°	1.6	0.2	999.9
89°	1.1	0.1	1000.0
90°	0.0	0.0	1000.0
180°	0.0	0.0	1000.0

Photometric test report

Family Lunis 21		Order number: 51DB18TF91C EAN: 4069025012975							LP number 59684_7	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
2H	x									
	y									
	2H	17.6	18.9	18.0	19.2	19.5	17.6	18.9	18.0	19.2
	3H	17.7	18.8	18.1	19.2	19.5	17.7	18.8	18.1	19.2
	4H	17.8	18.9	18.2	19.2	19.6	17.8	18.9	18.2	19.2
	6H	18.0	18.9	18.4	19.2	19.6	18.0	18.9	18.4	19.2
4H	8H	18.1	18.9	18.5	19.2	19.7	18.1	18.9	18.5	19.2
	12H	18.1	18.8	18.6	19.2	19.6	18.1	18.8	18.6	19.2
	2H	17.6	18.6	18.0	18.9	19.3	17.6	18.6	18.0	18.9
	3H	17.8	18.6	18.2	19.0	19.4	17.8	18.6	18.2	19.0
	4H	17.9	18.7	18.4	19.1	19.5	17.9	18.7	18.4	19.1
	6H	18.1	18.8	18.6	19.2	19.7	18.1	18.8	18.6	19.2
8H	8H	18.2	18.8	18.7	19.2	19.7	18.2	18.8	18.7	19.2
	12H	18.3	18.8	18.8	19.3	19.8	18.3	18.8	18.8	19.3
	4H	18.0	18.5	18.5	19.0	19.5	18.0	18.5	18.5	19.0
	6H	18.2	18.7	18.7	19.2	19.7	18.2	18.7	18.7	19.2
	8H	18.4	18.8	18.9	19.3	19.8	18.4	18.8	18.9	19.3
	12H	18.5	18.8	19.0	19.3	19.9	18.5	18.8	19.0	19.3
12H	4H	18.0	18.5	18.5	18.9	19.4	18.0	18.5	18.5	18.9
	6H	18.3	18.6	18.8	19.1	19.7	18.3	18.6	18.8	19.1
	8H	18.4	18.7	19.0	19.2	19.8	18.4	18.7	19.0	19.2

Luminance table		Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	D = 182
C- planes	0°			
γ	Luminance in cd/m²			
45°	13646.9			
50°	8796.5			
55°	6082.7			
60°	4470.5			
65°	3498.4			
70°	3345.6			
75°	3360.2			
80°	3418.5			
85°	3319.4			

Photometric test report

Family
Lunis 21

Order number: 51DB18TF91C
EAN: 4069025012975

LP number
59684_7

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Lunis 21	Order number: 51DB18TF91C EAN: 4069025012975	LP number 59684_7
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
12	ON	ON	OFF	OFF	4110	25.4
11	ON	OFF	ON	ON	3630	21.7
10	ON	OFF	ON	OFF	3470	20.6
9	ON	OFF	OFF	ON	3280	19.1
8	ON	OFF	OFF	OFF	3090	17.7
7	OFF	ON	ON	ON	2700	15.3
6	OFF	ON	ON	OFF	2410	13.6
5	OFF	ON	OFF	ON	2150	12.1
4	OFF	ON	OFF	OFF	1850	10.4
3	OFF	OFF	ON	ON	1740	9.7
2	OFF	OFF	ON	OFF	1450	8.0
1	OFF	OFF	OFF	ON	1110	6.1
0	OFF	OFF	OFF	OFF	800	4.4