

Photometric test report

Family
Lunis 41



Order number: 51DR10MFHCB
EAN: 4069025152107

Version

Lamps

Controlgear

Setting

Rated values

recessed luminaire, diffuse cover, extremely wide distribution, adjustable color temperature: 4000 K | 6500 K

LED 6500 K | CRI ≥ 80

ECG


individual position: colour temperature 6500K

Net luminous flux = 2500 lm
Power consumption = 19.5 W
Luminous efficacy = 128.2 lm/W

LP number
59234_16

serial
documentation
16.01.2025

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 0	η_{LB}	100.0%
CIE	N1=49 N2=80 N3=96	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions	
DIN EN 13032 and DIN 5032	

Photometric test report

Family Lunis 41	Order number: 51DR10MFHCB EAN: 4069025152107	LP number 59234_16
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	368.6	368.6	368.6	368.6	368.6	368.6	368.6	2.2	2.2
5°	367.2	366.8	366.3	365.8	365.5	365.3	365.0	17.5	19.7
10°	362.1	361.4	360.8	360.1	359.5	358.9	358.3	34.3	54.0
15°	354.2	353.1	351.9	350.8	350.1	349.3	348.6	49.8	103.8
20°	342.9	341.5	340.1	338.8	337.8	336.9	336.0	63.6	167.3
25°	327.9	326.3	324.6	323.0	321.8	320.6	319.4	74.9	242.3
30°	310.7	308.8	306.8	304.8	303.5	302.2	300.8	83.7	325.9
35°	290.5	288.3	286.2	284.0	282.5	281.0	279.5	89.4	415.4
40°	267.0	264.6	262.3	260.0	258.4	256.8	255.2	91.8	507.2
45°	242.2	239.7	237.3	234.8	233.0	231.3	229.5	91.2	598.4
50°	215.7	213.2	210.6	208.1	206.2	204.3	202.4	87.6	686.0
55°	186.3	184.1	181.9	179.7	177.4	175.1	172.8	80.7	766.6
60°	157.1	154.5	151.9	149.2	146.6	144.0	141.4	70.8	837.5
65°	128.1	125.1	122.0	118.9	116.8	114.6	112.5	59.4	896.9
70°	96.9	93.9	90.9	87.9	85.9	83.8	81.7	45.6	942.5
75°	66.8	64.2	61.7	59.2	57.0	54.7	52.5	31.5	974.0
80°	40.0	39.6	39.2	38.8	35.1	31.4	27.8	19.6	993.6
85°	16.1	14.5	12.9	11.3	10.3	9.3	8.3	6.4	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Lunis 41		Order number: 51DR10MFHCB EAN: 4069025152107							LP number 59234_16	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	24.7	26.4	25.0	26.7	27.0	24.3	26.0	24.7	26.3
	3H	26.3	27.8	26.7	28.1	28.5	25.7	27.3	26.1	27.6
	4H	26.9	28.3	27.3	28.7	29.0	26.2	27.7	26.6	28.0
	6H	27.4	28.7	27.8	29.1	29.4	26.6	27.9	27.0	28.2
	8H	27.6	28.8	28.0	29.2	29.6	26.7	27.9	27.1	28.3
	12H	27.7	28.8	28.1	29.2	29.6	26.7	27.9	27.1	28.2
4H	2H	25.4	26.8	25.8	27.1	27.5	25.1	26.5	25.5	26.9
	3H	27.1	28.3	27.5	28.7	29.1	26.7	27.9	27.1	28.3
	4H	27.9	28.9	28.3	29.3	29.8	27.3	28.4	27.7	28.8
	6H	28.5	29.4	28.9	29.8	30.3	27.7	28.7	28.2	29.1
	8H	28.7	29.5	29.1	30.0	30.4	27.8	28.7	28.3	29.1
	12H	28.8	29.6	29.3	30.0	30.5	27.9	28.7	28.4	29.1
8H	4H	28.1	29.0	28.6	29.4	29.9	27.6	28.5	28.1	28.9
	6H	28.9	29.6	29.4	30.1	30.6	28.2	28.9	28.7	29.4
	8H	29.1	29.8	29.6	30.3	30.8	28.4	29.0	28.9	29.5
	12H	29.3	29.9	29.8	30.4	30.9	28.4	29.0	29.0	29.5
12H	4H	28.2	28.9	28.7	29.4	29.9	27.7	28.4	28.2	28.9
	6H	28.9	29.6	29.4	30.0	30.6	28.3	28.9	28.8	29.4
	8H	29.2	29.8	29.7	30.3	30.8	28.5	29.0	29.0	29.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 173	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	36430.3	36060.0	35689.9	35319.4	35052.1	34785.0	34517.7
50°	35691.3	35271.4	34851.6	34431.7	34116.5	33801.6	33486.6
55°	34548.3	34139.0	33729.4	33320.0	32891.9	32463.5	32035.4
60°	33412.9	32856.7	32300.9	31744.6	31188.6	30632.4	30076.3
65°	32249.4	31470.3	30690.9	29911.7	29381.5	28851.3	28321.0
70°	30117.8	29194.3	28270.7	27347.5	26700.1	26053.0	25405.8
75°	27440.3	26396.9	25354.4	24311.5	23403.8	22496.9	21589.1
80°	24483.7	24235.0	23985.7	23737.0	21498.5	19260.5	17021.9
85°	19605.1	17684.4	15764.9	13844.2	12605.6	11367.0	10127.2

Photometric test report

Family
Lunis 41

Order number: 51DR10MFHCB
EAN: 4069025152107

LP number
59234_16

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

