

Photometric test report

Family
Highbay 21

Order number: 52HN11DB4TLA
EAN: 4069025394705

LP number
59724_88

serial
documentation
27.02.2025



Version primary light control with lens, PMMA, housing, white, for Licross® rail, narrow distribution

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 53000 lm
Power consumption = 286.6 W
Luminous efficacy = 184.9 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2719 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=89 N2=97 N3=99
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 21	Order number: 52HN11DB4TLA EAN: 4069025394705	LP number 59724_88
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0,0° 180,0°	7,5° 172,5° 187,5° 352,5°	15,0° 165,0° 195,0° 345,0°	22,5° 157,5° 202,5° 337,5°	30,0° 150,0° 210,0° 330,0°	37,5° 142,5° 217,5° 322,5°	45,0° 135,0° 225,0° 315,0°
		Luminous intensity in cd/klm					
γ							
0,0°	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5
2,5°	2662.8	2671.1	2671.1	2670.6	2667.6	2663.3	2662.4
5,0°	2502.8	2490.9	2498.0	2494.5	2487.6	2479.1	2473.3
7,5°	2228.4	2233.8	2227.9	2223.2	2214.7	2203.4	2194.2
10,0°	1915.8	1894.8	1902.8	1897.9	1890.8	1880.8	1870.9
12,5°	1554.6	1560.7	1554.3	1552.6	1548.0	1540.2	1531.7
15,0°	1246.2	1237.0	1237.4	1238.4	1237.7	1233.9	1229.0
17,5°	947.1	964.7	959.6	960.0	960.5	959.5	958.4
20,0°	765.0	752.2	754.6	751.6	749.0	747.8	747.5
22,5°	591.2	598.6	590.3	583.2	577.5	573.8	572.1
25,0°	481.4	472.8	470.4	460.9	451.8	445.8	443.1
27,5°	370.5	376.3	371.1	363.9	355.1	347.9	344.8
30,0°	301.2	297.9	295.0	290.6	284.7	279.0	275.2
32,5°	234.8	237.8	234.9	232.8	229.2	225.3	220.4
35,0°	189.2	188.5	187.7	186.9	184.4	180.6	175.3
37,5°	154.0	153.7	151.7	151.0	148.4	144.9	141.0
40,0°	125.7	123.3	123.0	121.9	119.1	115.8	113.2
42,5°	99.2	100.3	99.3	98.6	95.9	92.9	90.7
45,0°	81.4	79.6	79.7	79.0	77.2	74.6	72.7
47,5°	64.2	64.9	64.5	64.0	62.8	60.9	59.5
50,0°	52.5	51.6	51.8	51.7	51.0	49.9	49.1
52,5°	41.7	41.9	41.8	42.1	41.9	41.4	40.9
55,0°	33.9	33.5	34.1	34.8	35.0	35.0	34.7
57,5°	27.1	27.4	28.1	29.2	29.7	29.7	29.6
60,0°	22.3	22.3	23.0	24.6	25.8	25.8	25.5
62,5°	19.0	19.2	19.6	20.7	22.4	22.3	22.0
65,0°	17.0	16.8	17.2	18.3	19.8	19.1	19.1
67,5°	14.7	14.8	14.9	16.1	17.2	16.3	16.1
70,0°	12.8	12.5	12.6	13.8	14.3	13.8	13.9
72,5°	11.3	11.1	10.9	11.6	11.4	11.2	11.7
75,0°	9.7	9.3	8.9	9.6	9.3	9.1	9.3
77,5°	7.4	7.4	7.1	7.5	7.1	6.8	7.1
80,0°	4.9	4.7	4.8	4.8	4.5	4.5	4.8
82,5°	2.2	2.3	2.3	2.4	2.4	2.5	2.7
85,0°	0.8	0.8	0.8	0.8	0.8	0.9	1.0
87,5°	0.4	0.4	0.4	0.4	0.4	0.4	0.4

Photometric test report

Family Highbay 21	Order number: 52HN11DB4TLA EAN: 4069025394705	LP number 59724_88
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	52,5° 127,5° 232,5° 307,5°	60,0° 120,0° 240,0° 300,0°	67,5° 112,5° 247,5° 292,5°	75,0° 105,0° 255,0° 285,0°	82,5° 97,5° 262,5° 277,5°	90,0° 270,0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0,0°	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5	4.1	4.1
2,5°	2661.4	2660.0	2657.7	2657.0	2651.0	2647.2	31.8	35.9
5,0°	2468.0	2461.9	2456.3	2452.9	2444.7	2440.4	59.1	95.0
7,5°	2185.5	2176.0	2168.0	2162.0	2152.6	2148.3	78.5	173.5
10,0°	1860.3	1847.8	1837.7	1831.0	1822.1	1817.6	88.9	262.4
12,5°	1522.0	1510.4	1500.7	1495.5	1488.9	1485.2	90.6	353.0
15,0°	1223.0	1215.3	1207.9	1204.2	1200.8	1197.6	86.8	439.8
17,5°	955.3	949.4	945.6	944.9	945.8	944.0	78.6	518.5
20,0°	745.4	741.8	741.4	743.7	748.0	747.7	70.2	588.6
22,5°	571.4	571.2	573.5	575.9	579.7	580.1	60.8	649.4
25,0°	443.2	444.5	446.3	448.3	449.2	448.8	52.5	701.9
27,5°	344.0	344.5	345.1	346.1	344.9	343.6	44.7	746.7
30,0°	273.7	273.8	273.9	272.4	270.2	268.2	38.5	785.2
32,5°	217.7	217.2	215.9	213.7	211.0	209.4	32.9	818.1
35,0°	172.5	170.5	168.2	166.4	165.0	164.5	27.8	845.9
37,5°	138.1	135.6	133.3	132.0	130.7	130.3	23.7	869.5
40,0°	110.2	108.1	106.1	104.8	103.7	103.1	20.0	889.6
42,5°	88.5	86.8	85.0	83.9	83.2	82.7	16.9	906.5
45,0°	71.2	69.8	68.4	67.3	66.9	66.6	14.2	920.7
47,5°	58.5	57.3	56.0	55.1	54.8	54.6	12.1	932.8
50,0°	48.3	47.1	46.0	45.5	45.1	44.8	10.3	943.0
52,5°	40.2	39.3	38.3	37.7	37.1	36.8	8.7	951.8
55,0°	34.1	33.4	32.5	31.7	31.0	30.7	7.5	959.3
57,5°	29.3	29.0	28.2	27.0	26.3	26.1	6.6	965.9
60,0°	25.7	25.8	24.8	23.5	22.8	22.6	5.8	971.6
62,5°	22.4	22.9	21.8	20.7	20.1	19.9	5.1	976.8
65,0°	19.6	20.2	19.7	18.4	17.9	17.8	4.6	981.4
67,5°	16.7	17.6	17.8	16.4	16.0	16.0	4.1	985.5
70,0°	14.1	15.0	15.6	14.4	14.4	14.6	3.6	989.1
72,5°	11.7	12.4	13.4	12.9	13.2	13.4	3.1	992.3
75,0°	9.5	10.4	12.0	11.4	11.8	11.9	2.7	995.0
77,5°	7.2	8.1	9.6	9.6	10.0	10.2	2.1	997.1
80,0°	5.1	5.7	7.0	7.5	7.6	8.0	1.5	998.6
82,5°	3.0	3.6	4.5	5.0	5.3	5.6	0.9	999.5
85,0°	1.2	1.7	2.3	2.7	3.1	3.3	0.4	999.9
87,5°	0.4	0.4	0.5	0.6	0.8	0.9	0.1	1000.1

Photometric test report

Family Highbay 21		Order number: 52HN11DB4TLA EAN: 4069025394705							LP number 59724_88	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	18.6	19.7	19.0	20.0	20.4	18.0	19.2	18.4	19.5
	3H	19.0	20.0	19.4	20.3	20.7	18.7	19.7	19.1	20.0
	4H	19.2	20.1	19.6	20.5	20.9	19.1	20.0	19.5	20.4
	6H	19.4	20.2	19.8	20.6	21.0	19.5	20.3	19.9	20.7
	8H	19.5	20.2	19.9	20.6	21.0	19.8	20.4	20.2	20.8
	12H	19.5	20.1	19.9	20.5	20.9	19.8	20.4	20.3	20.8
4H	2H	18.8	19.7	19.2	20.0	20.4	18.3	19.2	18.7	19.5
	3H	19.3	20.1	19.8	20.5	20.9	19.1	19.9	19.6	20.3
	4H	19.7	20.3	20.1	20.7	21.2	19.7	20.3	20.1	20.8
	6H	19.9	20.4	20.4	20.9	21.4	20.2	20.8	20.7	21.2
	8H	19.9	20.4	20.4	20.9	21.3	20.4	20.9	20.9	21.3
	12H	19.9	20.3	20.4	20.8	21.3	20.5	20.9	21.0	21.4
8H	4H	19.8	20.2	20.2	20.7	21.2	19.8	20.3	20.3	20.7
	6H	20.0	20.4	20.5	20.9	21.4	20.4	20.8	20.9	21.2
	8H	20.0	20.4	20.6	20.9	21.4	20.6	21.0	21.1	21.4
	12H	20.0	20.3	20.6	20.8	21.4	20.8	21.1	21.3	21.6
12H	4H	19.8	20.2	20.3	20.6	21.1	19.8	20.2	20.3	20.6
	6H	20.0	20.4	20.6	20.9	21.4	20.4	20.7	20.9	21.2
	8H	20.1	20.3	20.6	20.8	21.4	20.6	20.9	21.1	21.4

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264				
C-planes	0,0° 180,0°	10,0° 170,0° 190,0° 350,0°	20,0° 160,0° 200,0° 340,0°	30,0° 150,0° 210,0° 330,0°	40,0° 140,0° 220,0° 320,0°	50,0° 130,0° 230,0° 310,0°	60,0° 120,0° 240,0° 300,0°	70,0° 110,0° 250,0° 290,0°	80,0° 100,0° 260,0° 280,0°	90,0° 270,0°
γ	Luminance in cd/m²									
45,0°	27122.5	26477.6	26442.3	25729.2	24622.1	23887.9	23272.6	22654.8	22333.6	22186.0
50,0°	19226.9	18905.7	18989.0	18691.7	18188.6	17834.3	17268.0	16774.8	16569.6	16411.3
55,0°	13927.7	13795.0	14214.5	14398.1	14334.0	14082.2	13732.6	13244.1	12797.0	12629.1
60,0°	10522.8	10589.6	11350.0	12180.7	12104.6	12081.6	12165.2	11517.0	10836.2	10661.8
65,0°	9499.5	9420.5	9954.9	11014.4	10619.9	10807.6	11270.3	10792.7	10067.8	9948.4
70,0°	8810.1	8618.6	9307.4	9831.2	9481.3	9605.4	10340.3	10600.2	9903.5	10041.3
75,0°	8806.4	8334.0	8633.7	8475.9	8273.0	8556.7	9432.7	11002.3	10675.6	10843.0
80,0°	6647.7	6395.6	6575.9	6164.6	6220.4	6682.3	7782.1	9870.0	10200.0	10804.0
85,0°	2184.5	2128.6	2176.4	2208.8	2442.5	2963.1	4531.2	6532.4	8048.5	8967.7

Photometric test report

Family
Highbay 21

Order number: 52HN11DB4TLA
EAN: 4069025394705

LP number
59724_88

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 21	Order number: 52HN11DB4TLA EAN: 4069025394705	LP number 59724_88
Dimming levels table		environmental temperature: 25°C



Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	53000	286.6
95	240	252	50315	270.4
90	227	250	47747	255.4
85	213	248	44996	239.3
80	200	245	42396	224.4
75	187	243	39781	209.7
70	174	240	37143	195.0
65	161	237	34482	180.2
60	148	234	31789	165.6
55	135	231	29085	151.1
50	123	227	26576	137.7
45	110	223	23848	123.3
40	97	219	21094	108.7
35	85	214	18527	95.5
30	73	208	15952	82.5
25	60	201	13142	68.4
20	48	193	10520	55.4
15	36	182	7886	42.5
10	24	168	5241	29.5
5	12	142	2576	16.0
2	5	110	1018	8.1