

Photometric test report

Family
Highbay 21

Order number: 52HN12DA4FLA03
EAN: 4069025421586

LP number
59723_187

serial
documentation
20.03.2025



Version primary light control with lens, PMMA, housing, white, for Licross® rail, wide distribution, with DALI multisensor

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 14000 lm
Power consumption = 72.1 W
Luminous efficacy = 194.2 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 920 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=90 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 21	Order number: 52HN12DA4FLA03 EAN: 4069025421586	LP number 59723_187
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0,0° 180,0°	7,5° 172,5° 187,5° 352,5°	15,0° 165,0° 195,0° 345,0°	22,5° 157,5° 202,5° 337,5°	30,0° 150,0° 210,0° 330,0°	37,5° 142,5° 217,5° 322,5°	45,0° 135,0° 225,0° 315,0°
		Luminous intensity in cd/klm					
γ							
0,0°	791.0	791.0	791.0	791.0	791.0	791.0	791.0
2,5°	794.7	794.4	795.0	795.0	794.2	792.8	792.0
5,0°	809.1	811.4	809.6	807.9	804.8	800.8	797.1
7,5°	839.0	837.9	835.9	831.3	824.9	817.3	810.1
10,0°	873.0	873.9	866.7	857.6	846.5	834.6	825.0
12,5°	902.2	899.8	892.6	881.8	868.2	853.9	842.5
15,0°	912.4	911.0	905.2	895.6	883.1	869.5	858.7
17,5°	919.8	918.2	913.1	904.4	892.7	879.7	870.3
20,0°	913.1	910.4	906.8	900.7	891.6	880.0	870.9
22,5°	873.0	875.7	872.3	868.8	863.2	854.7	847.2
25,0°	810.1	803.4	805.6	804.0	800.6	794.9	789.9
27,5°	697.5	704.9	702.5	701.8	699.9	697.0	693.3
30,0°	593.2	587.4	585.8	584.9	582.5	580.2	578.9
32,5°	456.1	464.3	462.1	462.0	458.3	454.5	453.6
35,0°	347.7	343.4	342.9	343.5	340.5	335.4	333.2
37,5°	248.6	249.1	246.7	247.3	245.8	241.7	237.9
40,0°	174.7	169.8	171.0	172.0	172.0	169.5	166.1
42,5°	115.9	118.7	117.3	118.1	118.9	118.2	116.5
45,0°	82.2	79.8	80.4	81.1	81.3	81.6	80.9
47,5°	56.5	57.6	57.2	57.7	57.6	57.9	57.5
50,0°	42.4	41.3	41.7	42.1	42.1	42.1	42.0
52,5°	32.0	31.8	31.7	32.2	32.5	32.7	32.7
55,0°	25.6	24.9	25.0	25.6	26.1	26.6	26.9
57,5°	20.6	20.3	20.3	20.8	21.4	22.1	22.4
60,0°	17.2	16.8	16.6	17.2	18.2	18.6	18.9
62,5°	14.5	14.3	13.9	14.3	15.3	15.8	16.0
65,0°	13.1	12.5	12.0	12.2	13.0	13.5	13.7
67,5°	11.1	10.9	10.3	10.4	11.4	11.4	11.5
70,0°	9.4	9.0	8.7	8.7	9.6	9.3	9.5
72,5°	7.6	7.5	7.3	7.2	7.3	7.4	7.8
75,0°	5.9	5.7	5.6	5.7	5.6	5.7	6.1
77,5°	4.1	4.1	4.1	4.2	4.1	4.2	4.5
80,0°	2.6	2.5	2.5	2.7	2.7	2.8	2.9
82,5°	1.1	1.2	1.2	1.3	1.5	1.5	1.7
85,0°	0.5	0.5	0.5	0.5	0.5	0.5	0.6
87,5°	0.2	0.3	0.3	0.3	0.3	0.3	0.3

Photometric test report

Family Highbay 21	Order number: 52HN12DA4FLA03 EAN: 4069025421586	LP number 59723_187
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	52,5° 127,5° 232,5° 307,5°	60,0° 120,0° 240,0° 300,0°	67,5° 112,5° 247,5° 292,5°	75,0° 105,0° 255,0° 285,0°	82,5° 97,5° 262,5° 277,5°	90,0° 270,0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0,0°	791.0	791.0	791.0	791.0	791.0	791.0	1.2	1.2
2,5°	791.3	790.7	790.0	789.4	788.0	786.7	9.5	10.7
5,0°	794.2	790.9	788.1	786.0	783.2	781.9	19.1	29.7
7,5°	803.7	797.3	791.2	786.8	782.5	780.9	29.0	58.7
10,0°	816.7	808.7	801.4	796.1	791.2	788.9	39.5	98.2
12,5°	833.0	825.3	818.6	813.6	808.7	806.6	50.4	148.6
15,0°	850.7	844.9	836.9	832.9	831.6	829.0	61.4	210.0
17,5°	864.2	859.8	856.6	853.6	849.6	847.0	72.4	282.5
20,0°	864.8	860.1	856.9	853.9	850.4	848.0	82.3	364.7
22,5°	841.4	836.7	833.2	829.7	826.8	824.5	89.2	453.9
25,0°	786.0	782.5	779.1	775.6	772.9	771.0	91.6	545.4
27,5°	691.2	689.6	687.4	684.8	682.7	681.4	87.8	633.3
30,0°	578.6	579.1	578.3	576.4	575.3	574.3	79.6	712.9
32,5°	454.5	456.7	457.0	455.4	454.6	454.3	67.4	780.2
35,0°	335.0	337.7	338.0	336.6	336.0	336.2	53.3	833.5
37,5°	239.3	241.4	241.0	239.6	239.1	239.2	40.5	874.0
40,0°	166.2	166.4	164.7	163.3	162.9	163.0	29.6	903.6
42,5°	115.3	113.5	111.1	110.0	109.8	109.7	21.3	924.9
45,0°	79.0	76.9	75.1	74.3	74.0	73.9	15.2	940.1
47,5°	56.0	54.4	53.1	52.3	51.9	51.7	11.2	951.3
50,0°	40.9	39.8	38.8	38.0	37.5	37.4	8.5	959.8
52,5°	31.8	30.8	29.9	29.1	28.8	28.7	6.8	966.6
55,0°	25.9	25.0	24.2	23.4	23.2	23.3	5.6	972.3
57,5°	21.7	20.8	20.1	19.5	19.4	19.6	4.8	977.0
60,0°	18.6	18.0	17.1	16.6	16.8	17.1	4.2	981.2
62,5°	16.0	15.6	14.7	14.4	14.7	15.1	3.6	984.8
65,0°	14.0	13.6	12.8	12.7	13.1	13.5	3.2	988.1
67,5°	12.0	12.1	11.2	11.1	11.6	12.1	2.9	991.0
70,0°	9.8	10.4	9.7	9.7	10.2	10.6	2.5	993.4
72,5°	7.8	8.3	8.3	8.3	8.8	9.1	2.1	995.5
75,0°	6.2	6.3	6.8	6.9	7.3	7.6	1.6	997.1
77,5°	4.6	4.9	5.3	5.5	5.8	6.0	1.3	998.4
80,0°	3.1	3.4	3.7	4.0	4.2	4.4	0.9	999.2
82,5°	1.8	2.1	2.4	2.6	2.8	2.9	0.5	999.7
85,0°	0.7	1.0	1.2	1.3	1.6	1.6	0.2	1000.0
87,5°	0.3	0.3	0.3	0.3	0.4	0.4	0.1	1000.0

Photometric test report

Family Highbay 21			Order number: 52HN12DA4FLA03 EAN: 4069025421586							LP number 59723_187	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	18.1	19.4	18.5	19.7	20.0	17.9	19.2	18.3	19.5	19.8
	3H	18.2	19.2	18.5	19.6	19.9	18.0	19.1	18.4	19.4	19.8
	4H	18.2	19.2	18.6	19.5	19.9	18.1	19.1	18.5	19.4	19.8
	6H	18.1	19.0	18.6	19.4	19.8	18.1	19.0	18.5	19.4	19.8
	8H	18.2	19.0	18.7	19.4	19.8	18.2	19.0	18.7	19.4	19.8
	12H	18.2	18.9	18.6	19.3	19.7	18.2	18.9	18.7	19.3	19.7
4H	2H	18.0	19.0	18.4	19.4	19.7	17.9	18.8	18.2	19.2	19.6
	3H	18.1	18.9	18.5	19.3	19.7	18.0	18.8	18.4	19.2	19.6
	4H	18.1	18.9	18.6	19.3	19.7	18.1	18.8	18.5	19.2	19.7
	6H	18.1	18.7	18.6	19.2	19.7	18.2	18.8	18.6	19.2	19.7
	8H	18.1	18.7	18.6	19.1	19.6	18.2	18.7	18.7	19.2	19.7
	12H	18.1	18.6	18.6	19.0	19.5	18.3	18.7	18.8	19.1	19.6
8H	4H	18.1	18.6	18.6	19.1	19.6	18.0	18.6	18.5	19.0	19.5
	6H	18.1	18.5	18.6	19.0	19.5	18.1	18.6	18.6	19.1	19.6
	8H	18.0	18.4	18.6	18.9	19.5	18.2	18.6	18.7	19.1	19.6
	12H	18.0	18.3	18.6	18.8	19.4	18.2	18.5	18.7	19.0	19.6
12H	4H	18.1	18.5	18.6	19.0	19.5	18.1	18.5	18.6	19.0	19.5
	6H	18.1	18.4	18.6	18.9	19.5	18.2	18.5	18.7	19.0	19.5
	8H	18.1	18.3	18.6	18.9	19.4	18.2	18.5	18.7	19.0	19.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:				L = 426 B = 264		
C-planes	0,0° 180,0°	10,0° 170,0° 190,0° 350,0°	20,0° 160,0° 200,0° 340,0°	30,0° 150,0° 210,0° 330,0°	40,0° 140,0° 220,0° 320,0°	50,0° 130,0° 230,0° 310,0°	60,0° 120,0° 240,0° 300,0°	70,0° 110,0° 250,0° 290,0°	80,0° 100,0° 260,0° 280,0°	90,0° 270,0°
		Luminance in cd/m²								
γ										
45,0°	14476.2	14028.1	14239.0	14318.1	14347.6	14028.5	13530.1	13159.9	13037.9	13002.0
50,0°	8212.1	7985.8	8135.3	8154.0	8152.9	7998.3	7711.1	7454.8	7292.0	7234.9
55,0°	5559.9	5397.2	5517.3	5658.2	5810.2	5698.9	5416.9	5190.6	5049.2	5066.4
60,0°	4277.5	4154.2	4224.2	4522.3	4664.4	4656.7	4485.9	4211.2	4162.2	4249.4
65,0°	3848.9	3625.2	3547.5	3839.5	4016.1	4130.7	4014.5	3744.9	3813.7	3984.1
70,0°	3435.5	3244.6	3139.3	3477.3	3401.2	3528.9	3775.8	3513.7	3653.1	3872.3
75,0°	2825.2	2727.3	2739.9	2712.2	2795.6	2954.8	3045.5	3316.6	3445.0	3655.4
80,0°	1842.4	1783.4	1897.5	1968.5	2001.4	2187.7	2435.9	2754.9	2960.8	3134.9
85,0°	719.9	701.8	713.5	717.0	784.0	988.2	1392.6	1734.1	2126.4	2318.1

Photometric test report

Family
Highbay 21

Order number: 52HN12DA4FLA03
EAN: 4069025421586

LP number
59723_187

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 21	Order number: 52HN12DA4FLA03 EAN: 4069025421586	LP number 59723_187
Dimming levels table		environmental temperature: 25°C 

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	14000	72.1
95	241	252	13303	68.3
90	228	250	12606	64.7
85	215	248	11901	61.0
80	202	246	11197	57.4
75	189	243	10494	53.5
70	176	241	9782	49.9
65	164	238	9126	46.6
60	151	235	8413	42.9
55	138	232	7695	39.3
50	125	228	6976	35.7
45	113	224	6313	32.4
40	100	220	5591	28.8
35	88	215	4919	25.5
30	75	209	4192	22.0
25	63	203	3520	18.7
20	50	194	2785	15.1
15	38	184	2109	11.9
10	25	169	1374	8.4
5	13	145	690	4.9
2	5	110	235	2.5