

Photometric test report

Family
Highbay 21

Order number: 52HN12DA3FLA
EAN: 4069025445360

LP number
59723_229



Version primary light control with lens, PMMA, housing, white, wide distribution
Lamps LED 3000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting AC-mode
Rated values Net luminous flux = 12810 lm
Power consumption = 72.1 W
Luminous efficacy = 177.7 lm/W

serial
documentation
24.04.2025


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 920 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=90 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 21	Order number: 52HN12DA3FLA EAN: 4069025445360	LP number 59723_229
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0,0° 180,0°	7,5° 172,5° 187,5° 352,5°	15,0° 165,0° 195,0° 345,0°	22,5° 157,5° 202,5° 337,5°	30,0° 150,0° 210,0° 330,0°	37,5° 142,5° 217,5° 322,5°	45,0° 135,0° 225,0° 315,0°
		Luminous intensity in cd/klm					
γ							
0,0°	791.0	791.0	791.0	791.0	791.0	791.0	791.0
2,5°	794.7	794.4	795.0	795.0	794.2	792.8	792.0
5,0°	809.1	811.4	809.6	807.9	804.8	800.8	797.1
7,5°	839.0	837.9	835.9	831.3	824.9	817.3	810.1
10,0°	873.0	873.9	866.7	857.6	846.5	834.6	825.0
12,5°	902.2	899.8	892.6	881.8	868.2	853.9	842.5
15,0°	912.4	911.0	905.2	895.6	883.1	869.5	858.7
17,5°	919.8	918.2	913.1	904.4	892.7	879.7	870.3
20,0°	913.1	910.4	906.8	900.7	891.6	880.0	870.9
22,5°	873.0	875.7	872.3	868.8	863.2	854.7	847.2
25,0°	810.1	803.4	805.6	804.0	800.6	794.9	789.9
27,5°	697.5	704.9	702.5	701.8	699.9	697.0	693.3
30,0°	593.2	587.4	585.8	584.9	582.5	580.2	578.9
32,5°	456.1	464.3	462.1	462.0	458.3	454.5	453.6
35,0°	347.7	343.4	342.9	343.5	340.5	335.4	333.2
37,5°	248.6	249.1	246.7	247.3	245.8	241.7	237.9
40,0°	174.7	169.8	171.0	172.0	172.0	169.5	166.1
42,5°	115.9	118.7	117.3	118.1	118.9	118.2	116.5
45,0°	82.2	79.8	80.4	81.1	81.3	81.6	80.9
47,5°	56.5	57.6	57.2	57.7	57.6	57.9	57.5
50,0°	42.4	41.3	41.7	42.1	42.1	42.1	42.0
52,5°	32.0	31.8	31.7	32.2	32.5	32.7	32.7
55,0°	25.6	24.9	25.0	25.6	26.1	26.6	26.9
57,5°	20.6	20.3	20.3	20.8	21.4	22.1	22.4
60,0°	17.2	16.8	16.6	17.2	18.2	18.6	18.9
62,5°	14.5	14.3	13.9	14.3	15.3	15.8	16.0
65,0°	13.1	12.5	12.0	12.2	13.0	13.5	13.7
67,5°	11.1	10.9	10.3	10.4	11.4	11.4	11.5
70,0°	9.4	9.0	8.7	8.7	9.6	9.3	9.5
72,5°	7.6	7.5	7.3	7.2	7.3	7.4	7.8
75,0°	5.9	5.7	5.6	5.7	5.6	5.7	6.1
77,5°	4.1	4.1	4.1	4.2	4.1	4.2	4.5
80,0°	2.6	2.5	2.5	2.7	2.7	2.8	2.9
82,5°	1.1	1.2	1.2	1.3	1.5	1.5	1.7
85,0°	0.5	0.5	0.5	0.5	0.5	0.5	0.6
87,5°	0.2	0.3	0.3	0.3	0.3	0.3	0.3

Photometric test report

Family Highbay 21	Order number: 52HN12DA3FLA EAN: 4069025445360	LP number 59723_229
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	52,5° 127,5° 232,5° 307,5°	60,0° 120,0° 240,0° 300,0°	67,5° 112,5° 247,5° 292,5°	75,0° 105,0° 255,0° 285,0°	82,5° 97,5° 262,5° 277,5°	90,0° 270,0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0,0°	791.0	791.0	791.0	791.0	791.0	791.0	1.2	1.2
2,5°	791.3	790.7	790.0	789.4	788.0	786.7	9.5	10.7
5,0°	794.2	790.9	788.1	786.0	783.2	781.9	19.1	29.7
7,5°	803.7	797.3	791.2	786.8	782.5	780.9	29.0	58.7
10,0°	816.7	808.7	801.4	796.1	791.2	788.9	39.5	98.2
12,5°	833.0	825.3	818.6	813.6	808.7	806.6	50.4	148.6
15,0°	850.7	844.9	836.9	832.9	831.6	829.0	61.4	210.0
17,5°	864.2	859.8	856.6	853.6	849.6	847.0	72.4	282.5
20,0°	864.8	860.1	856.9	853.9	850.4	848.0	82.3	364.7
22,5°	841.4	836.7	833.2	829.7	826.8	824.5	89.2	453.9
25,0°	786.0	782.5	779.1	775.6	772.9	771.0	91.6	545.4
27,5°	691.2	689.6	687.4	684.8	682.7	681.4	87.8	633.3
30,0°	578.6	579.1	578.3	576.4	575.3	574.3	79.6	712.9
32,5°	454.5	456.7	457.0	455.4	454.6	454.3	67.4	780.2
35,0°	335.0	337.7	338.0	336.6	336.0	336.2	53.3	833.5
37,5°	239.3	241.4	241.0	239.6	239.1	239.2	40.5	874.0
40,0°	166.2	166.4	164.7	163.3	162.9	163.0	29.6	903.6
42,5°	115.3	113.5	111.1	110.0	109.8	109.7	21.3	924.9
45,0°	79.0	76.9	75.1	74.3	74.0	73.9	15.2	940.1
47,5°	56.0	54.4	53.1	52.3	51.9	51.7	11.2	951.3
50,0°	40.9	39.8	38.8	38.0	37.5	37.4	8.5	959.8
52,5°	31.8	30.8	29.9	29.1	28.8	28.7	6.8	966.6
55,0°	25.9	25.0	24.2	23.4	23.2	23.3	5.6	972.3
57,5°	21.7	20.8	20.1	19.5	19.4	19.6	4.8	977.0
60,0°	18.6	18.0	17.1	16.6	16.8	17.1	4.2	981.2
62,5°	16.0	15.6	14.7	14.4	14.7	15.1	3.6	984.8
65,0°	14.0	13.6	12.8	12.7	13.1	13.5	3.2	988.1
67,5°	12.0	12.1	11.2	11.1	11.6	12.1	2.9	991.0
70,0°	9.8	10.4	9.7	9.7	10.2	10.6	2.5	993.4
72,5°	7.8	8.3	8.3	8.3	8.8	9.1	2.1	995.5
75,0°	6.2	6.3	6.8	6.9	7.3	7.6	1.6	997.1
77,5°	4.6	4.9	5.3	5.5	5.8	6.0	1.3	998.4
80,0°	3.1	3.4	3.7	4.0	4.2	4.4	0.9	999.2
82,5°	1.8	2.1	2.4	2.6	2.8	2.9	0.5	999.7
85,0°	0.7	1.0	1.2	1.3	1.6	1.6	0.2	1000.0
87,5°	0.3	0.3	0.3	0.3	0.4	0.4	0.1	1000.0

Photometric test report

Family Highbay 21		Order number: 52HN12DA3FLA EAN: 4069025445360							LP number 59723_229	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
2H	x									
	y									
	2H	17.8	19.0	18.2	19.4	19.7	17.6	18.9	18.0	19.2
	3H	17.8	18.9	18.2	19.3	19.6	17.7	18.8	18.1	19.1
	4H	17.9	18.8	18.3	19.2	19.6	17.8	18.8	18.2	19.1
	6H	17.8	18.7	18.2	19.1	19.5	17.8	18.7	18.2	19.1
4H	8H	17.9	18.7	18.4	19.0	19.5	17.9	18.7	18.4	19.0
	12H	17.9	18.6	18.3	19.0	19.4	17.9	18.6	18.4	19.0
	2H	17.7	18.7	18.1	19.1	19.4	17.5	18.5	17.9	18.9
	3H	17.8	18.6	18.2	19.0	19.4	17.7	18.5	18.1	18.9
	4H	17.8	18.6	18.3	19.0	19.4	17.8	18.5	18.2	18.9
	6H	17.8	18.4	18.3	18.9	19.3	17.9	18.5	18.3	18.9
8H	8H	17.8	18.3	18.3	18.8	19.3	17.9	18.4	18.4	18.9
	12H	17.8	18.2	18.3	18.7	19.2	17.9	18.4	18.4	18.8
	4H	17.8	18.3	18.3	18.8	19.3	17.7	18.3	18.2	18.7
	6H	17.8	18.2	18.3	18.7	19.2	17.8	18.3	18.3	18.8
	8H	17.7	18.1	18.2	18.6	19.2	17.9	18.3	18.4	18.7
	12H	17.7	18.0	18.3	18.5	19.1	17.9	18.2	18.4	18.7
12H	4H	17.8	18.2	18.3	18.7	19.2	17.8	18.2	18.2	18.6
	6H	17.8	18.1	18.3	18.6	19.2	17.8	18.2	18.4	18.7
	8H	17.7	18.0	18.3	18.5	19.1	17.9	18.2	18.4	18.7
	2H	17.8	18.2	18.3	18.7	19.2	17.8	18.2	18.2	18.6
	3H	17.8	18.2	18.3	18.7	19.2	17.8	18.2	18.2	18.6
	4H	17.8	18.2	18.3	18.7	19.2	17.8	18.2	18.2	18.6

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 426 B = 264				
C-planes	0,0° 180,0°	10,0° 170,0° 190,0° 350,0°	20,0° 160,0° 200,0° 340,0°	30,0° 150,0° 210,0° 330,0°	40,0° 140,0° 220,0° 320,0°	50,0° 130,0° 230,0° 310,0°	60,0° 120,0° 240,0° 300,0°	70,0° 110,0° 250,0° 290,0°	80,0° 100,0° 260,0° 280,0°	90,0° 270,0°
γ	Luminance in cd/m²									
45,0°	13245.7	12835.7	13028.7	13101.1	13128.1	12836.1	12380.1	12041.3	11929.6	11896.8
50,0°	7514.1	7307.0	7443.8	7460.9	7459.9	7318.4	7055.6	6821.1	6672.2	6619.9
55,0°	5087.3	4938.5	5048.3	5177.3	5316.3	5214.5	4956.5	4749.4	4620.0	4635.7
60,0°	3913.9	3801.1	3865.1	4137.9	4267.9	4260.9	4104.6	3853.2	3808.4	3888.2
65,0°	3521.8	3317.1	3245.9	3513.2	3674.7	3779.6	3673.3	3426.6	3489.5	3645.5
70,0°	3143.5	2968.8	2872.5	3181.8	3112.1	3228.9	3454.9	3215.1	3342.6	3543.1
75,0°	2585.1	2495.5	2507.0	2481.7	2557.9	2703.6	2786.6	3034.7	3152.2	3344.7
80,0°	1685.8	1631.8	1736.2	1801.2	1831.2	2001.8	2228.9	2520.7	2709.1	2868.4
85,0°	658.7	642.1	652.9	656.1	717.3	904.2	1274.2	1586.7	1945.7	2121.1

Photometric test report

Family
Highbay 21

Order number: 52HN12DA3FLA
EAN: 4069025445360

LP number
59723_229

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 21	Order number: 52HN12DA3FLA EAN: 4069025445360	LP number 59723_229
Dimming levels table environmental temperature: 25°C		sit eco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	12810	72.1
95	241	252	12173	68.3
90	228	250	11537	64.7
85	215	248	10893	61.0
80	202	246	10251	57.4
75	189	243	9608	53.5
70	176	241	8957	49.9
65	163	238	8307	46.3
60	151	235	7706	42.9
55	138	232	7049	39.3
50	125	228	6391	35.7
45	113	224	5785	32.4
40	100	220	5124	28.8
35	88	215	4508	25.5
30	75	209	3843	22.0
25	63	203	3227	18.7
20	50	194	2554	15.1
15	38	184	1934	11.9
10	25	169	1260	8.4
5	13	145	633	4.9
2	5	110	216	2.5