




Photometric test report

Family Lunis 41	Order number: 51DR107DHBA EAN: 4058352509937	LP number 59234_4
	Version	diffuse cover, extremely wide distribution, adjustable color temperature: 4000 K 5700 K
	Lamps	LED 5700 K CRI ≥ 80
	Controlgear	ECG
	Setting	factory setting: colour temperature 5700K
	Rated values	Net luminous flux = 1360 lm Power consumption = 15.0 W Luminous efficacy = 90.7 lm/W
		serial documentation 07.12.2021
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 369 cd/klm**



Classifications	
DIN 5040	A 4 0
CIE	N1=49 N2=80 N3=96 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 41	Order number: 51DR107DHBA EAN: 4058352509937	LP number 59234_4
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	368.6	368.6	368.6	368.6	368.6	368.6	368.6	2.2	2.2
5°	367.2	366.8	366.3	365.8	365.5	365.3	365.0	17.5	19.7
10°	362.1	361.4	360.8	360.1	359.5	358.9	358.3	34.3	54.0
15°	354.2	353.1	351.9	350.8	350.1	349.3	348.6	49.8	103.8
20°	342.9	341.5	340.1	338.8	337.8	336.9	336.0	63.6	167.3
25°	327.9	326.3	324.6	323.0	321.8	320.6	319.4	74.9	242.3
30°	310.7	308.8	306.8	304.8	303.5	302.2	300.8	83.7	325.9
35°	290.5	288.3	286.2	284.0	282.5	281.0	279.5	89.4	415.4
40°	267.0	264.6	262.3	260.0	258.4	256.8	255.2	91.8	507.2
45°	242.2	239.7	237.3	234.8	233.0	231.3	229.5	91.2	598.4
50°	215.7	213.2	210.6	208.1	206.2	204.3	202.4	87.6	686.0
55°	186.3	184.1	181.9	179.7	177.4	175.1	172.8	80.7	766.6
60°	157.1	154.5	151.9	149.2	146.6	144.0	141.4	70.8	837.5
65°	128.1	125.1	122.0	118.9	116.8	114.6	112.5	59.4	896.9
70°	96.9	93.9	90.9	87.9	85.9	83.8	81.7	45.6	942.5
75°	66.8	64.2	61.7	59.2	57.0	54.7	52.5	31.5	974.0
80°	40.0	39.6	39.2	38.8	35.1	31.4	27.8	19.6	993.6
85°	16.1	14.5	12.9	11.3	10.3	9.3	8.3	6.4	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Lunis 41	Order number: 51DR107DHBA EAN: 4058352509937	LP number 59234_4
---------------------------	---	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	24.8	26.5	25.2	26.8	27.1	24.5	26.2	24.8	26.5	26.8
	3H	26.4	27.9	26.8	28.3	28.6	25.9	27.4	26.3	27.7	28.1
	4H	27.0	28.5	27.4	28.8	29.2	26.4	27.8	26.8	28.2	28.5
	6H	27.5	28.8	27.9	29.2	29.6	26.7	28.0	27.1	28.4	28.8
	8H	27.7	28.9	28.1	29.3	29.7	26.8	28.0	27.2	28.4	28.8
	12H	27.8	29.0	28.2	29.4	29.8	26.8	28.0	27.3	28.4	28.8
4H	2H	25.5	26.9	25.9	27.3	27.7	25.2	26.7	25.6	27.0	27.4
	3H	27.3	28.5	27.7	28.9	29.3	26.8	28.0	27.2	28.4	28.8
	4H	28.0	29.1	28.4	29.5	29.9	27.4	28.5	27.9	28.9	29.3
	6H	28.6	29.5	29.1	30.0	30.4	27.9	28.8	28.3	29.2	29.7
	8H	28.8	29.7	29.3	30.1	30.6	28.0	28.8	28.4	29.3	29.8
	12H	29.0	29.7	29.4	30.2	30.7	28.0	28.8	28.5	29.3	29.8
8H	4H	28.3	29.1	28.7	29.6	30.1	27.8	28.6	28.2	29.1	29.5
	6H	29.0	29.7	29.5	30.2	30.7	28.3	29.0	28.8	29.5	30.0
	8H	29.3	29.9	29.8	30.4	30.9	28.5	29.1	29.0	29.6	30.1
	12H	29.5	30.0	30.0	30.5	31.0	28.6	29.1	29.1	29.6	30.2
12H	4H	28.3	29.1	28.8	29.5	30.0	27.8	28.6	28.3	29.0	29.5
	6H	29.1	29.7	29.6	30.2	30.7	28.4	29.0	28.9	29.5	30.0
	8H	29.4	29.9	29.9	30.4	30.9	28.6	29.2	29.1	29.7	30.2

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	D = 125
------------------------	---	--------------------------------------	----------------

C-planes	γ	0° 180°	15°	30°	45°	60°	75°	90°	
			165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°	270°	
		Luminance in cd/m²							
45°		37960.7	37574.8	37189.1	36803.1	36524.6	36246.3	35967.8	
50°		37190.7	36753.1	36315.7	35878.1	35549.7	35221.6	34893.3	
55°		35999.6	35573.1	35146.3	34719.7	34273.6	33827.3	33381.1	
60°		34816.5	34236.9	33657.8	33078.2	32498.8	31919.2	31339.8	
65°		33604.1	32792.3	31980.1	31168.3	30615.8	30063.2	29510.7	
70°		31383.0	30420.7	29458.3	28496.3	27821.7	27147.4	26473.1	
75°		28593.0	27505.8	26419.5	25332.8	24386.9	23441.9	22496.1	
80°		25512.2	25253.1	24993.3	24734.2	22401.6	20069.6	17736.9	
85°		20428.7	18427.3	16427.1	14425.7	13135.1	11844.5	10552.6	

Photometric test report

Family Lunis 41	Order number: 51DR107DHBA EAN: 4058352509937	LP number 59234_4
---------------------------	---	-----------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

