

Photometric test report

Family
Licross® 21 Recessed

Order number: 52TL12CN49XG
EAN: 4058352890745

LP number
59101_306



Version cover frosted, wide distribution, high visual comfort
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-Multilumen CLOi
Rated values Net luminous flux = 9260 lm
 Power consumption = 49.9 W
 Luminous efficacy = 185.6 lm/W

serial
documentation
17.08.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 671 cd/klm



Classifications

DIN 5040 A 6 0
 CIE N1=72 N2=92 N3=99
 N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Recessed	Order number: 52TL12CN49XG EAN: 4058352890745	LP number 59101_306
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	668.4	668.4	668.4	668.4	668.4	668.4	668.4	4.0	4.0
5°	667.5	664.4	657.4	655.8	655.7	654.2	654.4	31.4	35.4
10°	670.7	665.0	649.1	636.1	625.3	618.7	618.1	60.9	96.3
15°	666.2	657.2	632.9	612.0	594.0	578.5	575.5	87.4	183.7
20°	644.4	632.9	606.9	585.4	554.6	522.7	512.3	108.8	292.5
25°	604.1	590.6	566.7	541.2	494.5	444.9	427.0	121.8	414.2
30°	532.4	517.7	496.3	466.1	413.9	359.9	340.6	122.9	537.1
35°	425.0	409.7	387.0	361.9	325.4	286.0	271.1	111.0	648.1
40°	313.4	295.8	270.7	255.1	246.8	229.4	218.8	91.8	739.9
45°	219.2	200.3	175.7	171.1	181.8	184.7	175.5	71.8	811.7
50°	149.7	132.6	112.6	116.3	133.0	145.6	134.9	54.8	866.5
55°	102.7	89.1	74.7	81.5	98.1	107.9	98.1	41.3	907.7
60°	72.4	62.1	51.3	58.3	71.8	76.5	71.0	31.0	938.7
65°	52.1	44.3	35.9	41.6	51.4	54.2	52.1	23.1	961.9
70°	37.6	31.7	24.7	29.1	35.6	38.4	38.3	16.9	978.8
75°	26.0	21.3	16.2	19.0	22.9	25.9	26.8	11.6	990.4
80°	16.1	12.5	9.2	10.4	12.6	14.8	15.7	6.8	997.3
85°	7.0	5.4	3.8	4.1	4.8	5.7	5.8	2.7	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 21 Recessed	Order number: 52TL12CN49XG EAN: 4058352890745	LP number 59101_306
--------------------------------	--	------------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	21.5	22.9	21.8	23.2	23.5	21.4	22.9	21.8	23.2	23.5
	3H	22.1	23.3	22.5	23.7	24.0	22.2	23.5	22.6	23.8	24.2
	4H	22.4	23.5	22.7	23.9	24.2	22.5	23.7	22.9	24.1	24.4
	6H	22.6	23.7	23.0	24.0	24.4	22.8	23.9	23.2	24.2	24.6
	8H	22.8	23.7	23.2	24.1	24.5	22.9	23.9	23.4	24.3	24.7
	12H	22.8	23.7	23.3	24.1	24.5	23.0	23.9	23.4	24.3	24.7
4H	2H	21.6	22.8	22.0	23.2	23.6	21.6	22.8	22.0	23.1	23.5
	3H	22.3	23.3	22.7	23.7	24.1	22.6	23.6	23.0	23.9	24.4
	4H	22.7	23.5	23.1	23.9	24.4	23.0	23.9	23.5	24.3	24.7
	6H	23.0	23.7	23.4	24.2	24.6	23.4	24.1	23.8	24.6	25.0
	8H	23.1	23.8	23.6	24.2	24.7	23.5	24.2	24.0	24.6	25.1
	12H	23.2	23.8	23.7	24.3	24.8	23.6	24.2	24.1	24.6	25.1
8H	4H	22.7	23.4	23.2	23.9	24.3	23.1	23.7	23.5	24.2	24.7
	6H	23.1	23.6	23.6	24.1	24.6	23.5	24.1	24.0	24.5	25.0
	8H	23.2	23.7	23.7	24.2	24.7	23.7	24.2	24.2	24.6	25.2
	12H	23.4	23.8	23.9	24.3	24.8	23.8	24.2	24.3	24.7	25.2
12H	4H	22.8	23.3	23.2	23.8	24.3	23.1	23.7	23.6	24.1	24.6
	6H	23.1	23.6	23.6	24.1	24.6	23.5	24.0	24.0	24.5	25.0
	8H	23.3	23.7	23.8	24.2	24.7	23.7	24.1	24.2	24.6	25.1

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1500 B = 58	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	32997.9	30157.3	26443.1	25760.0	27365.2	27801.8	26420.8
50°	24785.8	21952.3	18646.8	19258.7	22022.1	24112.3	22330.1
55°	19051.4	16538.8	13865.2	15128.0	18200.2	20031.6	18195.6
60°	15408.2	13226.5	10922.1	12419.9	15277.3	16287.2	15109.6
65°	13121.9	11168.3	9053.5	10483.0	12957.0	13639.0	13109.3
70°	11693.4	9859.8	7687.9	9041.6	11068.2	11950.4	11920.2
75°	10691.8	8758.2	6675.7	7804.5	9421.9	10634.7	11017.9
80°	9861.7	7688.2	5656.3	6402.2	7739.7	9101.6	9649.0
85°	8552.2	6587.3	4651.6	5015.6	5896.1	6904.8	7129.5

Photometric test report

Family
Licross® 21 Recessed

Order number: **52TL12CN49XG**
EAN: **4058352890745**

LP number
59101_306

Luminance values in cd/m²

γ 65°

γ 70°


γ 75°

γ 80°

γ 85°

sit

eco



Photometric test report

Family Licross® 21 Recessed	Order number: 52TL12CN49XG EAN: 4058352890745	LP number 59101_306
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	9260	49.9	60.5	55.2
2	A	C	F	8820	47.3	56.9	52.1
3	A	D	E	8300	44.4	53.4	48.9
4	A	D	F	7770	41.4	49.5	45.4
5	B	C	E	7230	38.4	45.6	42.0
6	B	C	F	6690	35.3	42.2	38.8
7	B	D	E	6230	32.8	39.2	36.0
8	B	D	F	5680	29.9	35.3	32.6