

Photometric test report

Family
Licross® 21 Recessed

Order number: 52TL1EDE445GD
EAN: 4069025365521

LP number
59263_195



Version cover frosted, elliptical narrow distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting DC mode (central or group accumulator) initial emergency light level
Rated values Net luminous flux = 750 lm
 Power consumption = 5.3 W
 Luminous efficacy = 141.5 lm/W

serial
documentation
27.09.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 1670 cd/klm



Classifications

DIN 5040 A 7 0
 CIE N1=85 N2=95 N3=99
 N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Recessed	Order number: 52TL1EDE445GD EAN: 4069025365521	LP number 59263_195
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	10.0	10.0
5°	1493.3	1495.6	1516.6	1565.9	1616.3	1649.8	1662.9	75.0	85.0
10°	1088.5	1106.7	1175.0	1303.4	1460.6	1586.1	1636.2	126.8	211.8
15°	678.3	712.7	825.0	1006.5	1239.9	1474.8	1578.7	151.0	362.9
20°	362.1	388.9	492.0	707.6	980.6	1275.8	1432.9	148.2	511.0
25°	217.8	231.1	285.8	436.7	705.9	972.9	1137.5	127.8	638.8
30°	151.3	158.5	185.3	264.1	455.8	646.3	761.7	99.0	737.8
35°	95.4	107.0	131.3	171.8	268.4	391.1	463.8	70.7	808.5
40°	57.7	64.5	93.9	120.6	157.9	239.7	291.4	50.0	858.5
45°	43.5	45.9	58.2	86.3	99.5	145.4	176.9	35.2	893.7
50°	37.7	39.0	42.8	61.0	68.3	89.3	109.1	26.2	919.9
55°	34.6	35.0	36.7	43.5	50.5	59.6	73.7	20.9	940.8
60°	30.2	31.1	32.8	34.2	38.6	42.0	53.5	17.5	958.3
65°	23.9	25.4	29.1	28.1	30.1	30.8	41.3	14.6	972.8
70°	17.0	18.4	22.5	23.3	23.4	22.7	30.8	11.5	984.3
75°	10.9	12.0	16.2	17.9	17.4	15.7	20.7	8.4	992.7
80°	6.2	6.7	9.0	10.7	11.0	9.3	11.6	5.0	997.7
85°	3.1	3.3	4.2	5.0	4.8	3.9	4.2	2.3	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 21 Recessed	Order number: 52TL1EDE445GD EAN: 4069025365521	LP number 59263_195
--------------------------------	---	------------------------

UGR-Table		Standard room							siteco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	8.6	9.8	8.9	10.1	10.4	13.6	14.8	13.9	15.1	15.4
	3H	9.7	10.8	10.1	11.2	11.5	14.1	15.2	14.5	15.5	15.9
	4H	10.1	11.1	10.5	11.5	11.9	14.4	15.4	14.8	15.7	16.1
	6H	10.3	11.3	10.7	11.6	12.0	14.6	15.5	15.1	15.9	16.3
	8H	10.5	11.3	10.9	11.7	12.1	14.8	15.5	15.2	15.9	16.3
	12H	10.5	11.3	11.0	11.7	12.1	14.8	15.5	15.3	15.9	16.3
4H	2H	9.4	10.3	9.8	10.7	11.1	13.5	14.6	13.9	14.9	15.3
	3H	10.8	11.6	11.2	12.0	12.4	14.3	15.1	14.7	15.5	15.9
	4H	11.3	12.1	11.8	12.5	12.9	14.6	15.4	15.1	15.8	16.2
	6H	11.6	12.3	12.1	12.7	13.2	14.9	15.6	15.4	16.0	16.5
	8H	11.7	12.3	12.2	12.7	13.2	15.1	15.6	15.6	16.1	16.5
	12H	11.8	12.3	12.3	12.8	13.3	15.1	15.6	15.6	16.0	16.5
8H	4H	11.8	12.3	12.3	12.8	13.3	14.7	15.3	15.2	15.8	16.2
	6H	12.3	12.7	12.8	13.2	13.7	15.1	15.6	15.6	16.1	16.6
	8H	12.4	12.8	12.9	13.3	13.8	15.3	15.7	15.8	16.2	16.7
	12H	12.5	12.9	13.0	13.4	13.9	15.4	15.7	15.9	16.2	16.7
12H	4H	11.8	12.3	12.3	12.8	13.3	14.7	15.2	15.2	15.7	16.2
	6H	12.3	12.7	12.9	13.2	13.7	15.1	15.5	15.6	16.0	16.6
	8H	12.5	12.9	13.1	13.4	13.9	15.3	15.7	15.8	16.2	16.7

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 750 B = 58	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	1060.4	1118.6	1417.9	2103.7	2426.9	3545.3	4314.3
50°	1012.3	1045.6	1147.9	1637.1	1832.3	2396.1	2927.3
55°	1038.9	1051.5	1103.8	1306.8	1518.5	1792.3	2216.0
60°	1039.9	1074.0	1131.6	1180.2	1330.8	1447.6	1844.6
65°	976.2	1035.2	1187.9	1146.8	1229.2	1255.7	1685.5
70°	855.8	925.7	1133.2	1175.7	1179.4	1142.7	1554.1
75°	723.2	800.0	1078.8	1194.6	1160.1	1048.6	1378.2
80°	611.0	660.8	894.2	1058.1	1089.2	922.2	1153.7
85°	618.2	659.3	839.0	994.5	952.7	770.3	825.5

Photometric test report

Family Licross® 21 Recessed	Order number: 52TL1EDE445GD EAN: 4069025365521	LP number 59263_195	
Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°			siteco

