


Photometric test report

Family Licross® 11 Recessed	Order number: 51TE12DN4AXG3S4 EAN: 4058352934784	LP number 58637_198
	Version cover frosted, wide distribution, high visual comfort Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting emergency light operation: 3 h Rated values Net luminous flux = 1010 lm Power consumption = 6.7 W Luminous efficacy = 150.7 lm/W	serial documentation 29.09.2023 

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 498 cd/klm**



Classifications	
DIN 5040	A 5 0
CIE	N1=67 N2=92 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE12DN4AXG3S4 EAN: 4058352934784	LP number 58637_198
--	---	--------------------------------------

sITeco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	482.3	482.3	482.3	482.3	482.3	482.3	482.3	2.9	2.9
5°	485.4	482.8	478.2	477.5	477.4	475.9	475.7	22.9	25.8
10°	492.7	488.2	477.9	471.3	467.6	465.9	466.0	45.2	71.0
15°	493.2	486.1	471.9	467.9	471.0	473.7	476.3	67.5	138.5
20°	482.5	473.5	462.5	471.9	487.1	492.8	494.9	89.9	228.4
25°	456.4	447.1	449.2	479.4	497.6	491.1	485.8	109.5	337.8
30°	414.9	406.8	427.0	475.1	479.0	447.1	431.1	121.4	459.2
35°	364.2	358.0	387.7	436.7	420.7	368.9	346.8	122.0	581.2
40°	300.5	296.3	322.5	357.9	336.0	284.8	262.9	110.4	691.6
45°	229.2	226.3	238.5	259.8	247.2	211.8	193.4	90.1	781.7
50°	162.3	159.3	161.6	173.6	174.5	155.2	138.5	68.2	849.9
55°	112.5	108.0	105.1	112.3	121.6	110.9	97.2	49.6	899.5
60°	78.7	73.1	68.3	73.1	83.7	77.4	68.5	35.5	935.0
65°	56.0	50.2	45.0	48.4	56.8	54.5	49.6	25.5	960.5
70°	39.5	34.5	29.5	32.1	37.8	38.5	36.6	18.1	978.6
75°	26.0	22.0	18.4	20.2	23.9	25.9	25.8	12.0	990.6
80°	14.9	12.2	9.9	10.8	13.0	14.8	15.3	6.8	997.4
85°	5.4	4.3	3.6	4.0	4.7	5.6	5.8	2.5	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE12DN4AXG3S4 EAN: 4058352934784	LP number 58637_198
---------------------------------------	---	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	14.7	16.1	15.0	16.5	16.8	14.8	16.2	15.1	16.5	16.9
	3H	15.2	16.5	15.6	16.8	17.2	15.3	16.6	15.7	17.0	17.3
	4H	15.4	16.6	15.8	17.0	17.4	15.5	16.8	15.9	17.1	17.5
	6H	15.6	16.7	16.0	17.1	17.5	15.7	16.9	16.1	17.2	17.6
	8H	15.7	16.7	16.1	17.1	17.5	15.9	16.9	16.3	17.3	17.7
	12H	15.7	16.7	16.1	17.1	17.5	15.9	16.8	16.3	17.2	17.6
4H	2H	14.9	16.1	15.3	16.5	16.8	15.0	16.2	15.4	16.6	16.9
	3H	15.5	16.5	15.9	16.9	17.3	15.7	16.7	16.1	17.1	17.5
	4H	15.8	16.7	16.2	17.1	17.5	16.0	16.9	16.5	17.3	17.8
	6H	16.0	16.8	16.5	17.2	17.7	16.3	17.1	16.8	17.5	18.0
	8H	16.1	16.8	16.5	17.2	17.7	16.4	17.1	16.9	17.6	18.0
	12H	16.1	16.8	16.6	17.2	17.7	16.5	17.1	17.0	17.6	18.0
8H	4H	15.8	16.6	16.3	17.0	17.5	16.1	16.8	16.5	17.2	17.7
	6H	16.1	16.7	16.6	17.2	17.7	16.4	17.0	16.9	17.5	18.0
	8H	16.2	16.7	16.7	17.2	17.7	16.5	17.1	17.0	17.5	18.1
	12H	16.3	16.7	16.8	17.2	17.7	16.6	17.1	17.2	17.6	18.1
12H	4H	15.9	16.5	16.3	16.9	17.4	16.1	16.7	16.6	17.2	17.7
	6H	16.1	16.6	16.6	17.1	17.6	16.4	16.9	16.9	17.4	17.9
	8H	16.2	16.6	16.7	17.1	17.7	16.6	17.0	17.1	17.5	18.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500 B = 58
------------------------	---	--------------------------------------	----------------------------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		3762.2	3715.4	3915.8	4265.2	4057.9	3478.0	3174.4	
50°		2931.3	2877.8	2918.6	3136.0	3152.2	2803.7	2501.6	
55°		2276.6	2185.6	2127.4	2273.8	2462.0	2245.5	1966.9	
60°		1827.5	1698.2	1586.4	1698.0	1942.3	1796.3	1589.3	
65°		1539.2	1377.9	1236.9	1330.5	1560.5	1497.1	1363.6	
70°		1340.3	1170.4	1001.9	1089.5	1282.5	1307.4	1243.4	
75°		1164.6	987.9	826.8	905.8	1070.6	1162.9	1156.6	
80°		993.6	814.2	660.5	723.2	866.0	992.3	1024.2	
85°		712.6	576.5	477.7	530.8	628.3	741.3	772.2	

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TE12DN4AXG3S4
EAN: 4058352934784

LP number
58637_198

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

