


Photometric test report

Family Licross® 11 Recessed	Order number: 51TL127N485G EAN: 4058352922330	LP number 58637_202
	Version cover frosted, wide distribution, high visual comfort Lamps LED 4000 K CRI ≥ 80 Controlgear ECG Rated values Net luminous flux = 8950 lm Power consumption = 48.5 W Luminous efficacy = 184.5 lm/W	serial documentation 11.10.2023



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 498 cd/klm**



Classifications	
DIN 5040	A 5 0
CIE	N1=67 N2=92 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL127N485G EAN: 4058352922330	LP number 58637_202
---------------------------------------	----------------------------------------------------------------	-------------------------------

sITeco

Table of values for luminous intensities	Maximum luminous intensity
-------------------------------------------------	-----------------------------------

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	482.3	482.3	482.3	482.3	482.3	482.3	482.3	2.9	2.9
5°	485.4	482.8	478.2	477.5	477.4	475.9	475.7	22.9	25.8
10°	492.7	488.2	477.9	471.3	467.6	465.9	466.0	45.2	71.0
15°	493.2	486.1	471.9	467.9	471.0	473.7	476.3	67.5	138.5
20°	482.5	473.5	462.5	471.9	487.1	492.8	494.9	89.9	228.4
25°	456.4	447.1	449.2	479.4	497.6	491.1	485.8	109.5	337.8
30°	414.9	406.8	427.0	475.1	479.0	447.1	431.1	121.4	459.2
35°	364.2	358.0	387.7	436.7	420.7	368.9	346.8	122.0	581.2
40°	300.5	296.3	322.5	357.9	336.0	284.8	262.9	110.4	691.6
45°	229.2	226.3	238.5	259.8	247.2	211.8	193.4	90.1	781.7
50°	162.3	159.3	161.6	173.6	174.5	155.2	138.5	68.2	849.9
55°	112.5	108.0	105.1	112.3	121.6	110.9	97.2	49.6	899.5
60°	78.7	73.1	68.3	73.1	83.7	77.4	68.5	35.5	935.0
65°	56.0	50.2	45.0	48.4	56.8	54.5	49.6	25.5	960.5
70°	39.5	34.5	29.5	32.1	37.8	38.5	36.6	18.1	978.6
75°	26.0	22.0	18.4	20.2	23.9	25.9	25.8	12.0	990.6
80°	14.9	12.2	9.9	10.8	13.0	14.8	15.3	6.8	997.4
85°	5.4	4.3	3.6	4.0	4.7	5.6	5.8	2.5	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL127N485G EAN: 4058352922330	LP number 58637_202
---------------------------------------	----------------------------------------------------------------	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	22.2	23.7	22.6	24.0	24.4	22.3	23.8	22.7	24.1	24.5
	3H	22.8	24.1	23.1	24.4	24.8	22.9	24.2	23.3	24.5	24.9
	4H	23.0	24.2	23.4	24.6	24.9	23.1	24.4	23.5	24.7	25.1
	6H	23.2	24.3	23.6	24.7	25.0	23.3	24.4	23.7	24.8	25.2
	8H	23.3	24.3	23.7	24.7	25.1	23.4	24.5	23.9	24.8	25.2
	12H	23.3	24.2	23.7	24.6	25.0	23.5	24.4	23.9	24.8	25.2
4H	2H	22.5	23.7	22.9	24.0	24.4	22.6	23.8	23.0	24.1	24.5
	3H	23.1	24.1	23.5	24.5	24.9	23.3	24.3	23.7	24.7	25.1
	4H	23.4	24.3	23.8	24.7	25.1	23.6	24.5	24.0	24.9	25.4
	6H	23.6	24.4	24.0	24.8	25.3	23.9	24.7	24.3	25.1	25.6
	8H	23.7	24.4	24.1	24.8	25.3	24.0	24.7	24.5	25.1	25.6
	12H	23.7	24.3	24.2	24.8	25.3	24.1	24.7	24.5	25.1	25.6
8H	4H	23.4	24.1	23.9	24.6	25.1	23.7	24.4	24.1	24.8	25.3
	6H	23.7	24.3	24.2	24.7	25.2	24.0	24.6	24.5	25.1	25.6
	8H	23.8	24.3	24.3	24.8	25.3	24.1	24.6	24.6	25.1	25.6
	12H	23.8	24.3	24.4	24.8	25.3	24.2	24.6	24.7	25.2	25.7
12H	4H	23.4	24.0	23.9	24.5	25.0	23.7	24.3	24.1	24.7	25.2
	6H	23.7	24.2	24.2	24.7	25.2	24.0	24.5	24.5	25.0	25.5
	8H	23.8	24.2	24.3	24.7	25.3	24.1	24.6	24.7	25.1	25.6

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500 B = 58
------------------------	---------------------------------------------------	--------------------------------------	----------------------------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		33338.4	32924.0	34699.4	37795.2	35958.8	30819.6	28130.0	
50°		25975.1	25501.2	25863.2	27789.5	27932.6	24844.3	22167.2	
55°		20174.2	19367.8	18852.0	20149.2	21817.1	19898.7	17429.5	
60°		16194.4	15048.6	14057.5	15046.9	17211.8	15917.8	14083.4	
65°		13639.8	12209.7	10960.9	11790.3	13828.2	13266.1	12083.3	
70°		11876.7	10371.6	8878.2	9654.2	11364.5	11585.2	11018.3	
75°		10320.4	8753.9	7326.6	8027.0	9486.9	10304.9	10249.2	
80°		8804.6	7214.6	5853.2	6408.9	7674.3	8792.8	9076.0	
85°		6314.8	5108.5	4232.7	4703.7	5567.7	6568.6	6842.4	

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL127N485G EAN: 4058352922330	LP number 58637_202
----------------------------------------------	----------------------------------------------------------------	--------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco

