




Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51G08HE EAN: 4058352991374	LP number 59351_101
	Version post-top or side-entry mounting Optic asymmetric, extremely wide distribution with an additional rear light component (ST1.0ST0.5) Cover transparent, PMMA Lamps LED 3000 K CRI ≥ 70 Controlgear ECG SITECO iQ - DALI2 Rated values Net luminous flux = 8240 lm Power consumption = 58.6 W Luminous efficacy = 140.6 lm/W	serial documentation 13.11.2023





Luminous intensity in cd/klm C180-0 C200-20 C205-25 C270-90 **Imax: 633 cd/klm**



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%

Luminous intensity class acc. to EN13201-2

Class:	G2
Imax 70°	629.2
Imax 80°	139.7
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0


Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51G08HE EAN: 4058352991374	LP number 59351_101
--	--	-------------------------------

Envelope curve in cd/klm **KMK 62.5°** **KMK 60°** **KMK 57.5°** **KMK 55°** **siteco**



Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51G08HE EAN: 4058352991374	LP number 59351_101
Table of values for luminous intensities		Maximum luminous intensity

siteco

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4
2,5°	189.1	190.8	192.7	194.2	195.7	197.2	198.8	199.9	200.6	201.1	201.8	202.5	202.8
5,0°	188.9	193.0	197.2	201.2	204.8	208.6	212.0	214.5	216.9	219.2	220.0	220.3	221.0
7,5°	188.4	193.0	199.3	205.4	211.4	217.1	223.0	227.3	229.9	231.8	232.7	234.3	237.2
10,0°	193.1	198.8	206.8	213.9	219.9	226.4	232.6	239.3	244.2	249.3	254.5	257.4	260.7
12,5°	206.1	214.5	220.8	229.0	234.2	239.5	247.4	255.4	263.7	269.7	275.8	281.1	282.8
15,0°	212.4	223.0	233.6	241.8	249.4	259.1	265.4	271.2	278.7	287.0	296.3	302.5	306.5
17,5°	220.0	234.8	248.9	260.3	270.3	281.0	287.0	292.5	297.2	298.8	300.7	308.4	316.0
20,0°	232.8	246.6	256.8	271.0	288.2	298.1	309.0	320.0	321.0	323.0	320.5	321.7	328.5
22,5°	241.1	260.5	276.3	292.4	309.7	322.2	331.0	340.9	346.7	342.2	337.7	339.5	342.2
25,0°	248.7	270.3	293.7	315.2	333.7	346.8	356.0	365.1	365.2	355.8	353.6	354.5	353.5
27,5°	257.6	281.7	302.6	322.4	342.0	360.6	372.8	377.7	374.3	365.9	364.2	362.2	365.3
30,0°	262.6	288.5	312.2	342.2	359.5	371.7	384.8	388.7	385.2	379.7	380.1	374.5	372.6
32,5°	269.0	299.5	326.2	351.9	369.5	389.5	398.3	399.7	400.6	394.7	389.4	382.1	383.0
35,0°	281.2	304.9	333.4	360.8	376.1	393.0	396.5	399.9	400.2	397.3	392.2	383.8	382.1
37,5°	282.9	313.2	341.0	363.0	380.7	395.8	404.2	405.6	399.2	394.3	385.1	377.4	370.1
40,0°	293.3	324.4	349.0	369.5	386.2	399.9	411.5	406.9	400.5	388.2	373.4	363.7	354.4
42,5°	298.0	325.8	359.6	379.7	397.3	414.7	420.3	411.0	393.5	382.0	371.4	360.9	349.4
45,0°	307.6	333.9	374.0	394.1	403.9	422.7	423.7	415.2	397.5	386.4	366.4	340.7	330.5
47,5°	307.9	346.6	385.6	408.8	425.3	443.0	438.7	417.3	399.5	392.0	354.4	317.1	306.5
50,0°	320.8	363.3	394.0	416.7	432.3	445.9	447.4	426.9	402.0	371.5	339.7	306.2	280.5
52,5°	328.8	373.5	413.5	436.4	440.5	455.0	453.5	419.4	386.4	352.0	313.5	273.9	247.9
55,0°	316.8	378.8	439.2	477.8	488.5	479.6	471.8	438.8	394.3	332.9	278.8	245.8	222.9
57,5°	320.3	392.1	466.4	526.9	536.6	520.2	495.9	455.9	396.4	325.1	268.5	227.1	206.7
60,0°	348.7	432.1	530.9	593.9	604.8	569.0	523.8	469.6	400.2	320.2	267.7	227.7	193.6
62,5°	356.4	440.6	532.7	604.8	632.9	600.9	560.0	496.4	410.7	332.0	258.8	212.8	172.3
65,0°	366.3	443.3	517.3	584.8	626.7	612.3	587.0	509.4	423.9	335.1	243.0	190.5	156.0
67,5°	383.7	483.7	552.0	599.5	611.8	602.4	564.6	502.1	415.0	323.2	230.4	170.4	139.3
70,0°	384.5	510.1	619.9	629.2	605.9	569.0	499.5	446.2	376.6	305.7	212.8	153.8	121.9
72,5°	390.2	514.5	629.8	623.0	586.5	511.7	425.7	373.8	335.1	287.0	199.2	105.2	63.2
75,0°	348.2	447.8	521.6	521.4	487.1	406.3	322.5	296.1	262.0	185.8	87.8	31.9	11.7
77,5°	212.1	289.8	322.0	319.4	290.5	260.8	217.4	169.2	100.5	41.0	13.2	4.9	3.3
80,0°	89.2	118.6	134.9	139.7	125.2	107.6	78.1	36.2	11.2	4.3	3.3	3.1	2.4
82,5°	17.9	22.7	26.1	30.7	31.1	21.8	8.8	2.6	2.1	1.9	1.8	1.7	1.6
85,0°	1.5	1.6	1.6	1.6	1.7	1.6	1.4	1.3	1.3	1.2	1.1	1.0	0.9
87,5°	0.8	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.6	0.6	0.6	0.5	0.5
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51G08HE EAN: 4058352991374	LP number 59351_101
Table of values for luminous intensities		Maximum luminous intensity

siteco

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4
2,5°	202.5	202.1	202.5	202.6	202.6	202.6	187.3	185.4	183.6	181.9	180.1	178.0	176.6
5,0°	221.0	220.8	221.0	221.5	222.4	221.8	185.5	181.6	178.1	174.4	170.7	167.4	164.1
7,5°	239.3	240.4	242.0	243.9	245.6	246.6	183.0	177.6	172.3	167.7	163.4	159.3	155.2
10,0°	263.9	267.0	270.9	273.3	276.4	277.2	187.4	182.0	175.8	169.7	162.8	156.0	149.3
12,5°	285.7	289.2	292.2	297.0	301.3	303.4	196.2	185.7	175.5	165.7	157.0	150.2	143.8
15,0°	308.6	308.6	312.1	312.9	310.6	311.0	200.7	187.3	174.0	162.8	152.5	142.7	134.3
17,5°	320.2	320.9	325.5	328.5	328.1	327.1	205.6	190.7	176.9	163.4	149.0	136.4	126.7
20,0°	334.6	339.0	341.4	342.8	340.5	342.5	214.0	195.6	177.6	160.7	144.5	131.9	121.0
22,5°	347.0	353.5	357.9	360.0	357.2	355.5	216.2	194.8	173.9	155.7	140.2	126.0	113.6
25,0°	358.3	363.1	366.4	368.2	369.2	370.3	221.5	196.9	176.1	153.0	133.7	118.2	106.4
27,5°	370.6	372.0	376.1	380.8	383.1	384.5	228.0	200.2	172.0	146.2	127.7	111.4	96.3
30,0°	375.2	377.8	383.2	389.6	395.7	396.9	232.8	201.5	167.3	140.7	121.0	103.2	87.4
32,5°	381.9	378.9	387.4	397.0	396.9	388.8	235.0	197.9	164.2	137.0	115.2	97.2	83.2
35,0°	381.1	379.9	381.2	392.0	387.5	381.5	240.3	196.6	159.5	129.9	108.0	91.5	79.9
37,5°	369.1	368.3	371.8	377.7	373.1	368.0	240.4	196.5	155.8	123.8	100.7	86.0	76.3
40,0°	354.0	354.2	350.6	349.4	349.3	348.6	242.4	200.0	157.4	123.0	98.6	81.5	71.0
42,5°	345.7	338.7	323.3	319.1	313.5	313.2	248.0	198.0	145.5	111.5	90.0	73.1	65.3
45,0°	323.5	313.1	303.9	294.4	284.5	279.7	254.9	191.5	132.5	96.3	82.5	68.2	61.4
47,5°	299.7	280.2	265.2	258.0	250.1	248.9	246.4	178.1	117.4	85.1	74.5	64.4	57.1
50,0°	262.5	247.2	236.7	223.4	214.2	214.0	248.1	166.3	99.4	76.5	65.2	58.1	53.2
52,5°	232.0	219.3	205.9	189.3	179.9	178.8	239.2	152.3	88.0	67.8	56.8	51.5	50.0
55,0°	205.2	189.2	174.4	154.3	151.1	156.3	229.5	145.0	81.4	59.3	50.8	47.4	46.8
57,5°	183.6	155.7	139.4	129.7	126.9	127.9	234.6	151.5	86.0	56.0	47.7	43.3	42.7
60,0°	159.2	130.1	110.8	105.5	99.8	97.9	248.1	157.2	87.1	57.8	48.8	43.4	42.2
62,5°	141.2	110.0	90.9	82.9	75.2	72.6	266.5	161.1	79.6	52.8	44.4	41.8	39.5
65,0°	124.5	94.9	71.3	63.6	59.2	57.7	266.3	153.7	69.4	46.8	42.7	40.1	36.6
67,5°	109.6	77.4	57.6	49.5	46.6	45.1	261.3	139.7	59.8	43.9	40.1	38.8	36.2
70,0°	86.5	52.3	33.9	25.7	23.5	23.4	247.9	129.2	56.0	40.5	37.4	35.9	35.7
72,5°	34.2	16.1	9.8	7.3	6.8	6.6	246.9	131.3	48.5	38.4	35.3	32.2	33.0
75,0°	4.4	3.5	3.5	3.4	3.3	3.2	219.3	115.7	37.6	34.7	33.1	30.0	29.0
77,5°	2.9	2.7	2.7	2.6	2.5	2.4	142.4	71.2	23.6	24.1	24.8	21.6	18.3
80,0°	2.2	2.1	1.9	1.8	1.7	1.7	58.6	31.9	12.4	12.7	12.4	9.6	6.4
82,5°	1.5	1.4	1.3	1.2	1.1	1.1	12.1	7.1	4.0	4.1	3.7	3.1	2.9
85,0°	0.8	0.8	0.7	0.7	0.6	0.6	1.4	1.3	1.2	1.1	1.1	1.0	1.0
87,5°	0.4	0.3	0.3	0.3	0.2	0.2	0.8	0.7	0.7	0.6	0.6	0.6	0.5
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51G08HE EAN: 4058352991374	LP number 59351_101
Table of values for luminous intensities		Maximum luminous intensity
		sITeCO

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	186.4	0.3	0.3
2,5°	174.6	173.3	171.4	170.1	169.3	168.4	167.7	166.7	166.2	166.1	165.7	2.2	2.5
5,0°	160.8	158.2	156.6	154.8	153.3	152.2	151.2	150.6	150.2	149.6	149.4	4.5	7.0
7,5°	151.8	148.3	145.2	142.0	138.4	135.9	134.3	133.2	132.9	133.1	132.8	6.8	13.8
10,0°	143.7	139.6	136.5	133.7	130.7	128.0	125.1	122.0	118.0	116.0	115.0	9.3	23.1
12,5°	137.2	131.3	127.0	123.9	120.4	117.3	114.4	111.1	109.5	108.7	108.6	12.0	35.0
15,0°	127.3	121.0	115.1	110.1	105.7	102.3	100.1	98.6	98.0	98.1	98.4	14.6	49.6
17,5°	118.0	109.9	104.1	99.2	95.2	90.5	86.8	85.5	84.8	83.6	82.4	17.3	66.9
20,0°	110.9	103.7	96.9	92.5	89.0	85.4	81.1	76.8	73.5	71.6	70.7	20.2	87.2
22,5°	103.0	94.1	88.7	85.5	83.1	79.1	76.5	74.5	71.9	69.3	67.9	23.4	110.5
25,0°	96.0	86.9	80.9	78.4	74.7	70.5	68.9	67.6	65.5	64.8	65.0	26.4	137.0
27,5°	87.5	82.5	77.8	73.4	69.0	66.1	64.3	63.6	63.5	62.2	61.4	29.3	166.3
30,0°	78.4	75.5	71.2	66.7	65.6	65.1	63.9	62.5	59.9	58.6	58.6	32.3	198.6
32,5°	75.4	70.7	66.4	64.0	63.9	62.1	59.3	58.3	58.2	59.6	61.4	35.1	233.7
35,0°	72.4	67.2	62.5	61.0	61.9	58.3	54.6	53.3	56.7	59.4	59.4	37.4	271.1
37,5°	69.3	65.1	62.1	59.7	58.1	57.1	56.3	53.9	53.2	54.1	54.3	39.2	310.3
40,0°	66.3	62.2	60.1	57.4	54.3	52.9	53.5	53.8	53.6	51.5	49.8	40.7	351.0
42,5°	62.8	60.2	55.7	54.3	52.9	52.6	52.5	52.3	51.9	50.5	50.0	42.0	393.0
45,0°	60.6	58.5	53.8	53.1	53.7	51.0	52.6	54.2	50.4	49.4	50.1	43.1	436.1
47,5°	54.0	53.6	52.7	51.3	48.2	47.0	48.3	49.3	47.4	46.7	49.3	43.6	479.7
50,0°	52.0	50.4	49.2	50.8	48.9	46.0	45.8	46.3	45.8	46.3	48.3	43.8	523.5
52,5°	51.1	48.7	45.8	47.3	47.6	45.0	42.5	42.6	43.4	43.4	42.8	43.5	566.9
55,0°	47.2	45.4	45.0	45.0	43.7	42.0	39.9	39.3	38.5	37.8	37.4	43.8	610.7
57,5°	44.8	43.4	43.0	41.4	39.0	38.2	36.8	36.0	36.1	36.1	35.7	45.0	655.8
60,0°	42.0	42.4	40.9	37.6	34.7	33.2	33.3	32.6	32.4	32.3	32.8	47.5	703.2
62,5°	37.1	38.9	39.3	35.3	32.1	29.7	29.1	29.1	28.8	27.7	27.0	48.5	751.7
65,0°	35.0	35.2	34.6	30.8	27.9	26.1	24.6	24.8	26.0	25.8	24.4	48.3	800.0
67,5°	34.2	31.7	28.6	25.9	24.9	23.5	21.3	20.8	22.4	22.6	21.4	48.0	848.0
70,0°	34.1	29.7	25.8	22.2	21.0	19.9	17.3	15.5	14.7	13.8	13.3	46.3	894.3
72,5°	30.6	27.0	23.4	16.9	12.4	11.0	9.2	7.4	6.3	5.8	5.6	42.4	936.8
75,0°	25.7	20.1	13.4	8.6	6.4	5.5	5.0	4.5	4.1	3.8	3.7	33.5	970.2
77,5°	14.2	9.2	6.7	5.4	4.9	4.5	4.1	3.8	3.3	3.0	2.9	19.7	989.9
80,0°	5.1	5.0	4.8	4.3	4.0	3.6	3.2	2.8	2.5	2.2	2.0	7.8	997.7
82,5°	3.0	3.1	3.2	3.2	3.0	2.8	2.4	2.0	1.7	1.5	1.4	1.8	999.5
85,0°	1.0	1.0	1.2	1.5	1.6	1.6	1.5	1.2	0.9	0.7	0.6	0.3	999.9
87,5°	0.5	0.5	0.4	0.4	0.3	0.3	0.3	0.3	0.3	0.1	0.1	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Streetlight 11 mini LED	Order number: 5XC2J51G08HE EAN: 4058352991374	LP number 59351_101
--	--	-------------------------------

Dimming levels table	environmental temperature: 25°C	siteco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	8240	58.6	60.9	59.8
95	241	252	7818	55.0	57.2	56.1
90	229	250	7429	51.9	53.9	52.9
85	216	248	7007	48.6	50.4	49.5
80	203	246	6586	45.3	47.0	46.2
75	190	243	6164	42.1	43.8	43.0
70	178	241	5774	39.3	40.7	40.0
65	165	238	5353	36.2	37.6	36.9
60	152	235	4931	33.2	34.4	33.8
55	140	232	4542	30.5	31.6	31.0
50	127	229	4120	27.5	28.5	28.0
45	114	225	3698	24.7	25.6	25.2
40	102	221	3309	22.2	23.0	22.6
35	89	216	2887	19.4	20.1	19.8
30	76	210	2466	16.7	17.3	17.0
25	63	203	2044	14.1	14.6	14.4
20	51	195	1654	11.7	12.1	11.9
15	38	184	1233	9.1	9.4	9.2
14	35	181	1135	8.5	8.8	8.6