

Photometric test report

Family
Monsun® 11



Order number: 51FP20DP467L3H
EAN: 4069025268938

Version

Lamps

Controlgear

Setting

Rated values

prismatic diffuser, opal, polycarbonate, wide distribution

LED 4000 K | CRI ≥ 80

ECG-DALI


emergency light operation: 3 h

Net luminous flux = 910 lm
Power consumption = 6.2 W
Luminous efficacy = 146.8 lm/W

LP number
59060_150

serial
documentation
30.09.2024

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 1	η_{LB}	100.0%
CIE	N1=45 N2=75 N3=93	ϕ_u	93.7%
	N4=94 N5=100	ϕ_o	6.3%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 11	Order number: 51FP20DP467L3H EAN: 4069025268938	LP number 59060_150
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	319.4	319.4	319.4	319.4	319.4	319.4	319.4	1.9	1.9
5°	319.1	317.8	316.0	317.2	318.6	318.6	318.8	15.2	17.1
10°	313.9	312.8	311.0	312.1	313.5	313.5	313.7	29.8	46.9
15°	305.6	304.7	302.7	303.7	305.0	304.9	305.2	43.2	90.1
20°	294.3	293.5	291.4	292.2	293.3	293.1	293.5	54.9	145.0
25°	280.9	280.2	277.7	277.9	278.8	278.5	278.8	64.6	209.6
30°	265.9	265.3	262.4	261.6	261.9	261.4	261.7	72.0	281.6
35°	249.2	248.5	245.6	243.7	242.9	242.2	242.4	77.0	358.5
40°	231.6	230.8	227.5	224.6	222.7	221.4	221.6	79.5	438.0
45°	212.9	211.8	208.5	204.2	201.3	199.0	199.4	79.5	517.5
50°	193.7	192.3	188.8	183.7	179.4	175.9	176.0	77.3	594.9
55°	174.1	172.4	168.8	162.7	157.2	152.3	152.1	73.1	667.9
60°	153.8	152.1	148.1	141.4	134.9	128.8	127.5	66.9	734.9
65°	133.1	131.4	127.0	119.9	112.8	105.5	102.8	59.2	794.0
70°	112.0	110.4	105.0	98.0	90.2	82.2	78.2	49.9	843.9
75°	90.5	88.8	83.0	75.7	67.3	58.8	53.6	39.3	883.2
80°	69.4	67.4	62.0	54.0	45.3	36.4	30.4	28.3	911.6
85°	51.2	49.1	43.8	35.9	26.7	17.7	11.3	18.6	930.2
90°	40.3	38.3	33.0	25.3	16.4	7.5	1.9	12.9	943.1
95°	36.9	35.1	30.2	22.8	14.1	5.6	1.6	11.6	954.7
100°	33.7	31.9	27.1	20.1	11.9	4.0	1.5	10.1	964.8
105°	30.1	28.5	23.8	17.3	9.5	2.6	1.3	8.6	973.4
110°	26.5	24.6	20.5	14.4	7.3	1.5	1.2	7.1	980.4
115°	22.8	21.1	17.3	11.6	5.2	1.3	1.2	5.7	986.1
120°	19.1	17.5	14.1	8.9	3.4	1.3	1.1	4.4	990.5
125°	15.4	13.9	10.8	6.2	1.7	1.2	1.0	3.2	993.6
130°	11.8	10.5	7.7	3.9	1.4	1.2	1.0	2.2	995.8
135°	8.3	7.2	5.0	2.0	1.4	1.2	1.1	1.4	997.2
140°	5.1	4.3	2.5	1.6	1.3	1.1	1.0	0.8	998.0
145°	2.4	2.0	1.8	1.6	1.4	1.2	1.2	0.5	998.5
150°	1.9	1.9	1.8	1.5	1.4	1.3	1.2	0.4	999.0
155°	1.8	1.8	1.6	1.5	1.4	1.3	1.3	0.4	999.3
160°	1.6	1.6	1.5	1.5	1.4	1.4	1.3	0.3	999.6
165°	1.5	1.5	1.4	1.4	1.4	1.4	1.3	0.2	999.8
170°	1.4	1.4	1.4	1.4	1.4	1.4	1.3	0.1	999.9
175°	1.3	1.3	1.3	1.4	1.4	1.4	1.3	0.1	1000.0
180°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.0	1000.0

Photometric test report

Family Monsun® 11	Order number: 51FP20DP467L3H EAN: 4069025268938	LP number 59060_150
UGR-Table	Standard room	siteco

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	13.8	15.5	14.1	15.8	16.1	13.6	15.3	13.9	15.6	15.9
	3H	15.6	17.2	16.0	17.5	17.8	15.1	16.7	15.5	17.0	17.4
	4H	16.4	17.9	16.8	18.2	18.6	15.7	17.2	16.1	17.6	18.0
	6H	17.1	18.5	17.5	18.9	19.3	16.2	17.6	16.6	17.9	18.3
	8H	17.5	18.8	17.9	19.1	19.5	16.3	17.6	16.7	18.0	18.4
	12H	17.8	19.0	18.2	19.4	19.8	16.4	17.6	16.8	18.0	18.4
4H	2H	14.5	16.0	14.9	16.3	16.7	14.4	15.8	14.8	16.2	16.6
	3H	16.5	17.8	16.9	18.2	18.6	16.1	17.4	16.5	17.8	18.2
	4H	17.5	18.6	17.9	19.0	19.5	16.9	18.0	17.3	18.4	18.8
	6H	18.3	19.4	18.8	19.8	20.2	17.4	18.4	17.8	18.8	19.3
	8H	18.7	19.7	19.2	20.1	20.6	17.6	18.5	18.0	18.9	19.4
	12H	19.1	19.9	19.6	20.4	20.9	17.7	18.5	18.1	19.0	19.5
8H	4H	17.8	18.8	18.3	19.2	19.7	17.3	18.2	17.7	18.7	19.1
	6H	18.9	19.6	19.3	20.1	20.6	18.0	18.7	18.4	19.2	19.7
	8H	19.3	20.1	19.8	20.5	21.0	18.2	18.9	18.7	19.4	19.9
	12H	19.8	20.4	20.4	20.9	21.5	18.4	19.0	18.9	19.5	20.0
12H	4H	17.9	18.7	18.3	19.2	19.7	17.4	18.2	17.9	18.7	19.1
	6H	18.9	19.6	19.4	20.1	20.6	18.1	18.8	18.6	19.3	19.8
	8H	19.5	20.1	20.0	20.6	21.1	18.4	19.0	18.9	19.5	20.0

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1590 B = 87		H(C0) = 21 H(C90) = 21		H(C180) = 21 H(C270) = 21	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°				
γ	Luminance in cd/m²										
45°	1595.9	1593.7	1595.5	1610.2	1653.8	1721.7	1830.5				
50°	1539.6	1535.1	1537.5	1548.1	1586.4	1651.9	1773.0				
55°	1485.0	1477.7	1479.9	1484.3	1516.7	1577.3	1711.9				
60°	1426.5	1419.3	1418.7	1418.6	1444.6	1499.0	1640.1				
65°	1365.1	1357.5	1351.2	1347.0	1367.8	1413.4	1555.4				
70°	1295.2	1286.8	1268.8	1261.0	1272.6	1309.5	1451.0				
75°	1209.8	1199.0	1169.2	1151.1	1145.7	1167.1	1299.3				
80°	1110.2	1090.6	1057.0	1011.5	980.4	966.8	1073.1				
85°	1029.0	1001.5	954.3	885.4	801.6	716.4	742.2				

Photometric test report

Family
Monsun® 11

Order number: 51FP20DP467L3H
EAN: 4069025268938

LP number
59060_150

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

