

Photometric test report

Family
Highbay 21

Order number: 52HN11DB4QLA01
EAN: 4069025421487

LP number
59724_166

serial
documentation
20.03.2025



Version primary light control with lens, PMMA, housing, white, for Licross® rail, narrow distribution, with multisensor node BT

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 38000 lm
Power consumption = 198.2 W
Luminous efficacy = 191.7 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2719 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=89 N2=97 N3=99
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 21	Order number: 52HN11DB4QLA01 EAN: 4069025421487	LP number 59724_166
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	0,0° 180,0°	7,5° 172,5° 187,5° 352,5°	15,0° 165,0° 195,0° 345,0°	22,5° 157,5° 202,5° 337,5°	30,0° 150,0° 210,0° 330,0°	37,5° 142,5° 217,5° 322,5°	45,0° 135,0° 225,0° 315,0°
		Luminous intensity in cd/klm					
γ							
0,0°	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5
2,5°	2662.8	2671.1	2671.1	2670.6	2667.6	2663.3	2662.4
5,0°	2502.8	2490.9	2498.0	2494.5	2487.6	2479.1	2473.3
7,5°	2228.4	2233.8	2227.9	2223.2	2214.7	2203.4	2194.2
10,0°	1915.8	1894.8	1902.8	1897.9	1890.8	1880.8	1870.9
12,5°	1554.6	1560.7	1554.3	1552.6	1548.0	1540.2	1531.7
15,0°	1246.2	1237.0	1237.4	1238.4	1237.7	1233.9	1229.0
17,5°	947.1	964.7	959.6	960.0	960.5	959.5	958.4
20,0°	765.0	752.2	754.6	751.6	749.0	747.8	747.5
22,5°	591.2	598.6	590.3	583.2	577.5	573.8	572.1
25,0°	481.4	472.8	470.4	460.9	451.8	445.8	443.1
27,5°	370.5	376.3	371.1	363.9	355.1	347.9	344.8
30,0°	301.2	297.9	295.0	290.6	284.7	279.0	275.2
32,5°	234.8	237.8	234.9	232.8	229.2	225.3	220.4
35,0°	189.2	188.5	187.7	186.9	184.4	180.6	175.3
37,5°	154.0	153.7	151.7	151.0	148.4	144.9	141.0
40,0°	125.7	123.3	123.0	121.9	119.1	115.8	113.2
42,5°	99.2	100.3	99.3	98.6	95.9	92.9	90.7
45,0°	81.4	79.6	79.7	79.0	77.2	74.6	72.7
47,5°	64.2	64.9	64.5	64.0	62.8	60.9	59.5
50,0°	52.5	51.6	51.8	51.7	51.0	49.9	49.1
52,5°	41.7	41.9	41.8	42.1	41.9	41.4	40.9
55,0°	33.9	33.5	34.1	34.8	35.0	35.0	34.7
57,5°	27.1	27.4	28.1	29.2	29.7	29.7	29.6
60,0°	22.3	22.3	23.0	24.6	25.8	25.8	25.5
62,5°	19.0	19.2	19.6	20.7	22.4	22.3	22.0
65,0°	17.0	16.8	17.2	18.3	19.8	19.1	19.1
67,5°	14.7	14.8	14.9	16.1	17.2	16.3	16.1
70,0°	12.8	12.5	12.6	13.8	14.3	13.8	13.9
72,5°	11.3	11.1	10.9	11.6	11.4	11.2	11.7
75,0°	9.7	9.3	8.9	9.6	9.3	9.1	9.3
77,5°	7.4	7.4	7.1	7.5	7.1	6.8	7.1
80,0°	4.9	4.7	4.8	4.8	4.5	4.5	4.8
82,5°	2.2	2.3	2.3	2.4	2.4	2.5	2.7
85,0°	0.8	0.8	0.8	0.8	0.8	0.9	1.0
87,5°	0.4	0.4	0.4	0.4	0.4	0.4	0.4

Photometric test report

Family Highbay 21	Order number: 52HN11DB4QLA01 EAN: 4069025421487	LP number 59724_166
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	52,5° 127,5° 232,5° 307,5°	60,0° 120,0° 240,0° 300,0°	67,5° 112,5° 247,5° 292,5°	75,0° 105,0° 255,0° 285,0°	82,5° 97,5° 262,5° 277,5°	90,0° 270,0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0,0°	2718.5	2718.5	2718.5	2718.5	2718.5	2718.5	4.1	4.1
2,5°	2661.4	2660.0	2657.7	2657.0	2651.0	2647.2	31.8	35.9
5,0°	2468.0	2461.9	2456.3	2452.9	2444.7	2440.4	59.1	95.0
7,5°	2185.5	2176.0	2168.0	2162.0	2152.6	2148.3	78.5	173.5
10,0°	1860.3	1847.8	1837.7	1831.0	1822.1	1817.6	88.9	262.4
12,5°	1522.0	1510.4	1500.7	1495.5	1488.9	1485.2	90.6	353.0
15,0°	1223.0	1215.3	1207.9	1204.2	1200.8	1197.6	86.8	439.8
17,5°	955.3	949.4	945.6	944.9	945.8	944.0	78.6	518.5
20,0°	745.4	741.8	741.4	743.7	748.0	747.7	70.2	588.6
22,5°	571.4	571.2	573.5	575.9	579.7	580.1	60.8	649.4
25,0°	443.2	444.5	446.3	448.3	449.2	448.8	52.5	701.9
27,5°	344.0	344.5	345.1	346.1	344.9	343.6	44.7	746.7
30,0°	273.7	273.8	273.9	272.4	270.2	268.2	38.5	785.2
32,5°	217.7	217.2	215.9	213.7	211.0	209.4	32.9	818.1
35,0°	172.5	170.5	168.2	166.4	165.0	164.5	27.8	845.9
37,5°	138.1	135.6	133.3	132.0	130.7	130.3	23.7	869.5
40,0°	110.2	108.1	106.1	104.8	103.7	103.1	20.0	889.6
42,5°	88.5	86.8	85.0	83.9	83.2	82.7	16.9	906.5
45,0°	71.2	69.8	68.4	67.3	66.9	66.6	14.2	920.7
47,5°	58.5	57.3	56.0	55.1	54.8	54.6	12.1	932.8
50,0°	48.3	47.1	46.0	45.5	45.1	44.8	10.3	943.0
52,5°	40.2	39.3	38.3	37.7	37.1	36.8	8.7	951.8
55,0°	34.1	33.4	32.5	31.7	31.0	30.7	7.5	959.3
57,5°	29.3	29.0	28.2	27.0	26.3	26.1	6.6	965.9
60,0°	25.7	25.8	24.8	23.5	22.8	22.6	5.8	971.6
62,5°	22.4	22.9	21.8	20.7	20.1	19.9	5.1	976.8
65,0°	19.6	20.2	19.7	18.4	17.9	17.8	4.6	981.4
67,5°	16.7	17.6	17.8	16.4	16.0	16.0	4.1	985.5
70,0°	14.1	15.0	15.6	14.4	14.4	14.6	3.6	989.1
72,5°	11.7	12.4	13.4	12.9	13.2	13.4	3.1	992.3
75,0°	9.5	10.4	12.0	11.4	11.8	11.9	2.7	995.0
77,5°	7.2	8.1	9.6	9.6	10.0	10.2	2.1	997.1
80,0°	5.1	5.7	7.0	7.5	7.6	8.0	1.5	998.6
82,5°	3.0	3.6	4.5	5.0	5.3	5.6	0.9	999.5
85,0°	1.2	1.7	2.3	2.7	3.1	3.3	0.4	999.9
87,5°	0.4	0.4	0.5	0.6	0.8	0.9	0.1	1000.1

Photometric test report

Family Highbay 21			Order number: 52HN11DB4QLA01 EAN: 4069025421487							LP number 59724_166	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	17.4	18.6	17.8	18.9	19.2	16.9	18.0	17.2	18.3	18.7
	3H	17.9	18.8	18.2	19.2	19.5	17.5	18.5	17.9	18.9	19.2
	4H	18.1	19.0	18.5	19.3	19.7	18.0	18.9	18.4	19.2	19.6
	6H	18.3	19.1	18.7	19.4	19.8	18.4	19.2	18.8	19.5	19.9
	8H	18.4	19.0	18.8	19.4	19.8	18.6	19.3	19.0	19.7	20.1
	12H	18.3	18.9	18.8	19.3	19.7	18.7	19.3	19.1	19.7	20.1
4H	2H	17.6	18.5	18.0	18.9	19.2	17.1	18.0	17.5	18.4	18.8
	3H	18.2	18.9	18.6	19.3	19.8	18.0	18.7	18.4	19.1	19.5
	4H	18.5	19.2	18.9	19.6	20.0	18.5	19.2	19.0	19.6	20.0
	6H	18.7	19.3	19.2	19.7	20.2	19.1	19.6	19.5	20.0	20.5
	8H	18.8	19.2	19.2	19.7	20.2	19.2	19.7	19.7	20.2	20.7
	12H	18.8	19.2	19.3	19.6	20.1	19.4	19.8	19.9	20.3	20.8
8H	4H	18.6	19.1	19.1	19.5	20.0	18.6	19.1	19.1	19.6	20.0
	6H	18.9	19.3	19.4	19.7	20.3	19.2	19.6	19.7	20.1	20.6
	8H	18.9	19.2	19.4	19.7	20.3	19.4	19.8	20.0	20.3	20.8
	12H	18.9	19.2	19.4	19.7	20.2	19.6	19.9	20.2	20.4	21.0
12H	4H	18.6	19.0	19.1	19.5	20.0	18.6	19.0	19.1	19.5	20.0
	6H	18.9	19.2	19.4	19.7	20.2	19.2	19.5	19.7	20.0	20.6
	8H	18.9	19.2	19.4	19.7	20.2	19.5	19.7	20.0	20.2	20.8

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:				L = 852 B = 264		
C-planes	0,0° 180,0°	10,0° 170,0° 190,0° 350,0°	20,0° 160,0° 200,0° 340,0°	30,0° 150,0° 210,0° 330,0°	40,0° 140,0° 220,0° 320,0°	50,0° 130,0° 230,0° 310,0°	60,0° 120,0° 240,0° 300,0°	70,0° 110,0° 250,0° 290,0°	80,0° 100,0° 260,0° 280,0°	90,0° 270,0°
		Luminance in cd/m²								
γ										
45,0°	19446.3	18984.0	18958.6	18447.4	17653.6	17127.2	16686.0	16243.1	16012.8	15906.9
50,0°	13785.4	13555.1	13614.8	13401.6	13040.9	12786.8	12380.8	12027.2	11880.1	11766.6
55,0°	9985.9	9890.7	10191.5	10323.1	10277.2	10096.7	9846.0	9495.7	9175.2	9054.8
60,0°	7544.7	7592.6	8137.8	8733.3	8678.7	8662.3	8722.2	8257.5	7769.3	7644.3
65,0°	6811.0	6754.3	7137.5	7897.1	7614.3	7748.8	8080.6	7738.2	7218.4	7132.8
70,0°	6316.7	6179.4	6673.2	7048.8	6797.9	6886.9	7413.8	7600.2	7100.6	7199.4
75,0°	6314.0	5975.3	6190.2	6077.1	5931.6	6135.0	6763.1	7888.4	7654.2	7774.2
80,0°	4766.3	4585.5	4714.8	4419.9	4459.9	4791.1	5579.6	7076.6	7313.2	7746.3
85,0°	1566.2	1526.2	1560.4	1583.7	1751.2	2124.5	3248.8	4683.6	5770.6	6429.7

Photometric test report

Family
Highbay 21

Order number: 52HN11DB4QLA01
EAN: 4069025421487

LP number
59724_166

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 21	Order number: 52HN11DB4QLA01 EAN: 4069025421487	LP number 59724_166
Dimming levels table		environmental temperature: 25°C

siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	38000	198.2
95	241	252	36142	187.8
90	228	250	34270	177.6
85	214	248	32244	166.6
80	201	245	30347	156.3
75	188	243	28447	146.3
70	175	240	26529	136.1
65	163	238	24754	126.7
60	150	235	22825	116.7
55	137	231	20886	106.6
50	124	228	18947	96.8
45	112	224	17141	87.6
40	99	219	15170	77.7
35	87	215	13346	68.5
30	74	209	11364	58.8
25	62	202	9525	49.6
20	50	194	7676	40.7
15	37	183	5668	31.1
10	25	169	3806	22.3
5	13	145	1934	13.0
1	4	102	528	5.9