


Photometric test report

Family Monsun® 21	Order number: 51FB207L440J EAN: 4058352757222	LP number 59394_10
	Version prismatic diffuser, opal, polycarbonate, extremely wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG Rated values Net luminous flux = 4410 lm Power consumption = 29.8 W Luminous efficacy = 148 lm/W	serial documentation 10.02.2023
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 318 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=45 N2=75 N3=93 N4=94 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	93.7%
ϕ_o	6.3%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 21	Order number: 51FB207L440J EAN: 4058352757222	LP number 59394_10
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	318.2	318.2	318.2	318.2	318.2	318.2	318.2	1.9	1.9
5°	317.5	317.5	315.1	315.9	316.6	317.2	317.8	15.1	17.0
10°	312.4	312.6	310.3	310.8	311.5	312.2	312.9	29.7	46.7
15°	304.0	304.5	302.1	302.5	303.1	303.6	304.5	43.0	89.7
20°	293.0	293.3	291.0	291.0	291.4	291.9	292.8	54.7	144.5
25°	278.2	280.0	277.5	276.9	276.9	277.3	278.2	64.3	208.8
30°	264.9	265.0	262.4	260.7	260.0	260.0	261.0	71.8	280.6
35°	248.3	248.5	245.7	243.1	241.2	240.6	241.7	76.7	357.3
40°	231.4	230.9	227.8	224.4	221.2	219.7	220.8	79.3	436.6
45°	213.0	212.5	208.9	204.3	200.0	197.3	198.2	79.4	515.9
50°	194.4	193.4	189.5	184.3	178.4	174.4	174.7	77.3	593.2
55°	174.9	174.0	169.9	163.6	156.5	151.3	150.6	73.2	666.4
60°	155.2	153.6	149.3	142.2	134.7	128.1	126.2	67.1	733.5
65°	134.5	133.3	127.9	120.6	112.6	105.3	102.1	59.5	793.0
70°	113.8	111.2	106.2	98.6	90.1	81.8	77.7	50.1	843.1
75°	91.9	90.6	84.2	76.2	67.3	58.7	53.5	39.7	882.8
80°	70.8	68.8	62.9	54.4	45.2	36.1	30.1	28.6	911.4
85°	52.2	50.3	44.7	36.3	26.8	17.6	11.2	18.9	930.2
90°	41.3	39.2	33.7	25.7	16.7	7.7	2.0	13.2	943.5
95°	37.2	35.5	30.5	23.1	14.2	5.7	1.8	11.7	955.1
100°	33.6	31.9	27.2	20.0	11.9	4.1	1.6	10.1	965.3
105°	29.8	28.2	23.6	17.2	9.5	2.6	1.4	8.5	973.8
110°	26.0	24.2	20.2	14.2	7.2	1.5	1.2	7.0	980.8
115°	21.9	20.5	16.9	11.4	5.1	1.4	1.2	5.5	986.3
120°	18.6	17.0	13.7	8.7	3.2	1.3	1.1	4.3	990.6
125°	14.8	13.4	10.4	6.0	1.7	1.3	1.1	3.1	993.6
130°	11.3	10.0	7.4	3.7	1.5	1.3	1.1	2.1	995.7
135°	7.8	6.8	4.7	1.9	1.5	1.3	1.0	1.3	997.1
140°	4.8	4.0	2.4	1.7	1.5	1.2	1.0	0.8	997.9
145°	2.3	2.1	1.9	1.7	1.5	1.3	1.2	0.5	998.4
150°	2.0	2.0	1.9	1.7	1.5	1.4	1.3	0.5	998.9
155°	1.9	1.9	1.8	1.7	1.5	1.4	1.3	0.4	999.3
160°	1.8	1.8	1.8	1.6	1.5	1.5	1.4	0.3	999.6
165°	1.7	1.7	1.6	1.5	1.5	1.5	1.4	0.2	999.8
170°	1.5	1.6	1.5	1.5	1.5	1.5	1.4	0.1	999.9
175°	1.5	1.5	1.5	1.5	1.5	1.5	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 21	Order number: 51FB207L440J EAN: 4058352757222	LP number 59394_10
------------------------------------	--	-------------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	20.0	21.7	20.4	22.0	22.4	19.7	21.4	20.1	21.8	22.1
	3H	21.8	23.4	22.2	23.7	24.1	21.3	22.8	21.7	23.2	23.5
	4H	22.7	24.1	23.1	24.5	24.9	21.9	23.4	22.3	23.7	24.1
	6H	23.4	24.8	23.8	25.1	25.5	22.3	23.7	22.7	24.0	24.4
	8H	23.7	25.0	24.2	25.4	25.8	22.4	23.7	22.9	24.1	24.5
	12H	24.0	25.2	24.5	25.6	26.0	22.5	23.7	22.9	24.1	24.5
4H	2H	20.7	22.2	21.1	22.6	22.9	20.5	22.0	20.9	22.3	22.7
	3H	22.8	24.0	23.2	24.4	24.8	22.3	23.5	22.7	23.9	24.3
	4H	23.7	24.9	24.2	25.3	25.7	23.0	24.2	23.4	24.6	25.0
	6H	24.6	25.6	25.1	26.1	26.5	23.5	24.5	24.0	25.0	25.4
	8H	25.0	25.9	25.5	26.4	26.9	23.7	24.6	24.1	25.1	25.5
	12H	25.4	26.2	25.9	26.7	27.2	23.8	24.6	24.3	25.1	25.6
8H	4H	24.1	25.0	24.5	25.5	25.9	23.4	24.4	23.9	24.8	25.3
	6H	25.1	25.9	25.6	26.4	26.9	24.1	24.9	24.6	25.4	25.9
	8H	25.6	26.3	26.1	26.8	27.3	24.3	25.1	24.8	25.5	26.0
	12H	26.1	26.7	26.6	27.2	27.7	24.5	25.1	25.0	25.6	26.1
12H	4H	24.1	25.0	24.6	25.4	25.9	23.5	24.4	24.0	24.8	25.3
	6H	25.2	25.9	25.7	26.4	26.9	24.3	24.9	24.8	25.4	25.9
	8H	25.8	26.4	26.3	26.9	27.4	24.5	25.1	25.1	25.6	26.2

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1299	H(C0) = 21	H(C180) = 21
			B = 87	H(C90) = 21	H(C270) = 21

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		9470.9	9477.4	9469.9	9538.0	9726.5	10097.5	10764.7	
50°		9164.9	9149.8	9138.5	9190.8	9331.5	9685.0	10407.9	
55°		8850.1	8839.7	8821.9	8833.1	8927.4	9259.3	10011.2	
60°		8540.8	8497.7	8465.0	8434.0	8522.5	8804.4	9583.6	
65°		8183.3	8157.4	8060.8	8008.6	8068.0	8325.8	9115.6	
70°		7804.7	7682.4	7590.2	7499.9	7501.1	7686.9	8487.5	
75°		7289.6	7245.0	7013.6	6840.5	6748.1	6853.6	7604.2	
80°		6712.6	6585.7	6332.7	6011.5	5760.5	5627.4	6198.0	
85°		6212.7	6066.8	5741.8	5275.4	4720.0	4153.5	4228.3	

Photometric test report

Family Monsun® 21	Order number: 51FB207L440J EAN: 4058352757222	LP number 59394_10
------------------------------------	--	-------------------------------------



Luminance values in cd/m²

γ 65°	γ 70°	γ 75°	γ 80°	γ 85°
--------------	--------------	--------------	--------------	--------------

