

Photometric test report

Family Monsun® 12	Order number: 51FP109P460H EAN: 4058352376300	LP number 58939_6
	Version prismatic diffuser, opal, PMMA, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG CLOi Rated values Net luminous flux = 6100 lm Power consumption = 34.0 W Luminous efficacy = 179.4 lm/W	serial documentation 09.07.2020
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 340 cd/klm**



Classifications	
DIN 5040	A 4 1
CIE	N1=47 N2=77 N3=93 N4=94 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	94.2%
ϕ_o	5.8%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 12	Order number: 51FP109P460H EAN: 4058352376300	LP number 58939_6
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	340.1	340.1	340.1	340.1	340.1	340.1	340.1	2.0	2.0
5°	339.4	338.3	336.5	337.9	339.5	339.4	339.8	16.2	18.2
10°	333.5	333.0	331.2	332.8	334.6	334.7	335.0	31.7	49.9
15°	324.2	324.2	322.5	324.2	326.1	326.4	326.9	46.1	96.0
20°	311.0	311.6	310.1	311.9	314.1	314.7	315.3	58.6	154.6
25°	294.4	295.4	294.1	296.0	298.4	299.4	300.2	68.7	223.4
30°	275.2	276.6	275.1	276.8	279.4	280.7	281.6	76.1	299.5
35°	253.9	255.2	253.8	254.9	257.1	258.4	259.7	80.5	380.0
40°	231.8	232.9	231.3	231.1	232.5	233.8	235.1	81.9	461.9
45°	209.4	209.9	207.8	205.9	206.1	206.6	208.2	80.4	542.4
50°	187.2	187.1	184.8	181.3	179.3	178.3	179.7	76.6	619.0
55°	165.5	164.8	162.1	157.0	153.1	150.2	150.9	70.7	689.7
60°	143.9	142.9	139.5	133.7	127.9	123.2	122.7	63.3	753.0
65°	123.6	122.5	117.8	111.0	104.2	97.9	96.0	54.9	808.0
70°	104.7	103.3	97.1	89.4	81.7	74.3	71.0	45.8	853.8
75°	86.1	84.4	77.8	69.2	60.2	52.2	47.8	36.3	890.0
80°	68.0	66.1	60.2	50.5	40.7	32.1	26.9	26.7	916.7
85°	51.8	50.0	44.6	35.3	24.7	15.7	10.1	18.3	935.0
90°	40.8	39.2	34.4	26.0	15.9	6.9	1.8	13.1	948.2
95°	34.8	33.5	29.7	22.7	13.6	5.1	1.6	11.2	959.3
100°	29.9	28.8	25.4	19.2	11.3	3.7	1.4	9.4	968.7
105°	25.7	24.7	21.4	16.1	8.8	2.4	1.2	7.7	976.4
110°	22.1	20.9	18.0	13.0	6.6	1.4	1.1	6.1	982.5
115°	19.0	17.8	15.0	10.4	4.7	1.2	1.1	4.9	987.4
120°	16.0	14.8	12.2	7.9	3.1	1.2	1.0	3.8	991.2
125°	13.0	11.9	9.4	5.6	1.7	1.1	0.9	2.7	993.9
130°	10.1	9.1	6.9	3.7	1.4	1.1	1.0	1.9	995.9
135°	7.3	6.5	4.6	2.1	1.4	1.1	1.1	1.3	997.1
140°	4.8	4.1	2.7	1.7	1.4	1.1	1.1	0.8	998.0
145°	2.6	2.3	1.9	1.7	1.4	1.2	1.2	0.5	998.5
150°	2.0	2.0	1.9	1.6	1.3	1.3	1.3	0.4	998.9
155°	1.9	1.9	1.7	1.6	1.4	1.4	1.4	0.4	999.3
160°	1.7	1.7	1.6	1.4	1.4	1.4	1.4	0.3	999.6
165°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.8
170°	1.3	1.4	1.4	1.4	1.4	1.4	1.4	0.1	999.9
175°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 12	Order number: 51FP109P460H EAN: 4058352376300	LP number 58939_6
-----------------------------	--	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	20.1	21.8	20.5	22.1	22.4	20.1	21.8	20.4	22.1	22.4
	3H	21.8	23.4	22.2	23.7	24.1	21.5	23.0	21.8	23.3	23.7
	4H	22.7	24.1	23.1	24.5	24.8	22.0	23.4	22.4	23.8	24.2
	6H	23.4	24.8	23.8	25.1	25.5	22.4	23.7	22.8	24.1	24.5
	8H	23.8	25.0	24.2	25.4	25.8	22.5	23.8	22.9	24.1	24.5
	12H	24.1	25.3	24.5	25.7	26.1	22.5	23.7	23.0	24.1	24.6
4H	2H	20.8	22.3	21.2	22.6	23.0	20.8	22.2	21.2	22.6	23.0
	3H	22.7	24.0	23.2	24.4	24.8	22.4	23.6	22.8	24.0	24.4
	4H	23.7	24.8	24.1	25.2	25.7	23.0	24.1	23.4	24.5	25.0
	6H	24.6	25.6	25.1	26.0	26.5	23.5	24.5	23.9	24.9	25.4
	8H	25.0	25.9	25.5	26.4	26.9	23.6	24.6	24.1	25.0	25.5
	12H	25.4	26.3	25.9	26.7	27.2	23.7	24.6	24.2	25.0	25.5
8H	4H	24.0	24.9	24.5	25.4	25.9	23.4	24.3	23.9	24.8	25.2
	6H	25.1	25.9	25.6	26.3	26.8	24.0	24.8	24.5	25.3	25.8
	8H	25.6	26.3	26.1	26.8	27.3	24.2	24.9	24.7	25.4	25.9
	12H	26.2	26.8	26.7	27.3	27.8	24.4	25.0	24.9	25.5	26.0
12H	4H	24.1	24.9	24.5	25.3	25.8	23.5	24.3	24.0	24.8	25.3
	6H	25.2	25.9	25.7	26.3	26.9	24.2	24.9	24.7	25.3	25.8
	8H	25.8	26.4	26.3	26.9	27.4	24.5	25.0	25.0	25.5	26.1

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1590	H(C0) = 21	H(C180) = 21
			B = 87	H(C90) = 21	H(C270) = 21

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		10518.2	10583.4	10660.8	10883.7	11353.5	11982.2	12813.5	
50°		9975.8	10012.7	10087.6	10241.5	10628.8	11225.9	12136.7	
55°		9459.4	9470.5	9528.5	9603.5	9902.9	10424.7	11384.5	
60°		8949.2	8941.6	8957.2	8985.6	9182.9	9613.9	10582.0	
65°		8500.5	8480.1	8408.3	8355.0	8472.3	8796.6	9741.5	
70°		8115.3	8069.5	7860.1	7711.6	7725.3	7935.9	8838.5	
75°		7713.7	7640.9	7347.7	7049.7	6874.8	6945.7	7765.0	
80°		7288.0	7167.0	6873.3	6343.4	5901.7	5705.3	6350.0	
85°		6977.4	6829.7	6510.4	5846.1	4969.3	4257.9	4434.7	

Photometric test report

Family Monsun® 12	Order number: 51FP109P460H EAN: 4058352376300	LP number 58939_6
------------------------------------	--	------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco

