




Photometric test report

Family Spot 21	Order number: 51SE12MBD5B EAN: 4058352716601	LP number 59384_3										
	<table border="0"> <tr> <td>Version</td> <td>reflector, cover panel, PC, narrow distribution</td> </tr> <tr> <td>Lamps</td> <td>LED 4000 K CRI ≥ 90</td> </tr> <tr> <td>Controlgear</td> <td>ECG Multilumen</td> </tr> <tr> <td>Setting</td> <td>factory setting: DIP-Step=14</td> </tr> <tr> <td>Rated values</td> <td>Net luminous flux = 5250 lm Power consumption = 39.5 W Luminous efficacy = 132.9 lm/W</td> </tr> </table>	Version	reflector, cover panel, PC, narrow distribution	Lamps	LED 4000 K CRI ≥ 90	Controlgear	ECG Multilumen	Setting	factory setting: DIP-Step=14	Rated values	Net luminous flux = 5250 lm Power consumption = 39.5 W Luminous efficacy = 132.9 lm/W	serial documentation 14.02.2023
Version	reflector, cover panel, PC, narrow distribution											
Lamps	LED 4000 K CRI ≥ 90											
Controlgear	ECG Multilumen											
Setting	factory setting: DIP-Step=14											
Rated values	Net luminous flux = 5250 lm Power consumption = 39.5 W Luminous efficacy = 132.9 lm/W											
												

Luminous intensity in cd/klm C180-0 **Imax: 5631 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=95 N2=98 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21	Order number: 51SE12MBD5B EAN: 4058352716601	LP number 59384_3
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	5630.9	1.3	1.3
1°	5563.8	10.6	12.0
2°	5452.3	20.9	32.9
3°	5253.2	30.1	63.0
4°	4992.9	38.2	101.2
5°	4624.7	44.2	145.4
6°	4116.1	47.2	192.6
7°	3563.6	47.6	240.2
8°	2975.5	45.4	285.6
9°	2466.1	42.3	327.9
10°	2068.6	39.4	367.3
11°	1734.5	36.3	403.6
12°	1497.3	34.1	437.8
13°	1298.1	32.0	469.8
14°	1124.5	29.8	499.6
15°	997.0	28.3	527.9
16°	883.3	26.7	554.6
17°	791.2	25.4	580.0
18°	719.9	24.4	604.4
19°	657.0	23.5	627.8
20°	607.4	22.8	650.6
21°	567.0	22.3	672.9
22°	528.8	21.7	694.6
23°	501.0	21.5	716.1
24°	477.4	21.3	737.4
25°	457.0	21.2	758.5
26°	440.6	21.2	779.7
27°	425.0	21.2	800.9
28°	408.0	21.0	821.9
29°	383.2	20.4	842.3
30°	346.7	19.0	861.3
31°	309.5	17.5	878.8
32°	269.8	15.7	894.4
33°	226.5	13.5	908.0
34°	186.7	11.4	919.4
35°	144.7	9.1	928.5
36°	108.4	7.0	935.5
37°	75.1	5.0	940.5
38°	48.0	3.2	943.7
39°	33.2	2.3	946.0
40°	25.7	1.8	947.8
41°	21.0	1.5	949.3
42°	18.4	1.3	950.7
43°	17.3	1.3	952.0
44°	16.5	1.3	953.2
45°	15.9	1.2	954.4
46°	15.7	1.2	955.7

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	15.2	1.2	956.9
48°	15.2	1.2	958.1
49°	14.8	1.2	959.4
50°	14.9	1.3	960.6
51°	15.0	1.3	961.9
52°	15.1	1.3	963.2
53°	15.9	1.4	964.6
54°	16.8	1.5	966.1
55°	18.1	1.6	967.7
56°	19.7	1.8	969.5
57°	20.9	1.9	971.4
58°	21.3	2.0	973.4
59°	20.6	1.9	975.3
60°	18.8	1.8	977.1
61°	16.0	1.5	978.7
62°	13.5	1.3	980.0
63°	11.7	1.1	981.1
64°	10.7	1.1	982.2
65°	10.2	1.0	983.2
66°	9.8	1.0	984.2
67°	9.3	0.9	985.1
68°	9.1	0.9	986.0
69°	8.8	0.9	986.9
70°	8.5	0.9	987.8
71°	8.5	0.9	988.7
72°	8.6	0.9	989.6
73°	8.4	0.9	990.5
74°	8.1	0.9	991.3
75°	7.7	0.8	992.1
76°	7.8	0.8	993.0
77°	7.7	0.8	993.8
78°	7.1	0.8	994.6
79°	7.0	0.8	995.3
80°	6.6	0.7	996.0
81°	6.2	0.7	996.7
82°	5.6	0.6	997.3
83°	4.9	0.5	997.8
84°	4.2	0.5	998.3
85°	3.7	0.4	998.7
86°	3.1	0.3	999.1
87°	2.8	0.3	999.4
88°	2.2	0.2	999.6
89°	2.5	0.3	999.9
90°	2.2	0.2	1000.1

Photometric test report

Family Spot 21	Order number: 51SE12MBD5B EAN: 4058352716601	LP number 59384_3
-------------------	---	----------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	20.8	21.8	21.2	22.1	22.4	20.8	21.8	21.2	22.1	22.4
	3H	21.3	22.1	21.7	22.4	22.8	21.3	22.1	21.7	22.4	22.8
	4H	21.6	22.4	22.0	22.8	23.2	21.6	22.4	22.0	22.8	23.2
	6H	22.0	22.9	22.4	23.2	23.6	22.0	22.9	22.4	23.2	23.6
	8H	22.5	23.1	22.9	23.5	23.9	22.5	23.1	22.9	23.5	23.9
	12H	22.6	23.3	23.1	23.7	24.1	22.6	23.3	23.1	23.7	24.1
4H	2H	20.9	21.7	21.3	22.0	22.4	20.9	21.7	21.3	22.0	22.4
	3H	21.5	22.2	21.9	22.6	23.0	21.5	22.2	21.9	22.6	23.0
	4H	22.1	22.7	22.5	23.1	23.5	22.1	22.7	22.5	23.1	23.5
	6H	22.7	23.3	23.2	23.8	24.2	22.7	23.3	23.2	23.8	24.2
	8H	23.3	23.7	23.8	24.2	24.7	23.3	23.7	23.8	24.2	24.7
	12H	23.5	24.0	23.9	24.4	24.9	23.5	24.0	23.9	24.4	24.9
8H	4H	22.3	22.8	22.8	23.2	23.7	22.3	22.8	22.8	23.2	23.7
	6H	23.4	23.7	23.9	24.2	24.7	23.4	23.7	23.9	24.2	24.7
	8H	23.8	24.2	24.3	24.7	25.2	23.8	24.2	24.3	24.7	25.2
	12H	24.1	24.5	24.6	25.0	25.6	24.1	24.5	24.6	25.0	25.6
12H	4H	22.2	22.7	22.7	23.2	23.7	22.2	22.7	22.7	23.2	23.7
	6H	23.3	23.7	23.8	24.2	24.7	23.3	23.7	23.8	24.2	24.7
	8H	23.8	24.2	24.4	24.7	25.3	23.8	24.2	24.4	24.7	25.3


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 79
-----------------	---------------------------------	--------------------------------------

C-planes	0°
γ	Luminance in cd/m ²
45°	24037.0
50°	24805.9
55°	33888.5
60°	40220.6
65°	25918.8
70°	26665.4
75°	31740.5
80°	40634.8
85°	46022.6

Photometric test report

Family Spot 21	Order number: 51SE12MBD5B EAN: 4058352716601	LP number 59384_3
--------------------------	---	-----------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Spot 21	Order number: 51SE12MBD5B EAN: 4058352716601	LP number 59384_3
--------------------------	---	-----------------------------

Multilumen Table	environmental temperature: 25°C	siteco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
15	ON	ON	ON	ON	5460	41.5
14	ON	ON	ON	OFF	5250	39.5
13	ON	ON	OFF	ON	5040	37.5
12	ON	ON	OFF	OFF	4810	35.6
11	ON	OFF	ON	ON	4560	33.4
10	ON	OFF	ON	OFF	4330	31.4
9	ON	OFF	OFF	ON	4090	29.4
8	ON	OFF	OFF	OFF	3830	27.4
7	OFF	ON	ON	ON	3630	25.7
6	OFF	ON	ON	OFF	3390	23.9
5	OFF	ON	OFF	ON	3120	21.8
4	OFF	ON	OFF	OFF	2870	19.9
3	OFF	OFF	ON	ON	2560	17.7
2	OFF	OFF	ON	OFF	2300	15.8
1	OFF	OFF	OFF	ON	2010	13.8
0	OFF	OFF	OFF	OFF	1730	11.9