


Photometric test report

Family Spot 21	Order number: 51SE62MBA5B EAN: 4058352769898	LP number 59384_7
Version	reflector, cover panel, PC, narrow distribution	serial documentation 14.02.2023
Lamps	LED 2700 K CRI ≥ 90	
Controlgear	ECG Multilumen	
Setting	factory setting: DIP-Step=14	
Rated values	Net luminous flux = 5040 lm Power consumption = 39.7 W Luminous efficacy = 127 lm/W	



Luminous intensity in cd/klm C180-0 **Imax: 5631 cd/klm**



Classifications	
DIN 5040	A 8 0
CIE	N1=95 N2=98 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Spot 21	Order number: 51SE62MBA5B EAN: 4058352769898	LP number 59384_7
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	5630.9	1.3	1.3
1°	5563.8	10.6	12.0
2°	5452.3	20.9	32.9
3°	5253.2	30.1	63.0
4°	4992.9	38.2	101.2
5°	4624.7	44.2	145.4
6°	4116.1	47.2	192.6
7°	3563.6	47.6	240.2
8°	2975.5	45.4	285.6
9°	2466.1	42.3	327.9
10°	2068.6	39.4	367.3
11°	1734.5	36.3	403.6
12°	1497.3	34.1	437.8
13°	1298.1	32.0	469.8
14°	1124.5	29.8	499.6
15°	997.0	28.3	527.9
16°	883.3	26.7	554.6
17°	791.2	25.4	580.0
18°	719.9	24.4	604.4
19°	657.0	23.5	627.8
20°	607.4	22.8	650.6
21°	567.0	22.3	672.9
22°	528.8	21.7	694.6
23°	501.0	21.5	716.1
24°	477.4	21.3	737.4
25°	457.0	21.2	758.5
26°	440.6	21.2	779.7
27°	425.0	21.2	800.9
28°	408.0	21.0	821.9
29°	383.2	20.4	842.3
30°	346.7	19.0	861.3
31°	309.5	17.5	878.8
32°	269.8	15.7	894.4
33°	226.5	13.5	908.0
34°	186.7	11.4	919.4
35°	144.7	9.1	928.5
36°	108.4	7.0	935.5
37°	75.1	5.0	940.5
38°	48.0	3.2	943.7
39°	33.2	2.3	946.0
40°	25.7	1.8	947.8
41°	21.0	1.5	949.3
42°	18.4	1.3	950.7
43°	17.3	1.3	952.0
44°	16.5	1.3	953.2
45°	15.9	1.2	954.4
46°	15.7	1.2	955.7

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	15.2	1.2	956.9
48°	15.2	1.2	958.1
49°	14.8	1.2	959.4
50°	14.9	1.3	960.6
51°	15.0	1.3	961.9
52°	15.1	1.3	963.2
53°	15.9	1.4	964.6
54°	16.8	1.5	966.1
55°	18.1	1.6	967.7
56°	19.7	1.8	969.5
57°	20.9	1.9	971.4
58°	21.3	2.0	973.4
59°	20.6	1.9	975.3
60°	18.8	1.8	977.1
61°	16.0	1.5	978.7
62°	13.5	1.3	980.0
63°	11.7	1.1	981.1
64°	10.7	1.1	982.2
65°	10.2	1.0	983.2
66°	9.8	1.0	984.2
67°	9.3	0.9	985.1
68°	9.1	0.9	986.0
69°	8.8	0.9	986.9
70°	8.5	0.9	987.8
71°	8.5	0.9	988.7
72°	8.6	0.9	989.6
73°	8.4	0.9	990.5
74°	8.1	0.9	991.3
75°	7.7	0.8	992.1
76°	7.8	0.8	993.0
77°	7.7	0.8	993.8
78°	7.1	0.8	994.6
79°	7.0	0.8	995.3
80°	6.6	0.7	996.0
81°	6.2	0.7	996.7
82°	5.6	0.6	997.3
83°	4.9	0.5	997.8
84°	4.2	0.5	998.3
85°	3.7	0.4	998.7
86°	3.1	0.3	999.1
87°	2.8	0.3	999.4
88°	2.2	0.2	999.6
89°	2.5	0.3	999.9
90°	2.2	0.2	1000.1

Photometric test report

Family Spot 21	Order number: 51SE62MBA5B EAN: 4058352769898	LP number 59384_7
-------------------	---	----------------------

UGR-Table	Standard room	sitEco
-----------	---------------	--------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	20.7	21.7	21.0	22.0	22.3	20.7	21.7	21.0	22.0	22.3
	3H	21.2	22.0	21.6	22.3	22.7	21.2	22.0	21.6	22.3	22.7
	4H	21.5	22.3	21.9	22.6	23.0	21.5	22.3	21.9	22.6	23.0
	6H	21.9	22.7	22.3	23.1	23.5	21.9	22.7	22.3	23.1	23.5
	8H	22.4	23.0	22.8	23.4	23.8	22.4	23.0	22.8	23.4	23.8
	12H	22.5	23.2	22.9	23.6	24.0	22.5	23.2	22.9	23.6	24.0
4H	2H	20.7	21.5	21.1	21.9	22.3	20.7	21.5	21.1	21.9	22.3
	3H	21.4	22.0	21.8	22.4	22.8	21.4	22.0	21.8	22.4	22.8
	4H	21.9	22.5	22.4	22.9	23.4	21.9	22.5	22.4	22.9	23.4
	6H	22.6	23.2	23.0	23.6	24.1	22.6	23.2	23.0	23.6	24.1
	8H	23.1	23.6	23.6	24.0	24.5	23.1	23.6	23.6	24.0	24.5
	12H	23.3	23.8	23.8	24.3	24.8	23.3	23.8	23.8	24.3	24.8
8H	4H	22.2	22.6	22.6	23.1	23.5	22.2	22.6	22.6	23.1	23.5
	6H	23.2	23.6	23.8	24.0	24.6	23.2	23.6	23.8	24.0	24.6
	8H	23.7	24.0	24.2	24.5	25.0	23.7	24.0	24.2	24.5	25.0
	12H	24.0	24.4	24.5	24.9	25.4	24.0	24.4	24.5	24.9	25.4
12H	4H	22.1	22.6	22.6	23.0	23.5	22.1	22.6	22.6	23.0	23.5
	6H	23.1	23.6	23.6	24.1	24.6	23.1	23.6	23.6	24.1	24.6
	8H	23.7	24.1	24.2	24.6	25.1	23.7	24.1	24.2	24.6	25.1


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 79
-----------------	---------------------------------	--------------------------------------

C-planes	0°
γ	Luminance in cd/m ²
45°	23075.5
50°	23813.7
55°	32533.0
60°	38611.8
65°	24882.1
70°	25598.8
75°	30470.9
80°	39009.5
85°	44181.7

Photometric test report

Family Spot 21	Order number: 51SE62MBA5B EAN: 4058352769898	LP number 59384_7
--------------------------	---	-----------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family
Spot 21

Order number: 51SE62MBA5B
EAN: 4058352769898

LP number
59384_7

Multilumen Table

environmental temperature: 25°C



DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
15	ON	ON	ON	ON	5240	41.7
14	ON	ON	ON	OFF	5040	39.7
13	ON	ON	OFF	ON	4830	37.6
12	ON	ON	OFF	OFF	4620	35.5
11	ON	OFF	ON	ON	4370	33.4
10	ON	OFF	ON	OFF	4150	31.4
9	ON	OFF	OFF	ON	3920	29.4
8	ON	OFF	OFF	OFF	3680	27.3
7	OFF	ON	ON	ON	3480	25.8
6	OFF	ON	ON	OFF	3250	23.9
5	OFF	ON	OFF	ON	3000	21.9
4	OFF	ON	OFF	OFF	2760	20.0
3	OFF	OFF	ON	ON	2460	17.8
2	OFF	OFF	ON	OFF	2210	15.9
1	OFF	OFF	OFF	ON	1930	13.9
0	OFF	OFF	OFF	OFF	1660	12.0