




Photometric test report

Family Licross® Recessed	Order number: 51TL14CN475F EAN: 4058352265031	LP number 58683_9
	Version cover frosted, asymmetric distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-Multilumen CLOi Rated values Net luminous flux = 7640 lm Power consumption = 48.0 W Luminous efficacy = 159.2 lm/W	serial documentation 15.11.2019
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 681 cd/klm**



Classifications	
DIN 5040	A 4 0
CIE	N1=56 N2=84 N3=97 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® Recessed	Order number: 51TL14CN475F EAN: 4058352265031	LP number 58683_9
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	0°	15° 345°	30° 330°	45° 315°	60° 300°	75° 285°	90° 270°
γ	Luminous intensity in cd/klm						
0°	423.3	423.3	423.3	423.3	423.3	423.3	423.3
5°	492.9	491.4	480.7	469.8	456.1	438.7	421.2
10°	571.7	566.6	544.9	518.0	484.6	447.0	411.0
15°	644.7	637.1	605.9	562.5	507.2	447.4	393.4
20°	680.9	674.8	644.8	594.0	519.7	438.2	368.1
25°	657.9	657.6	642.1	600.0	518.2	419.3	336.2
30°	585.4	591.2	594.0	574.0	501.7	394.4	301.7
35°	486.6	496.5	513.6	518.9	472.6	367.8	269.2
40°	391.6	400.9	423.7	447.6	435.3	342.4	241.4
45°	315.0	320.7	340.1	373.0	389.0	312.9	214.9
50°	257.7	259.4	273.6	305.9	334.9	275.1	186.5
55°	210.4	209.0	219.8	247.0	276.4	230.5	156.0
60°	164.7	163.2	172.4	194.6	218.3	183.7	125.4
65°	122.2	121.6	130.0	147.7	165.1	139.3	96.1
70°	85.2	85.7	92.4	106.6	118.3	100.1	70.2
75°	55.7	56.1	61.0	71.1	77.9	65.9	46.5
80°	31.6	31.9	35.4	40.3	43.4	36.3	25.7
85°	13.1	12.9	14.6	16.5	16.2	13.2	9.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C-planes	105° 255°	120° 240°	135° 225°	150° 210°	165° 195°	180°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0°	423.3	423.3	423.3	423.3	423.3	423.3	2.5	2.5
5°	404.2	389.5	375.7	365.6	362.1	361.8	20.2	22.8
10°	378.5	351.6	328.9	312.6	305.3	303.2	40.3	63.1
15°	347.6	311.7	283.3	263.5	254.2	251.1	59.8	123.0
20°	312.8	271.7	241.2	220.7	211.0	207.4	77.2	200.1
25°	275.0	232.7	202.9	183.7	174.4	171.0	89.9	290.0
30°	237.7	196.9	169.7	152.6	144.6	141.7	96.4	386.5
35°	204.1	165.0	141.0	127.0	121.0	118.9	96.9	483.4
40°	176.0	138.8	117.2	106.8	102.8	101.6	93.4	576.7
45°	151.3	116.9	98.0	90.5	88.3	87.8	87.1	663.9
50°	128.6	98.3	82.7	77.4	76.2	76.3	79.3	743.1
55°	107.1	82.4	69.7	65.9	65.5	66.0	69.9	813.0
60°	87.0	68.0	58.3	55.3	55.4	56.0	59.0	872.0
65°	68.6	55.0	47.7	45.3	45.4	45.9	47.4	919.5
70°	51.6	42.4	37.2	35.1	35.2	35.4	35.8	955.3
75°	35.3	29.8	26.5	24.5	24.4	24.5	24.7	980.0
80°	20.2	17.6	15.6	14.5	14.4	14.5	14.3	994.3
85°	7.8	7.1	6.7	6.2	6.2	6.3	5.7	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® Recessed	Order number: 51TL14CN475F EAN: 4058352265031	LP number 58683_9
-------------------------------------------	----------------------------------------------------------------	------------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	25.5	27.1	25.8	27.4	27.7	24.1	25.7	24.4	26.0	26.3
	3H	26.4	27.9	26.8	28.2	28.6	25.2	26.6	25.6	27.0	27.3
	4H	26.8	28.1	27.2	28.5	28.9	25.6	26.9	26.0	27.3	27.7
	6H	27.0	28.3	27.4	28.7	29.0	25.9	27.1	26.3	27.5	27.9
	8H	27.1	28.3	27.5	28.7	29.1	25.9	27.1	26.4	27.5	27.9
	12H	27.2	28.3	27.6	28.7	29.1	26.0	27.1	26.5	27.5	27.9
4H	2H	26.2	27.6	26.6	27.9	28.3	24.7	26.0	25.1	26.4	26.7
	3H	27.3	28.5	27.8	28.9	29.3	26.1	27.2	26.5	27.6	28.0
	4H	27.8	28.8	28.2	29.2	29.6	26.6	27.6	27.1	28.1	28.5
	6H	28.1	29.0	28.6	29.4	29.9	27.0	27.9	27.5	28.3	28.8
	8H	28.2	29.0	28.7	29.5	30.0	27.1	27.9	27.6	28.4	28.8
	12H	28.3	29.0	28.8	29.5	30.0	27.2	27.9	27.7	28.4	28.8
8H	4H	28.1	28.9	28.6	29.4	29.8	26.9	27.7	27.3	28.1	28.6
	6H	28.5	29.2	29.0	29.7	30.2	27.4	28.0	27.9	28.5	29.0
	8H	28.7	29.3	29.2	29.8	30.3	27.5	28.1	28.0	28.6	29.1
	12H	28.8	29.3	29.3	29.8	30.3	27.7	28.1	28.2	28.6	29.2
12H	4H	28.2	28.9	28.7	29.3	29.8	26.9	27.6	27.4	28.1	28.6
	6H	28.6	29.2	29.1	29.7	30.2	27.4	28.0	27.9	28.5	29.0
	8H	28.8	29.3	29.3	29.8	30.3	27.6	28.1	28.1	28.6	29.2

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500
			B = 58

C-planes	0°	15° 345°	30° 330°	45° 315°	60° 300°	75° 285°	90° 270°	105° 255°	120° 240°	135° 225°	150° 210°	165° 195°	180°
γ	Luminance in cd/m ²												
45°	39115.5	39822.4	42241.5	46325.9	48305.2	38864.1	26689.6	18795.8	14515.2	12165.1	11243.0	10968.8	10898.9
50°	35201.2	35434.5	37378.6	41785.2	45759.8	37577.4	25480.7	17574.6	13435.0	11293.1	10568.2	10415.2	10425.6
55°	32205.8	32002.4	33648.6	37812.4	42324.6	35285.1	23878.4	16403.1	12612.1	10670.8	10093.6	10029.8	10111.1
60°	28925.0	28669.7	30280.2	34179.1	38344.5	32257.5	22016.0	15274.6	11938.8	10232.7	9720.5	9723.9	9841.7
65°	25389.9	25258.6	27006.3	30686.1	34300.2	28938.4	19973.0	14252.4	11437.4	9906.2	9417.5	9431.8	9546.3
70°	21870.3	22014.9	23729.7	27378.5	30366.4	25706.0	18023.3	13244.3	10881.6	9559.8	8999.6	9035.3	9077.4
75°	18905.2	19034.1	20684.1	24117.8	26428.7	22366.7	15791.5	11980.5	10126.6	8976.4	8298.1	8278.8	8300.2
80°	16004.8	16145.4	17888.6	20396.4	21925.2	18352.3	13011.0	10222.0	8904.6	7881.0	7353.1	7302.0	7343.5
85°	13191.2	13044.1	14669.3	16587.7	16307.6	13273.8	9202.2	7870.2	7182.0	6703.4	6296.3	6264.1	6321.5


Photometric test report

Family Licross® Recessed	Order number: 51TL14CN475F EAN: 4058352265031	LP number 58683_9
-------------------------------------------	----------------------------------------------------------------	------------------------------------



Luminance values in cd/m²

γ 65°	γ 70°	γ 75°	γ 80°	γ 85°
--------------	--------------	--------------	--------------	--------------



Photometric test report

Family Licross® Recessed	Order number: 51TL14CN475F EAN: 4058352265031	LP number 58683_9
------------------------------------	----------------------------------------------------------------	-----------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption	Power consumption
	1	2	3			[W] end of lifetime	[W] average
1	A	C	E	7640	48.0	53.0	50.5
2	A	C	F	7320	45.8	50.7	48.2
3	A	D	E	6870	42.7	47.1	44.9
4	A	D	F	6340	39.1	43.1	41.1
5	B	C	E	5930	36.5	39.9	38.2
6	B	C	F	5390	33.0	36.0	34.5
7	B	D	E	4910	29.9	32.5	31.2
8	B	D	F	4420	26.9	29.4	28.2