


# Photometric test report

<b>Family</b> <b>Licross® Protected</b>	<b>Order number: 51TP11CN58XF</b> <b>EAN: 4058352447758</b>	<b>LP number</b> <b>58526_14</b>
	<b>Version</b> prismatic cover, frosted, narrow distribution <b>Lamps</b> LED 5000 K   CRI ≥ 80 <b>Controlgear</b> ECG-Multilumen CLOi <b>Rated values</b> Net luminous flux = 8150 lm Power consumption = 49.0 W Luminous efficacy = 166.3 lm/W	<b>serial documentation</b> <b>12.12.2019</b>
		

**Luminous intensity in cd/klm** C180-0 C270-90 **Imax: 1742 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=83 N2=94 N3=98 N4=100 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	100.0%
$\phi_o$	0.0%

**Measurement conditions**  
DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> <b>Licross® Protected</b>	<b>Order number: 51TP11CN58XF</b> <b>EAN: 4058352447758</b>	<b>LP number</b> <b>58526_14</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>sITeco</b>

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	1742.2	1742.2	1742.2	1742.2	1742.2	1742.2	1742.2	10.4	10.4
5°	1666.1	1675.3	1660.6	1665.8	1671.6	1669.6	1670.7	79.7	90.1
10°	1438.7	1454.0	1443.6	1449.9	1452.8	1449.1	1448.5	137.9	228.0
15°	1099.0	1113.1	1114.3	1128.7	1137.3	1134.2	1132.4	159.4	387.5
20°	752.6	761.9	768.4	788.3	803.8	805.8	803.7	147.1	534.5
25°	477.8	482.8	489.1	506.4	523.2	529.8	529.1	117.2	651.7
30°	296.4	297.2	300.0	310.9	324.6	332.2	333.5	85.9	737.6
35°	189.3	187.5	185.3	189.4	198.7	205.9	208.7	61.1	798.7
40°	131.6	127.9	121.5	120.2	125.3	132.4	136.6	44.7	843.4
45°	99.4	94.4	85.5	81.0	83.2	90.3	95.8	34.4	877.7
50°	79.8	74.4	64.7	58.7	59.3	65.8	72.1	27.9	905.7
55°	65.2	60.1	51.3	45.2	44.8	50.3	56.0	23.4	929.0
60°	52.4	48.1	41.3	36.1	35.0	38.9	43.4	19.6	948.6
65°	41.2	37.9	33.1	29.2	27.7	29.8	32.8	16.1	964.7
70°	31.9	29.5	26.2	23.4	21.7	22.1	23.6	12.9	977.6
75°	24.4	22.6	20.2	18.2	16.5	15.4	15.7	10.0	987.6
80°	18.3	17.0	15.2	13.6	11.8	9.9	9.2	7.3	994.9
85°	13.3	12.5	11.1	9.7	7.7	5.4	4.2	5.0	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

Family <b>Licross® Protected</b>	Order number: <b>51TP11CN58XF</b> EAN: <b>4058352447758</b>	LP number <b>58526_14</b>
-------------------------------------	--	------------------------------

UGR-Table	Standard room	<b>siteco</b>	
-----------	---------------	---------------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	15.9	17.1	16.2	17.4	17.7	15.7	17.0	16.1	17.3	17.6
	3H	17.0	18.1	17.4	18.4	18.8	16.6	17.7	17.0	18.0	18.4
	4H	17.5	18.5	17.9	18.9	19.2	17.0	18.0	17.4	18.4	18.7
	6H	18.0	18.9	18.4	19.3	19.7	17.3	18.2	17.7	18.6	19.0
	8H	18.3	19.1	18.8	19.5	19.9	17.5	18.2	17.9	18.6	19.0
	12H	18.6	19.3	19.0	19.7	20.1	17.5	18.3	18.0	18.6	19.1
4H	2H	16.1	17.1	16.5	17.5	17.8	16.0	17.0	16.4	17.3	17.7
	3H	17.4	18.2	17.8	18.6	19.1	17.0	17.9	17.5	18.3	18.7
	4H	18.1	18.8	18.5	19.2	19.7	17.5	18.3	18.0	18.7	19.1
	6H	18.7	19.3	19.2	19.8	20.2	17.9	18.6	18.4	19.0	19.5
	8H	19.0	19.6	19.5	20.0	20.5	18.1	18.6	18.5	19.1	19.6
	12H	19.4	19.9	19.9	20.3	20.8	18.2	18.7	18.7	19.1	19.6
8H	4H	18.2	18.8	18.7	19.2	19.7	17.7	18.3	18.2	18.7	19.2
	6H	19.0	19.5	19.5	19.9	20.5	18.3	18.7	18.8	19.2	19.7
	8H	19.4	19.8	19.9	20.3	20.9	18.5	18.9	19.0	19.4	19.9
	12H	19.9	20.2	20.4	20.7	21.3	18.7	19.0	19.2	19.5	20.1
12H	4H	18.3	18.7	18.8	19.2	19.7	17.8	18.3	18.3	18.7	19.2
	6H	19.1	19.4	19.6	19.9	20.5	18.4	18.7	18.9	19.2	19.7
	8H	19.5	19.9	20.1	20.4	20.9	18.6	19.0	19.2	19.5	20.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:		L = 1480	H(C0) = 13	H(C180) = 13
				B = 78	H(C90) = 0	H(C270) = 0

C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		8508.8	8118.9	7457.5	7237.0	7671.8	8641.9	9561.3	
50°		7312.3	6853.0	6064.7	5654.9	5923.4	6878.1	7917.3	
55°		6479.4	6011.3	5238.0	4761.6	4930.6	5830.7	6897.8	
60°		5739.7	5316.0	4667.0	4228.5	4313.7	5112.1	6126.1	
65°		5073.7	4711.4	4226.9	3892.0	3922.5	4563.1	5483.8	
70°		4520.7	4216.5	3872.2	3644.7	3652.4	4070.9	4865.3	
75°		4104.2	3851.0	3589.6	3447.6	3436.0	3624.4	4295.1	
80°		3816.9	3611.3	3394.6	3317.4	3250.4	3230.9	3735.5	
85°		3700.2	3568.9	3395.7	3348.1	3213.6	2947.1	3371.4	


**Photometric test report**

**Family**  
Licross® Protected

**Order number: 51TP11CN58XF**  
**EAN: 4058352447758**

**LP number**  
**58526\_14**

**Luminance values in cd/m<sup>2</sup>**    γ 65°    γ 70°    γ 75°    γ 80°    γ 85°    **siteco**



### Photometric test report

Family <b>Licross® Protected</b>	Order number: <b>51TP11CN58XF</b> EAN: <b>4058352447758</b>	LP number <b>58526_14</b>
-------------------------------------	--	------------------------------

<b>Multilumen Table</b>	environmental temperature: 25°C	<b>sITeco</b>
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption	Power consumption
	1	2	3			[W] end of lifetime	[W] average
1	A	C	E	8150	49.0	54.4	51.7
2	A	C	F	7530	44.8	49.8	47.3
3	A	D	E	7040	41.7	46.2	44.0
4	A	D	F	6480	38.1	42.1	40.1
5	B	C	E	6030	35.5	39.0	37.2
6	B	C	F	5530	32.5	35.5	34.0
7	B	D	E	5020	29.4	32.0	30.7
8	B	D	F	4510	26.4	29.0	27.7