


# Photometric test report

<b>Family</b> <b>Lunis R LED</b>	<b>Order number:</b> 5LR610D4OB11AF + 5LR94685EE <b>EAN:</b> 4058352125915 + 4039806161208	<b>LP number</b> <b>58556_10</b>
	<b>Version</b> Downlight for recessed ceiling, diffuser disc, frosted, matt inner <b>Lamps</b> 1 x LED 4000K / CRI ≥ 80 (unbekannt LED 4000K / CRI = 80) <b>Controlgear</b> ECG-DALI <b>Setting</b> factory setting: High Lumen Output <b>Rated values</b> Net luminous flux = 3880 lm Power consumption = 37.0 W Luminous efficacy = 104.9 lm/W	<b>serial documentation</b> <b>03.05.2018</b>




**Luminous intensity in cd/klm** C180-0 C270-90 **Imax: 431 cd/klm**



Classifications	
DIN 5040	A 4 0
CIE	N1=54 N2=84 N3=97 N4=100 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	100.0%
$\phi_o$	0.0%

**Measurement conditions**  
 DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> Lunis R LED	<b>Order number: 5LR610D4OB11AF + 5LR94685EE</b> <b>EAN: 4058352125915 + 4039806161208</b>	<b>LP number</b> 58556_10
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	430.7	430.7	430.7	430.7	430.7	430.7	430.7	2.6	2.6
5°	428.8	428.7	428.5	428.4	428.2	428.0	427.8	20.5	23.0
10°	421.5	421.2	421.1	421.0	420.8	420.8	420.7	40.1	63.1
15°	407.6	407.5	407.4	407.4	407.2	407.2	407.1	57.8	120.9
20°	389.0	389.0	389.0	388.9	388.8	388.7	388.6	72.9	193.8
25°	365.8	365.9	365.8	365.8	365.6	365.7	365.6	84.7	278.5
30°	338.9	338.9	338.7	338.8	338.7	338.7	338.6	92.8	371.4
35°	307.2	307.4	307.2	307.2	307.2	307.2	307.0	96.6	468.0
40°	271.9	271.8	271.7	271.8	271.8	271.7	271.6	95.7	563.7
45°	233.9	233.9	233.9	233.9	233.9	233.9	233.9	90.7	654.4
50°	196.2	196.3	196.2	196.3	196.3	196.3	196.5	82.4	736.8
55°	160.5	160.6	160.6	160.8	160.8	160.9	161.0	72.2	809.0
60°	127.8	128.0	128.0	128.1	128.0	128.2	128.2	60.8	869.7
65°	98.4	98.5	98.5	98.6	98.7	98.8	98.7	49.0	918.7
70°	71.4	71.4	71.4	71.6	71.6	71.6	71.6	36.8	955.6
75°	47.1	47.1	47.2	47.3	47.3	47.3	47.3	25.0	980.6
80°	25.8	25.9	25.8	25.9	25.9	26.0	25.9	14.0	994.5
85°	10.1	10.0	10.0	10.0	10.0	9.9	10.0	5.4	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

<b>Family</b> Lunis R LED	<b>Order number:</b> 5LR610D4OB11AF + 5LR94685EE <b>EAN:</b> 4058352125915 + 4039806161208	<b>LP number</b> 58556_10
------------------------------	---	------------------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	21.4	23.0	21.8	23.4	23.7	21.4	23.1	21.8	23.4	23.7
	3H	22.7	24.1	23.0	24.4	24.8	22.7	24.1	23.0	24.5	24.8
	4H	23.1	24.5	23.5	24.8	25.2	23.1	24.5	23.5	24.8	25.2
	6H	23.4	24.7	23.8	25.0	25.4	23.4	24.7	23.9	25.1	25.5
	8H	23.6	24.7	24.0	25.1	25.5	23.6	24.7	24.0	25.1	25.5
	12H	23.6	24.7	24.0	25.1	25.5	23.6	24.7	24.1	25.1	25.5
4H	2H	22.0	23.4	22.4	23.8	24.1	22.1	23.4	22.4	23.8	24.1
	3H	23.4	24.6	23.9	25.0	25.4	23.5	24.6	23.9	25.0	25.4
	4H	24.0	25.0	24.4	25.4	25.9	24.0	25.1	24.5	25.5	25.9
	6H	24.4	25.3	24.9	25.7	26.2	24.4	25.3	24.9	25.8	26.2
	8H	24.5	25.4	25.0	25.8	26.3	24.6	25.4	25.0	25.8	26.3
	12H	24.6	25.4	25.1	25.8	26.3	24.7	25.4	25.1	25.8	26.3
8H	4H	24.3	25.1	24.7	25.5	26.0	24.3	25.1	24.7	25.5	26.0
	6H	24.7	25.4	25.2	25.9	26.4	24.8	25.4	25.3	25.9	26.4
	8H	24.9	25.5	25.4	26.0	26.5	24.9	25.5	25.4	26.0	26.5
	12H	25.1	25.6	25.6	26.0	26.6	25.1	25.6	25.6	26.1	26.6
12H	4H	24.3	25.0	24.8	25.5	26.0	24.3	25.0	24.8	25.5	26.0
	6H	24.8	25.4	25.3	25.9	26.4	24.8	25.4	25.3	25.9	26.4
	8H	25.0	25.5	25.5	26.0	26.5	25.0	25.5	25.5	26.0	26.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 308		
C-planes	$\gamma$	0°	15°	30°	45°	60°	75°	90°
		180°	165°	150°	135°	120°	105°	270°
		195°	210°	225°	240°	255°	270°	
		345°	330°	315°	300°	285°		
		Luminance in cd/m <sup>2</sup>						
45°		17228.7	17226.9	17224.0	17225.2	17226.9	17225.8	17224.0
50°		15893.3	15901.2	15895.3	15902.5	15906.4	15905.1	15919.6
55°		14572.2	14585.4	14584.7	14597.1	14602.3	14608.9	14613.3
60°		13314.6	13327.3	13326.3	13337.4	13333.9	13355.9	13355.1
65°		12126.5	12133.5	12134.5	12151.4	12165.4	12171.4	12166.4
70°		10868.4	10872.2	10873.4	10896.7	10894.3	10907.8	10905.4
75°		9480.3	9483.7	9498.2	9508.1	9514.5	9524.4	9522.7
80°		7737.3	7753.8	7747.8	7754.4	7761.3	7789.5	7776.0
85°		6006.8	5978.1	5967.3	5951.2	5963.1	5930.9	5969.1

**Photometric test report**

<b>Family</b> Lunis R LED	<b>Order number:</b> 5LR610D4OB11AF + 5LR94685EE <b>EAN:</b> 4058352125915 + 4039806161208	<b>LP number</b> 58556_10
------------------------------	---	------------------------------

**Luminance values in cd/m<sup>2</sup>**     γ 65°   γ 70°   γ 75°   γ 80°   γ 85°     **siteco**

