

Photometric test report

Family
Silica® 21



Order number: **51MX30TCT9B**
EAN: **4058352795811**

LP number
59412_76

serial
documentation
03.05.2023

Version Suspended luminaire, with homogeneous illumination, cover, opal, direct-/ indirect distribution, extremely wide distribution, UGR≤25, tunable white

Lamps LED 6500 K | CRI ≥ 80

Controlgear ECG-DALI

Setting individual position

Rated values Net luminous flux = 10300 lm
Power consumption = 84.4 W
Luminous efficacy = 122 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 204 cd/klm



Classifications

DIN 5040 C 4 2
CIE N1=47 N2=79 N3=96
N4=58 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 57.8%
 ϕ_o 42.2%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21	Order number: 51MX30TCT9B EAN: 4058352795811	LP number 59412_76
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	204.1	204.1	204.1	204.1	204.1	204.1	204.1	1.2	1.2
5°	203.5	203.8	203.3	203.3	203.4	203.8	203.6	9.7	10.9
10°	200.3	199.9	199.8	200.3	201.2	200.6	201.1	19.1	30.0
15°	196.9	196.3	195.1	196.0	196.7	197.0	196.8	27.9	57.9
20°	190.5	190.1	188.7	189.7	189.8	190.2	191.2	35.6	93.5
25°	180.9	181.1	180.3	181.3	182.3	182.2	183.2	42.1	135.5
30°	172.0	171.7	170.5	171.9	173.3	173.2	173.3	47.2	182.7
35°	160.6	160.7	159.7	160.3	160.9	161.7	162.5	50.6	233.3
40°	148.7	148.4	148.5	148.2	149.1	149.3	150.6	52.5	285.7
45°	134.5	134.5	134.8	134.8	135.4	135.8	137.6	52.4	338.1
50°	118.7	119.6	120.0	120.5	121.6	121.8	122.6	50.7	388.8
55°	104.0	104.1	104.8	105.3	106.3	106.3	107.2	47.3	436.2
60°	87.2	87.5	88.1	88.4	89.8	89.9	91.2	42.2	478.3
65°	70.0	70.7	71.5	72.5	73.2	73.9	73.9	35.9	514.2
70°	52.0	53.0	53.5	54.9	56.0	56.6	57.0	28.2	542.4
75°	34.3	35.1	35.7	36.9	38.2	39.1	39.4	19.6	562.0
80°	18.0	18.4	19.0	19.8	21.0	21.9	22.2	10.8	572.8
85°	5.8	6.0	6.3	6.8	7.4	8.1	8.3	3.8	576.6
90°	6.3	6.1	6.5	6.3	3.9	1.8	1.1	2.6	579.2
95°	21.6	22.1	23.8	22.9	15.1	7.9	4.1	9.5	588.7
100°	38.0	39.1	40.0	35.9	24.8	14.2	9.4	16.0	604.7
105°	54.7	56.0	55.9	49.2	34.1	21.4	15.7	22.2	626.9
110°	74.8	75.5	71.9	60.8	43.8	28.8	22.2	28.3	655.2
115°	92.7	92.3	86.1	71.6	53.1	36.3	29.5	33.2	688.4
120°	108.0	106.6	98.3	80.7	62.0	43.6	36.5	36.7	725.0
125°	119.6	116.6	106.6	89.4	69.8	50.5	44.0	38.5	763.5
130°	125.1	122.5	111.1	94.7	75.6	57.5	51.4	38.5	802.0
135°	126.1	123.5	112.8	98.1	79.9	63.9	58.8	36.9	838.9
140°	124.1	122.0	113.0	100.2	83.2	69.8	66.5	34.3	873.1
145°	121.3	120.0	112.4	100.8	86.1	75.2	72.7	31.0	904.1
150°	117.8	117.1	110.2	99.7	88.4	80.4	78.4	27.1	931.3
155°	113.3	112.8	106.2	98.4	90.0	85.0	83.4	22.8	954.1
160°	107.2	106.9	101.9	96.9	91.4	88.5	88.0	18.2	972.3
165°	101.6	101.0	98.5	95.2	92.8	91.2	91.2	13.6	985.9
170°	97.5	97.0	96.2	94.8	93.7	93.4	93.4	9.1	994.9
175°	94.9	94.8	94.2	94.0	94.0	94.0	94.0	4.5	999.4
180°	94.2	94.2	94.2	94.2	94.2	94.2	94.2	0.6	1000.0

Photometric test report

Family Silica® 21			Order number: 51MX30TCT9B EAN: 4058352795811							LP number 59412_76		
UGR-Table			Standard room							siteco		
Reflection factor of ceiling			0.7	0.7	0.5	0.5	0.3	0.7	0.7			0.5
Reflection factor of walls			0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor			0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions			View crosswise (C0)					View endwise (C90)				
x	y											
2H	2H		18.5	19.6	19.3	20.4	21.5	18.7	19.7	19.5	20.6	21.6
	3H		19.9	20.8	20.8	21.7	22.8	20.2	21.2	21.1	22.0	23.1
	4H		20.4	21.3	21.3	22.1	23.3	20.8	21.7	21.7	22.6	23.7
	6H		20.6	21.4	21.5	22.3	23.5	21.1	21.9	22.0	22.8	24.0
	8H		20.6	21.4	21.5	22.3	23.5	21.1	21.9	22.0	22.8	24.0
	12H		20.6	21.3	21.5	22.2	23.4	21.2	21.9	22.1	22.8	24.0
4H	2H		19.1	20.0	20.0	20.9	22.0	19.2	20.1	20.1	20.9	22.1
	3H		20.7	21.4	21.6	22.3	23.5	20.9	21.6	21.8	22.5	23.7
	4H		21.3	21.9	22.2	22.8	24.0	21.6	22.3	22.5	23.2	24.4
	6H		21.6	22.1	22.5	23.1	24.3	22.1	22.6	23.0	23.6	24.8
	8H		21.7	22.2	22.6	23.1	24.3	22.2	22.7	23.1	23.6	24.9
	12H		21.6	22.1	22.6	23.0	24.3	22.2	22.7	23.2	23.6	24.9
8H	4H		21.4	22.0	22.4	22.9	24.1	21.7	22.2	22.7	23.2	24.4
	6H		21.9	22.3	22.9	23.3	24.5	22.3	22.7	23.3	23.7	24.9
	8H		22.0	22.4	23.0	23.4	24.6	22.5	22.9	23.5	23.9	25.1
	12H		22.0	22.3	23.0	23.3	24.6	22.6	22.9	23.6	23.9	25.2
12H	4H		21.4	21.8	22.4	22.8	24.1	21.7	22.1	22.6	23.1	24.3
	6H		21.9	22.3	22.9	23.2	24.5	22.3	22.6	23.3	23.6	24.9
	8H		22.0	22.3	23.0	23.3	24.6	22.5	22.8	23.5	23.8	25.1

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 3000 B = 50	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45° 50° 55° 60°		13056.9	13064.8	13089.5	13091.1	13149.4	13184.0
		12684.2	12780.7	12817.0	12871.3	12990.5	13013.1
		12454.4	12468.3	12543.2	12605.7	12721.9	12722.9
		11975.5	12023.3	12093.0	12140.8	12334.0	12350.5
65° 70° 75° 80°		11373.7	11487.6	11620.0	11774.2	11887.0	12006.4
		10439.1	10635.5	10743.7	11017.5	11233.4	11371.9
		9099.0	9314.4	9464.8	9792.2	10122.5	10385.5
		7119.8	7256.2	7506.2	7831.2	8302.6	8656.9
85°		4582.2	4744.5	5001.3	5371.6	5850.7	6349.4

Photometric test report

Family
Silica® 21

Order number: 51MX30TCT9B
EAN: 4058352795811

LP number
59412_76

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

