

Photometric test report

Family
Silica® 21



Order number: **51MX31TAT7W**
EAN: **4058352685365**

LP number
59310_31

serial
documentation
03.05.2023

Version Suspended luminaire, reflector, black, direct-/indirect distribution, narrow distribution, $UGR \leq 16$ ($L65 \leq 3000 \text{ cd/m}^2$), tunable white

Lamps LED 6500 K | CRI ≥ 80

Controlgear ECG-DALI

Setting individual position

Rated values Net luminous flux = 6220 lm
Power consumption = 53.5 W
Luminous efficacy = 116.3 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 870 cd/klm



Classifications

DIN 5040 C 7 2
CIE N1=85 N2=99 N3=100
N4=60 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 59.6%
 ϕ_o 40.4%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21	Order number: 51MX31TAT7W EAN: 4058352685365	LP number 59310_31
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	870.3	870.3	870.3	870.3	870.3	870.3	870.3	5.2	5.2
5°	846.0	847.0	846.3	847.4	849.1	850.7	849.9	40.5	45.7
10°	729.9	730.5	735.4	740.2	741.6	737.5	738.7	70.1	115.8
15°	563.5	566.8	573.7	583.4	582.7	575.8	574.3	81.6	197.4
20°	436.6	435.3	429.7	429.7	431.1	427.8	432.4	80.9	278.3
25°	328.9	328.2	319.1	311.5	316.6	319.6	325.6	74.2	352.5
30°	247.8	246.0	233.3	230.7	239.5	241.8	245.2	65.7	418.2
35°	177.2	177.8	169.0	168.0	180.3	183.5	180.9	55.4	473.6
40°	120.1	121.7	120.2	121.8	131.6	132.5	129.5	44.2	517.8
45°	75.2	76.8	78.8	83.5	89.3	88.1	85.7	32.1	549.9
50°	44.3	46.1	49.1	53.4	57.3	54.4	51.5	21.6	571.5
55°	25.2	26.5	29.2	32.4	34.1	31.0	29.0	13.5	585.0
60°	8.3	10.2	15.9	18.3	18.2	12.9	10.8	6.7	591.7
65°	2.5	3.2	5.0	9.4	5.8	3.6	3.2	2.5	594.2
70°	1.1	1.1	1.0	1.8	1.2	1.4	1.5	0.7	594.9
75°	0.2	0.3	0.3	0.4	0.4	0.4	0.3	0.2	595.0
80°	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	595.1
85°	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.2	595.3
90°	5.7	5.5	5.8	5.6	3.2	1.1	0.4	2.2	597.5
95°	20.7	21.1	22.8	21.9	14.5	7.6	3.9	9.1	606.6
100°	36.3	37.4	38.2	34.3	23.7	13.6	9.0	15.3	621.9
105°	52.3	53.6	53.5	47.0	32.7	20.5	15.0	21.3	643.2
110°	71.5	72.2	68.8	58.2	41.9	27.5	21.3	27.0	670.2
115°	88.7	88.3	82.4	68.5	50.8	34.7	28.2	31.7	701.9
120°	103.3	102.0	94.0	77.2	59.3	41.7	35.0	35.1	737.0
125°	114.4	111.6	102.0	85.5	66.7	48.3	42.1	36.8	773.8
130°	119.7	117.2	106.2	90.6	72.3	55.0	49.2	36.8	810.6
135°	120.6	118.1	107.9	93.8	76.4	61.1	56.3	35.3	845.9
140°	118.7	116.7	108.1	95.8	79.5	66.7	63.6	32.8	878.7
145°	116.0	114.8	107.5	96.4	82.4	71.9	69.6	29.6	908.3
150°	112.6	112.0	105.4	95.3	84.5	76.9	75.0	25.9	934.3
155°	108.3	107.8	101.5	94.1	86.0	81.3	79.8	21.8	956.1
160°	102.5	102.2	97.5	92.7	87.4	84.6	84.2	17.4	973.5
165°	97.2	96.6	94.2	91.1	88.8	87.3	87.2	13.0	986.5
170°	93.2	92.7	92.0	90.7	89.7	89.4	89.3	8.7	995.2
175°	90.7	90.6	90.1	89.9	89.9	89.9	89.9	4.3	999.5
180°	90.1	90.1	90.1	90.1	90.1	90.1	90.1	0.5	1000.0

Photometric test report

Family Silica® 21		Order number: 51MX31TAT7W EAN: 4058352685365							LP number 59310_31	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
2H	x									
	y									
	2H	13.9	14.7	14.7	15.5	16.6	14.5	15.3	15.3	16.1
	3H	13.6	14.3	14.5	15.2	16.3	14.2	15.0	15.1	15.8
	4H	13.4	14.1	14.3	15.0	16.1	14.1	14.8	15.0	15.6
	6H	13.2	13.8	14.2	14.7	15.9	13.9	14.5	14.8	15.4
4H	8H	13.2	13.7	14.1	14.6	15.8	13.8	14.3	14.7	15.2
	12H	13.1	13.5	14.0	14.5	15.6	13.7	14.2	14.7	15.1
	2H	13.7	14.3	14.5	15.2	16.3	14.2	14.8	15.1	15.7
	3H	13.4	13.9	14.3	14.8	16.0	13.9	14.5	14.9	15.4
	4H	13.2	13.7	14.2	14.6	15.8	13.8	14.3	14.7	15.2
	6H	13.0	13.5	14.0	14.4	15.6	13.6	14.1	14.6	15.0
8H	8H	13.0	13.3	13.9	14.3	15.5	13.6	13.9	14.5	14.9
	12H	12.8	13.2	13.8	14.1	15.4	13.5	13.8	14.4	14.7
	4H	13.0	13.4	13.9	14.3	15.5	13.5	13.9	14.5	14.9
	6H	12.8	13.2	13.8	14.1	15.3	13.4	13.7	14.3	14.6
	8H	12.7	13.0	13.7	14.0	15.2	13.3	13.6	14.3	14.6
	12H	12.6	12.9	13.6	13.9	15.1	13.2	13.4	14.2	14.4
12H	4H	12.9	13.2	13.9	14.2	15.4	13.4	13.7	14.4	14.7
	6H	12.7	13.0	13.7	14.0	15.2	13.3	13.5	14.3	14.5
	8H	12.6	12.9	13.6	13.9	15.1	13.2	13.4	14.2	14.4

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1176 B = 49	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45°		11481.4	11728.8	12025.0	12747.8	13628.8	13454.0
50°		7443.7	7741.1	8252.8	8967.8	9613.8	9135.7
55°		4742.9	4994.6	5493.3	6092.3	6409.2	5839.9
60°		1795.1	2206.3	3437.5	3943.5	3930.1	2794.2
65°		638.8	808.1	1266.8	2394.5	1474.2	919.0
70°		338.6	360.4	305.5	579.8	393.2	455.7
75°		89.7	125.5	123.4	163.5	163.5	162.7
80°		32.3	35.4	42.3	51.0	64.0	77.7
85°		505.3	506.5	500.3	476.8	459.5	465.7

Photometric test report

Family
Silica® 21

Order number: 51MX31TAT7W
EAN: 4058352685365

LP number
59310_31

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

