


Photometric test report

Family Licross® 21 Protected	Order number: 52TP11DN48XG EAN: 4058352903667	LP number 58526_178
Version	prismatic cover, frosted, narrow distribution	serial documentation 03.08.2023
Lamps	LED 4000 K CRI ≥ 80	
Controlgear	ECG-DALI	
Rated values	Net luminous flux = 8000 lm Power consumption = 45.5 W Luminous efficacy = 175.8 lm/W	



Luminous intensity in cd/klm C180-0 C270-90 Imax: 1742 cd/klm



Classifications	
DIN 5040	A 7 0
CIE	N1=83 N2=94 N3=98 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Protected	Order number: 52TP11DN48XG EAN: 4058352903667	LP number 58526_178
-----------------------------------------------	----------------------------------------------------------------	--------------------------------------

sITeco

Table of values for luminous intensities	Maximum luminous intensity
-------------------------------------------------	-----------------------------------

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	1742.2	1742.2	1742.2	1742.2	1742.2	1742.2	1742.2	10.4	10.4
5°	1666.1	1675.3	1660.6	1665.8	1671.6	1669.6	1670.7	79.7	90.1
10°	1438.7	1454.0	1443.6	1449.9	1452.8	1449.1	1448.5	137.9	228.0
15°	1099.0	1113.1	1114.3	1128.7	1137.3	1134.2	1132.4	159.4	387.5
20°	752.6	761.9	768.4	788.3	803.8	805.8	803.7	147.1	534.5
25°	477.8	482.8	489.1	506.4	523.2	529.8	529.1	117.2	651.7
30°	296.4	297.2	300.0	310.9	324.6	332.2	333.5	85.9	737.6
35°	189.3	187.5	185.3	189.4	198.7	205.9	208.7	61.1	798.7
40°	131.6	127.9	121.5	120.2	125.3	132.4	136.6	44.7	843.4
45°	99.4	94.4	85.5	81.0	83.2	90.3	95.8	34.4	877.7
50°	79.8	74.4	64.7	58.7	59.3	65.8	72.1	27.9	905.7
55°	65.2	60.1	51.3	45.2	44.8	50.3	56.0	23.4	929.0
60°	52.4	48.1	41.3	36.1	35.0	38.9	43.4	19.6	948.6
65°	41.2	37.9	33.1	29.2	27.7	29.8	32.8	16.1	964.7
70°	31.9	29.5	26.2	23.4	21.7	22.1	23.6	12.9	977.6
75°	24.4	22.6	20.2	18.2	16.5	15.4	15.7	10.0	987.6
80°	18.3	17.0	15.2	13.6	11.8	9.9	9.2	7.3	994.9
85°	13.3	12.5	11.1	9.7	7.7	5.4	4.2	5.0	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 21 Protected	Order number: 52TP11DN48XG EAN: 4058352903667	LP number 58526_178
----------------------------------------	----------------------------------------------------------------	-------------------------------

UGR-Table		Standard room									
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	15.8	17.0	16.2	17.4	17.7	15.7	16.9	16.0	17.2	17.5
	3H	16.9	18.0	17.3	18.3	18.7	16.5	17.6	16.9	18.0	18.3
	4H	17.4	18.5	17.8	18.8	19.2	16.9	17.9	17.3	18.3	18.7
	6H	17.9	18.8	18.4	19.2	19.6	17.2	18.1	17.6	18.5	18.9
	8H	18.3	19.0	18.7	19.4	19.8	17.4	18.2	17.8	18.6	19.0
	12H	18.5	19.2	18.9	19.6	20.0	17.5	18.2	17.9	18.6	19.0
4H	2H	16.0	17.1	16.4	17.4	17.8	15.9	16.9	16.3	17.3	17.6
	3H	17.3	18.2	17.8	18.6	19.0	17.0	17.8	17.4	18.2	18.6
	4H	18.0	18.7	18.4	19.2	19.6	17.4	18.2	17.9	18.6	19.0
	6H	18.6	19.3	19.1	19.7	20.2	17.9	18.5	18.3	18.9	19.4
	8H	19.0	19.5	19.4	20.0	20.5	18.0	18.6	18.5	19.0	19.5
	12H	19.3	19.8	19.8	20.3	20.8	18.1	18.6	18.6	19.1	19.6
8H	4H	18.2	18.7	18.6	19.2	19.7	17.7	18.2	18.1	18.7	19.2
	6H	18.9	19.4	19.4	19.9	20.4	18.2	18.7	18.7	19.1	19.6
	8H	19.4	19.8	19.9	20.3	20.8	18.4	18.8	18.9	19.3	19.8
	12H	19.8	20.2	20.4	20.7	21.2	18.6	18.9	19.1	19.4	20.0
12H	4H	18.2	18.7	18.7	19.1	19.6	17.7	18.2	18.2	18.7	19.2
	6H	19.0	19.4	19.5	19.9	20.4	18.3	18.7	18.8	19.2	19.7
	8H	19.5	19.8	20.0	20.3	20.9	18.6	18.9	19.1	19.4	19.9

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1480	H(C0) = 13	H(C180) = 13
						B = 78	H(C90) = 0	H(C270) = 0
C-planes	γ	0°	15°	30°	45°	60°	75°	90°
		180°	165°	150°	135°	120°	105°	270°
		195°	210°	225°	240°	255°	285°	
		345°	330°	315°	300°			
		Luminance in cd/m ²						
45°		8352.2	7969.5	7320.2	7103.8	7530.6	8482.9	9385.4
50°		7177.7	6726.8	5953.1	5550.8	5814.4	6751.5	7771.6
55°		6360.2	5900.7	5141.6	4674.0	4839.8	5723.4	6770.8
60°		5634.0	5218.2	4581.1	4150.7	4234.3	5018.0	6013.3
65°		4980.3	4624.7	4149.1	3820.3	3850.3	4479.1	5382.9
70°		4437.5	4138.9	3800.9	3577.6	3585.1	3996.0	4775.7
75°		4028.7	3780.1	3523.5	3384.2	3372.8	3557.6	4216.1
80°		3746.7	3544.8	3332.1	3256.3	3190.5	3171.5	3666.8
85°		3632.1	3503.2	3333.2	3286.5	3154.4	2892.8	3309.3


Photometric test report

Family Licross® 21 Protected	Order number: 52TP11DN48XG EAN: 4058352903667	LP number 58526_178
-----------------------------------------------	----------------------------------------------------------------	--------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco



Photometric test report

Family Licross® 21 Protected	Order number: 52TP11DN48XG EAN: 4058352903667	LP number 58526_178
----------------------------------------	----------------------------------------------------------------	--------------------------------------

Dimming levels table	environmental temperature: 25°C	sITeco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	8000	45.5
95	241	252	7613	43.2
90	227	250	7194	40.6
85	214	248	6806	38.4
80	201	245	6412	36.2
75	188	243	6015	33.9
70	174	240	5587	31.5
65	162	238	5215	29.4
60	149	234	4812	27.2
55	136	231	4403	25.0
50	123	227	3991	22.7
45	111	224	3610	20.8
40	98	219	3194	18.6
35	86	214	2807	16.5
30	73	208	2388	14.3
25	61	202	1997	12.3
20	49	194	1606	10.2
15	37	183	1211	8.2
10	25	169	814	6.2
5	12	142	385	4.1
2	5	110	150	3.0