

Photometric test report

Family
Lunis 31



Order number: 51DN16ME41B
EAN: 4069025151940

Version

Lamps

Controlgear

Setting

Rated values

cover, diffuse, wide distribution, UGR≤22

LED 4000 K | CRI ≥ 80

ECG Multilumen


factory setting: DIP-Step=2

Net luminous flux = 1650 lm
Power consumption = 11.5 W
Luminous efficacy = 143.5 lm/W

LP number
59698_2

serial
documentation
12.12.2024

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 6 0	η_{LB}	100.0%
CIE	N1=76 N2=93 N3=99	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 31	Order number: 51DN16ME41B EAN: 4069025151940	LP number 59698_2
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	740.7	0.2	0.2
1°	741.2	1.4	1.6
2°	740.0	2.8	4.4
3°	738.4	4.2	8.7
4°	736.0	5.6	14.3
5°	731.9	7.0	21.3
6°	727.8	8.3	29.6
7°	722.3	9.7	39.3
8°	715.0	10.9	50.2
9°	708.1	12.1	62.3
10°	699.1	13.3	75.7
11°	690.1	14.4	90.1
12°	678.5	15.5	105.6
13°	668.1	16.5	122.1
14°	655.4	17.4	139.4
15°	642.0	18.2	157.7
16°	630.4	19.1	176.7
17°	616.9	19.8	196.5
18°	603.7	20.5	217.0
19°	592.6	21.2	238.1
20°	580.0	21.8	259.9
21°	569.8	22.4	282.3
22°	558.6	22.9	305.2
23°	549.1	23.5	328.7
24°	538.4	24.0	352.7
25°	528.2	24.5	377.2
26°	519.4	25.0	402.2
27°	509.2	25.3	427.5
28°	500.4	25.8	453.3
29°	489.2	26.0	479.3
30°	478.1	26.2	505.5
31°	465.9	26.3	531.8
32°	451.4	26.2	558.1
33°	434.8	26.0	584.0
34°	415.7	25.5	609.5
35°	396.8	25.0	634.5
36°	372.2	24.0	658.5
37°	347.0	22.9	681.4
38°	324.2	21.9	703.3
39°	297.1	20.5	723.8
40°	274.0	19.3	743.1
41°	247.1	17.8	760.9
42°	223.1	16.4	777.2
43°	200.9	15.0	792.3
44°	181.7	13.8	806.1
45°	160.7	12.5	818.6
46°	144.1	11.4	829.9

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	131.3	10.5	840.5
48°	118.0	9.6	850.1
49°	108.8	9.0	859.1
50°	102.0	8.6	867.6
51°	95.2	8.1	875.8
52°	90.5	7.8	883.6
53°	85.6	7.5	891.1
54°	81.6	7.2	898.3
55°	77.0	6.9	905.2
56°	72.6	6.6	911.8
57°	68.9	6.3	918.2
58°	64.6	6.0	924.2
59°	61.1	5.7	929.9
60°	57.1	5.4	935.3
61°	53.3	5.1	940.4
62°	50.3	4.9	945.3
63°	47.2	4.6	949.9
64°	44.3	4.4	954.3
65°	41.3	4.1	958.4
66°	38.9	3.9	962.3
67°	36.3	3.7	966.0
68°	33.6	3.4	969.4
69°	31.4	3.2	972.6
70°	29.0	3.0	975.6
71°	26.8	2.8	978.4
72°	24.7	2.6	980.9
73°	22.7	2.4	983.3
74°	20.8	2.2	985.5
75°	18.8	2.0	987.5
76°	17.3	1.8	989.3
77°	15.5	1.7	991.0
78°	14.1	1.5	992.5
79°	12.4	1.3	993.8
80°	10.8	1.2	995.0
81°	9.6	1.0	996.1
82°	8.2	0.9	996.9
83°	7.1	0.8	997.7
84°	5.8	0.6	998.4
85°	4.7	0.5	998.9
86°	3.6	0.4	999.3
87°	2.7	0.3	999.6
88°	2.1	0.2	999.8
89°	1.3	0.1	999.9
90°	1.0	0.1	1000.1

Photometric test report

Family Lunis 31			Order number: 51DN16ME41B EAN: 4069025151940							LP number 59698_2	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	20.5	21.9	20.9	22.2	22.5	20.5	21.9	20.9	22.2	22.5
	3H	21.1	22.3	21.4	22.6	23.0	21.1	22.3	21.4	22.6	23.0
	4H	21.3	22.4	21.7	22.8	23.1	21.3	22.4	21.7	22.8	23.1
	6H	21.4	22.5	21.8	22.8	23.2	21.4	22.5	21.8	22.8	23.2
	8H	21.5	22.5	22.0	22.9	23.3	21.5	22.5	22.0	22.9	23.3
	12H	21.6	22.4	22.0	22.8	23.2	21.6	22.4	22.0	22.8	23.2
4H	2H	20.7	21.9	21.1	22.2	22.6	20.7	21.9	21.1	22.2	22.6
	3H	21.4	22.4	21.9	22.8	23.2	21.4	22.4	21.9	22.8	23.2
	4H	21.7	22.6	22.2	23.0	23.4	21.7	22.6	22.2	23.0	23.4
	6H	22.0	22.7	22.4	23.1	23.6	22.0	22.7	22.4	23.1	23.6
	8H	22.1	22.7	22.5	23.2	23.6	22.1	22.7	22.5	23.2	23.6
	12H	22.1	22.7	22.6	23.2	23.6	22.1	22.7	22.6	23.2	23.6
8H	4H	21.8	22.5	22.3	22.9	23.4	21.8	22.5	22.3	22.9	23.4
	6H	22.1	22.7	22.6	23.1	23.7	22.1	22.7	22.6	23.1	23.7
	8H	22.3	22.7	22.8	23.2	23.7	22.3	22.7	22.8	23.2	23.7
	12H	22.4	22.8	22.9	23.3	23.8	22.4	22.8	22.9	23.3	23.8
12H	4H	21.9	22.4	22.3	22.9	23.4	21.9	22.4	22.3	22.9	23.4
	6H	22.2	22.6	22.7	23.1	23.6	22.2	22.6	22.7	23.1	23.6
	8H	22.3	22.7	22.8	23.2	23.7	22.3	22.7	22.8	23.2	23.7

Luminance table		Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	D = 146
C-planes		0°		
γ	Luminance in cd/m²			
45°	22397.3			
50°	15633.5			
55°	13230.5			
60°	11253.3			
65°	9640.0			
70°	8352.1			
75°	7176.5			
80°	6152.4			
85°	5362.3			

Photometric test report

Family
Lunis 31

Order number: 51DN16ME41B
EAN: 4069025151940

LP number
59698_2

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Lunis 31	Order number: 51DN16ME41B EAN: 4069025151940	LP number 59698_2
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting		Luminous flux [lm]	Power consumption [W]
	1	2		
2	OFF	ON	1650	11.5
1	ON	OFF	1350	9.5
0	OFF	OFF	1050	7.5