


Photometric test report

Family Licross® 11 Performance	Order number: 51TM16CN49XG EAN: 4058352929964	LP number 58520_414
	Version cover frosted, direct-/ indirect distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-Multilumen CLOi Rated values Net luminous flux = 9190 lm Power consumption = 49.4 W Luminous efficacy = 186 lm/W	serial documentation 14.11.2025





Luminous intensity in cd/klm C180-0 C270-90 **Imax: 452 cd/klm**



Classifications	
DIN 5040	B 5 1
CIE	N1=65 N2=88 N3=96 N4=79 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	79.3%
ϕ_o	20.7%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Performance	Order number: 51TM16CN49XG EAN: 4058352929964	LP number 58520_414
Table of values for luminous intensities		Maximum luminous intensity



C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	427.7	427.7	427.7	427.7	427.7	427.7	427.7	2.6	2.6
5°	424.4	422.4	420.2	422.1	424.3	424.4	424.8	20.2	22.8
10°	414.9	412.5	408.9	409.5	411.2	411.6	412.2	39.1	61.9
15°	410.8	406.7	398.1	393.2	390.9	389.7	390.1	56.3	118.2
20°	424.3	415.5	394.5	375.8	364.0	357.7	356.8	71.8	190.0
25°	451.7	439.9	403.9	360.3	329.2	311.6	307.2	85.9	275.8
30°	429.5	430.9	412.5	347.4	284.5	251.0	241.5	94.2	370.0
35°	325.6	344.5	379.3	329.0	231.5	183.8	171.0	89.9	460.0
40°	224.9	238.5	293.1	289.7	177.2	125.7	113.8	76.0	535.9
45°	176.4	174.8	199.5	224.7	128.0	84.3	75.7	60.6	596.5
50°	156.0	144.3	136.6	154.2	90.2	58.9	53.2	48.2	644.7
55°	139.0	122.9	98.4	99.7	63.9	43.4	39.8	38.7	683.4
60°	113.7	99.1	72.2	64.7	46.3	33.0	30.8	30.7	714.1
65°	79.7	70.2	51.6	43.8	34.5	25.6	24.0	23.0	737.1
70°	47.7	43.4	35.6	31.1	26.2	19.7	18.2	16.2	753.3
75°	33.9	31.2	26.1	23.2	19.9	14.4	12.7	12.2	765.5
80°	33.7	30.7	23.7	18.2	15.1	9.9	7.5	10.6	776.1
85°	39.3	35.6	26.3	17.2	11.4	6.2	3.2	10.7	786.9
90°	50.4	45.6	32.3	18.9	10.0	3.9	0.6	12.4	799.3
95°	71.3	63.5	42.3	22.5	11.4	4.6	1.0	16.4	815.7
100°	97.9	84.6	52.5	26.5	12.9	5.3	1.6	20.8	836.6
105°	120.7	101.7	62.6	30.2	14.2	6.1	2.4	24.4	860.9
110°	134.6	112.6	69.4	33.2	15.3	6.7	2.9	26.3	887.2
115°	137.8	115.5	72.0	34.6	16.0	7.2	3.2	26.1	913.3
120°	129.6	108.9	68.7	33.6	15.7	7.4	3.5	23.8	937.1
125°	109.1	92.2	59.5	30.3	14.7	7.4	3.7	19.5	956.6
130°	83.4	71.0	47.4	25.5	13.2	7.2	3.7	14.5	971.2
135°	58.6	50.3	35.1	20.5	11.4	6.8	3.7	10.0	981.2
140°	39.2	34.3	25.3	16.3	9.8	6.3	3.7	6.7	987.9
145°	26.6	23.8	18.6	13.0	8.2	5.4	3.7	4.4	992.3
150°	18.7	17.2	14.2	10.0	6.9	5.0	3.7	2.9	995.2
155°	13.8	12.8	10.8	7.8	6.8	4.4	3.6	2.0	997.2
160°	10.2	9.8	7.9	6.8	5.6	4.6	3.5	1.3	998.5
165°	8.2	7.8	6.5	5.6	5.0	4.1	3.7	0.8	999.3
170°	6.4	5.6	4.7	4.7	5.0	4.1	3.9	0.5	999.8
175°	4.2	3.7	4.1	4.1	4.1	4.2	4.2	0.2	1000.0
180°	3.7	3.7	3.7	3.7	3.7	3.7	3.7	0.0	1000.0

Photometric test report

Family Licross® 11 Performance	Order number: 51TM16CN49XG EAN: 4058352929964	LP number 58520_414
--	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	18.8	20.0	19.4	20.6	21.2	15.0	16.2	15.5	16.8	17.4
	3H	19.4	20.5	20.0	21.1	21.8	15.4	16.5	16.0	17.1	17.8
	4H	19.5	20.5	20.2	21.2	21.9	15.6	16.6	16.2	17.2	17.9
	6H	19.8	20.7	20.5	21.4	22.1	15.7	16.7	16.4	17.3	18.0
	8H	20.1	20.8	20.7	21.5	22.3	15.7	16.6	16.4	17.3	18.0
	12H	20.4	21.1	21.1	21.8	22.6	15.7	16.6	16.4	17.2	18.0
4H	2H	18.8	19.8	19.4	20.4	21.1	15.4	16.4	16.1	17.1	17.8
	3H	19.5	20.3	20.1	21.0	21.7	16.0	16.9	16.7	17.5	18.3
	4H	19.7	20.5	20.4	21.2	22.0	16.3	17.1	17.0	17.7	18.5
	6H	20.1	20.8	20.9	21.5	22.3	16.5	17.2	17.2	17.9	18.7
	8H	20.5	21.1	21.2	21.8	22.7	16.6	17.2	17.3	17.9	18.8
	12H	21.0	21.5	21.8	22.3	23.1	16.6	17.2	17.3	17.9	18.7
8H	4H	19.7	20.3	20.4	21.0	21.8	16.5	17.0	17.2	17.8	18.6
	6H	20.2	20.7	21.0	21.5	22.4	16.8	17.3	17.6	18.1	19.0
	8H	20.7	21.2	21.5	21.9	22.8	17.0	17.5	17.8	18.2	19.1
	12H	21.5	21.9	22.3	22.6	23.6	17.1	17.5	17.9	18.3	19.2
12H	4H	19.6	20.2	20.4	20.9	21.8	16.5	17.0	17.2	17.7	18.6
	6H	20.2	20.7	21.0	21.4	22.3	17.0	17.4	17.7	18.1	19.0
	8H	20.8	21.1	21.5	21.9	22.8	17.2	17.5	18.0	18.3	19.2


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1480	H(C0) = 36	H(C180) = 36
			B = 115	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
	45°	10259.8	10248.7	11985.5	14048.8	8454.6	5955.7	5777.3	
	50°	9543.9	8907.9	8669.6	10250.0	6387.6	4514.5	4466.4	
	55°	9042.3	8082.2	6678.9	7133.0	4916.0	3661.6	3744.5	
	60°	7960.9	7025.5	5303.5	5051.1	3937.5	3129.8	3325.8	
	65°	6096.2	5437.0	4166.4	3794.8	3304.6	2789.5	3070.7	
	70°	4046.9	3741.7	3221.2	3057.4	2887.2	2542.1	2878.5	
	75°	3266.2	3055.6	2707.6	2650.6	2624.4	2312.1	2651.8	
	80°	3779.2	3519.4	2904.1	2506.1	2491.5	2113.2	2334.3	
	85°	5314.3	4956.0	3973.6	3019.3	2526.0	1997.8	1987.4	

Photometric test report

Family Licross® 11 Performance	Order number: 51TM16CN49XG EAN: 4058352929964	LP number 58520_414
--	--	--------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Licross® 11 Performance	Order number: 51TM16CN49XG EAN: 4058352929964	LP number 58520_414
--	--	--------------------------------------

Multilumen Table	environmental temperature: 25°C	sITeco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption	Power consumption
	1	2	3			end of lifetime [W]	average [W]
1	A	C	E	9190	49.4	52.1	50.8
2	A	C	F	8660	46.2	48.9	47.6
3	A	D	E	8120	43.1	45.4	44.2
4	A	D	F	7670	40.5	42.7	41.6
5	B	C	E	7120	37.4	39.6	38.5
6	B	C	F	6650	34.8	36.5	35.6
7	B	D	E	6100	31.8	33.5	32.6
8	B	D	F	5620	29.2	30.9	30.0