

Photometric test report

Family
Rondel 21

Order number: 51WB14MC82B
EAN: 4069025719614

LP number
60045_5

serial
documentation
27.04.2026

siteco



Version surface-mounted luminaire, cover opal,
polycarbonate, diffuse beam, adjustable color
temperature: 3000 K | 4000 K

Lamps LED 3000 K | CRI ≥ 80

Controlgear ECG Multilumen


Setting individual position: colour temperature 3000K

Rated values Net luminous flux = 1800 lm
Power consumption = 15.0 W
Luminous efficacy = 120 lm/W

Luminous intensity in cd/klm

C180-0

Imax: 265 cd/klm



Classifications

DIN 5040 A 3 1
CIE N1=42 N2=73 N3=92
N4=91 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 90.9%
 ϕ_o 9.1%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Rondel 21	Order number: 51WB14MC82B EAN: 4069025719614	LP number 60045_5
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	265.2	1.6	1.6
5°	264.7	12.6	14.2
10°	262.8	25.0	39.2
15°	259.4	36.8	76.1
20°	254.5	47.7	123.8
25°	248.0	57.4	181.2
30°	239.5	65.6	246.8
35°	229.0	72.0	318.8
40°	216.4	76.3	395.1
45°	201.7	78.2	473.3
50°	185.0	77.7	550.9
55°	166.1	74.6	625.5
60°	145.7	69.2	694.7
65°	123.9	61.6	756.3
70°	101.4	52.2	808.5
75°	78.8	41.7	850.2
80°	57.1	30.8	881.1
85°	38.5	21.0	902.1
90°	25.7	14.1	916.2
95°	18.7	10.2	926.4
100°	17.5	9.5	935.9
105°	17.1	9.0	944.9
110°	16.4	8.5	953.4
115°	15.7	7.8	961.2
120°	15.0	7.1	968.3
125°	14.2	6.4	974.7
130°	13.2	5.6	980.2
135°	12.4	4.8	985.0
140°	11.3	4.0	989.0
145°	10.2	3.2	992.2
150°	9.3	2.5	994.7
155°	8.3	1.9	996.7
160°	7.4	1.4	998.1
165°	6.7	0.9	999.0
170°	6.6	0.6	999.6
175°	6.8	0.3	1000.0
180°	7.0	0.0	1000.0

Photometric test report

Family Rondel 21			Order number: 51WB14MC82B EAN: 4069025719614							LP number 60045_5	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	18.8	20.6	19.2	20.9	21.2	18.8	20.6	19.2	20.9	21.2
	3H	20.7	22.3	21.1	22.6	23.0	20.7	22.3	21.1	22.6	23.0
	4H	21.5	23.1	21.9	23.4	23.8	21.5	23.1	21.9	23.4	23.8
	6H	22.3	23.7	22.7	24.1	24.4	22.3	23.7	22.7	24.1	24.4
	8H	22.6	24.0	23.0	24.3	24.7	22.6	24.0	23.0	24.3	24.7
	12H	22.9	24.2	23.4	24.6	25.0	22.9	24.2	23.4	24.6	25.0
4H	2H	19.7	21.2	20.1	21.5	21.9	19.7	21.2	20.1	21.5	21.9
	3H	21.7	23.1	22.2	23.4	23.8	21.7	23.1	22.2	23.4	23.8
	4H	22.7	23.9	23.2	24.3	24.7	22.7	23.9	23.2	24.3	24.7
	6H	23.6	24.6	24.0	25.1	25.5	23.6	24.6	24.0	25.1	25.5
	8H	24.0	25.0	24.5	25.4	25.9	24.0	25.0	24.5	25.4	25.9
	12H	24.4	25.3	24.9	25.7	26.2	24.4	25.3	24.9	25.7	26.2
8H	4H	23.2	24.1	23.6	24.6	25.0	23.2	24.1	23.6	24.6	25.0
	6H	24.2	25.0	24.7	25.5	26.0	24.2	25.0	24.7	25.5	26.0
	8H	24.7	25.5	25.2	25.9	26.4	24.7	25.5	25.2	25.9	26.4
	12H	25.2	25.9	25.7	26.4	26.9	25.2	25.9	25.7	26.4	26.9
12H	4H	23.3	24.1	23.7	24.6	25.1	23.3	24.1	23.7	24.6	25.1
	6H	24.4	25.1	24.9	25.6	26.1	24.4	25.1	24.9	25.6	26.1
	8H	24.9	25.6	25.4	26.1	26.6	24.9	25.6	25.4	26.1	26.6

Luminance table		Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	D = 306	H(C0) = 15 H(C90) = 15	H(C180) = 15 H(C270) = 15
C-planes		0°				
γ	Luminance in cd/m²					
45°	6571.3					
50°	6556.2					
55°	6509.2					
60°	6438.1					
65°	6331.1					
70°	6191.3					
75°	6043.3					
80°	5947.6					
85°	6315.2					

Photometric test report

Family
Rondel 21

Order number: 51WB14MC82B
EAN: 4069025719614

LP number
60045_5

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

