


# Photometric test report

<b>Family</b> <b>Silica® 21</b>	<b>Order number: 51MX22TAT4W</b> <b>EAN: 4058352626337</b>	<b>LP number</b> <b>59272_66</b>
	<b>Version</b> surface-mounted luminaire, reflector, black, direct distribution, wide distribution, UGR≤19 (L65≤1000cd/m²), tunable white	<b>serial documentation</b> <b>03.05.2023</b>
	<b>Lamps</b> LED 4000 K   CRI ≥ 80 <b>Controlgear</b> ECG-DALI <b>Setting</b> factory setting <b>Rated values</b> Net luminous flux = 3720 lm Power consumption = 33.8 W Luminous efficacy = 110.1 lm/W	

**Luminous intensity in cd/klm** C180-0 C270-90 **Imax: 700 cd/klm**



Classifications	
DIN 5040	A 6 0
CIE	N1=84 N2=99 N3=100 N4=100 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	100.0%
$\phi_o$	0.0%

**Measurement conditions**  
 DIN EN 13032 and DIN 5032

## Photometric test report

Family <b>Silica® 21</b>	Order number: <b>51MX22TAT4W</b> EAN: <b>4058352626337</b>	LP number <b>59272_66</b>
Table of values for luminous intensities		Maximum luminous intensity
		<b>siteco</b>

C-planes $\gamma$	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	698.3	698.3	698.3	698.3	698.3	698.3	698.3	4.2	4.2
5°	699.6	698.5	693.9	696.9	698.4	696.4	699.4	33.3	37.5
10°	694.6	694.5	689.5	695.3	694.0	687.7	690.0	65.9	103.4
15°	672.6	676.2	675.2	682.1	683.0	677.2	674.7	96.2	199.5
20°	643.1	649.9	651.2	653.1	656.2	653.1	648.8	122.2	321.7
25°	605.9	614.8	613.8	608.6	601.9	597.0	589.1	140.3	462.0
30°	546.6	557.0	551.8	537.6	523.2	517.8	519.3	147.1	609.1
35°	452.6	459.5	452.6	444.2	440.2	442.2	446.7	140.9	750.0
40°	321.1	327.1	329.4	337.0	343.8	344.5	346.6	118.4	868.3
45°	172.2	187.2	203.3	211.2	210.4	196.6	193.1	77.0	945.3
50°	63.8	73.4	88.4	94.7	94.6	78.0	74.0	34.9	980.1
55°	17.5	22.2	30.2	37.1	33.0	23.7	21.3	12.4	992.5
60°	5.9	7.1	10.7	14.2	11.5	8.5	8.2	4.7	997.2
65°	2.1	2.5	3.7	4.8	4.2	3.3	3.2	1.8	998.9
70°	1.4	1.5	1.1	1.1	1.3	1.7	1.7	0.7	999.6
75°	0.3	0.4	0.3	0.5	0.4	0.5	0.5	0.2	999.9
80°	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.1	999.9
85°	0.0	0.0	0.1	0.1	0.1	0.2	0.2	0.1	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

Family <b>Silica® 21</b>	Order number: <b>51MX22TAT4W</b> EAN: <b>4058352626337</b>	LP number <b>59272_66</b>
-----------------------------	---	------------------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	18.6	19.9	19.0	20.2	20.6	18.7	20.0	19.1	20.4	20.7
	3H	18.5	19.6	18.9	20.0	20.3	18.6	19.8	19.0	20.1	20.4
	4H	18.4	19.5	18.8	19.8	20.2	18.5	19.6	18.9	19.9	20.3
	6H	18.4	19.3	18.8	19.7	20.1	18.5	19.4	18.9	19.8	20.2
	8H	18.4	19.2	18.8	19.6	20.0	18.5	19.3	18.9	19.7	20.1
	12H	18.4	19.1	18.8	19.5	19.9	18.5	19.2	18.9	19.6	20.1
4H	2H	18.5	19.5	18.9	19.9	20.2	18.6	19.6	19.0	20.0	20.3
	3H	18.3	19.2	18.7	19.6	20.0	18.4	19.3	18.8	19.7	20.1
	4H	18.2	19.0	18.7	19.4	19.8	18.3	19.1	18.8	19.5	19.9
	6H	18.1	18.8	18.6	19.2	19.7	18.3	18.9	18.7	19.3	19.8
	8H	18.1	18.7	18.6	19.1	19.6	18.2	18.8	18.7	19.2	19.7
	12H	18.1	18.6	18.6	19.0	19.5	18.2	18.7	18.7	19.1	19.6
8H	4H	18.1	18.7	18.6	19.1	19.6	18.2	18.8	18.7	19.2	19.7
	6H	18.0	18.5	18.5	18.9	19.5	18.1	18.6	18.6	19.1	19.6
	8H	17.9	18.4	18.4	18.8	19.4	18.0	18.5	18.6	19.0	19.5
	12H	17.9	18.2	18.4	18.7	19.3	18.0	18.4	18.6	18.9	19.4
12H	4H	18.1	18.6	18.6	19.0	19.5	18.2	18.7	18.7	19.1	19.6
	6H	18.0	18.4	18.5	18.8	19.4	18.1	18.5	18.6	19.0	19.5
	8H	17.9	18.2	18.4	18.7	19.3	18.0	18.4	18.6	18.9	19.4

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1176 B = 49
-----------------	---------------------------------	-------------------------------	--------------------

C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		15725.2	17086.3	18560.6	19278.1	19212.9	17951.7	17629.9	
50°		6408.6	7376.3	8881.8	9511.4	9497.6	7836.5	7432.3	
55°		1966.5	2494.6	3397.9	4177.4	3714.3	2661.8	2393.3	
60°		763.8	919.4	1380.1	1837.0	1479.1	1094.1	1054.1	
65°		326.0	385.7	558.8	735.7	645.4	500.6	489.0	
70°		257.1	274.3	208.6	204.0	247.3	319.2	327.3	
75°		76.1	101.0	84.3	117.7	109.2	128.2	116.5	
80°		21.2	24.9	35.3	46.1	60.2	71.0	74.4	
85°		28.1	31.9	52.6	74.1	102.2	130.4	141.5	

**Photometric test report**

<b>Family</b> <b>Silica® 21</b>	<b>Order number: 51MX22TAT4W</b> <b>EAN: 4058352626337</b>	<b>LP number</b> <b>59272_66</b>
------------------------------------	---	-------------------------------------

**Luminance values in cd/m<sup>2</sup>**    γ 65°    γ 70°    γ 75°    γ 80°    γ 85°    **siteco**

