

Photometric test report

Family
Licross® 11 Performance

Order number: 51TD16DN4AXG3S
EAN: 4069025479495

LP number
58520_343



Version cover frosted, direct-/ indirect distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting emergency light operation: 3 h
Rated values Net luminous flux = 1000 lm
 Power consumption = 6.8 W
 Luminous efficacy = 147.1 lm/W

serial
documentation
29.09.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 452 cd/klm



Classifications

DIN 5040 B 5 1
 CIE N1=65 N2=88 N3=96
 N4=79 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 79.3%
 ϕ_o 20.7%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Performance	Order number: 51TD16DN4AXG3S EAN: 4069025479495	LP number 58520_343
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	427.7	427.7	427.7	427.7	427.7	427.7	427.7	2.6	2.6
5°	424.4	422.4	420.2	422.1	424.3	424.4	424.8	20.2	22.8
10°	414.9	412.5	408.9	409.5	411.2	411.6	412.2	39.1	61.9
15°	410.8	406.7	398.1	393.2	390.9	389.7	390.1	56.3	118.2
20°	424.3	415.5	394.5	375.8	364.0	357.7	356.8	71.8	190.0
25°	451.7	439.9	403.9	360.3	329.2	311.6	307.2	85.9	275.8
30°	429.5	430.9	412.5	347.4	284.5	251.0	241.5	94.2	370.0
35°	325.6	344.5	379.3	329.0	231.5	183.8	171.0	89.9	460.0
40°	224.9	238.5	293.1	289.7	177.2	125.7	113.8	76.0	535.9
45°	176.4	174.8	199.5	224.7	128.0	84.3	75.7	60.6	596.5
50°	156.0	144.3	136.6	154.2	90.2	58.9	53.2	48.2	644.7
55°	139.0	122.9	98.4	99.7	63.9	43.4	39.8	38.7	683.4
60°	113.7	99.1	72.2	64.7	46.3	33.0	30.8	30.7	714.1
65°	79.7	70.2	51.6	43.8	34.5	25.6	24.0	23.0	737.1
70°	47.7	43.4	35.6	31.1	26.2	19.7	18.2	16.2	753.3
75°	33.9	31.2	26.1	23.2	19.9	14.4	12.7	12.2	765.5
80°	33.7	30.7	23.7	18.2	15.1	9.9	7.5	10.6	776.1
85°	39.3	35.6	26.3	17.2	11.4	6.2	3.2	10.7	786.9
90°	50.4	45.6	32.3	18.9	10.0	3.9	0.6	12.4	799.3
95°	71.3	63.5	42.3	22.5	11.4	4.6	1.0	16.4	815.7
100°	97.9	84.6	52.5	26.5	12.9	5.3	1.6	20.8	836.6
105°	120.7	101.7	62.6	30.2	14.2	6.1	2.4	24.4	860.9
110°	134.6	112.6	69.4	33.2	15.3	6.7	2.9	26.3	887.2
115°	137.8	115.5	72.0	34.6	16.0	7.2	3.2	26.1	913.3
120°	129.6	108.9	68.7	33.6	15.7	7.4	3.5	23.8	937.1
125°	109.1	92.2	59.5	30.3	14.7	7.4	3.7	19.5	956.6
130°	83.4	71.0	47.4	25.5	13.2	7.2	3.7	14.5	971.2
135°	58.6	50.3	35.1	20.5	11.4	6.8	3.7	10.0	981.2
140°	39.2	34.3	25.3	16.3	9.8	6.3	3.7	6.7	987.9
145°	26.6	23.8	18.6	13.0	8.2	5.4	3.7	4.4	992.3
150°	18.7	17.2	14.2	10.0	6.9	5.0	3.7	2.9	995.2
155°	13.8	12.8	10.8	7.8	6.8	4.4	3.6	2.0	997.2
160°	10.2	9.8	7.9	6.8	5.6	4.6	3.5	1.3	998.5
165°	8.2	7.8	6.5	5.6	5.0	4.1	3.7	0.8	999.3
170°	6.4	5.6	4.7	4.7	5.0	4.1	3.9	0.5	999.8
175°	4.2	3.7	4.1	4.1	4.1	4.2	4.2	0.2	1000.0
180°	3.7	3.7	3.7	3.7	3.7	3.7	3.7	0.0	1000.0

Photometric test report

Family Licross® 11 Performance	Order number: 51TD16DN4AXG3S EAN: 4069025479495	LP number 58520_343
UGR-Table	Standard room	siteco

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	11.1	12.3	11.6	12.9	13.5	7.3	8.5	7.8	9.1	9.7
	3H	11.7	12.8	12.3	13.4	14.1	7.7	8.8	8.3	9.4	10.1
	4H	11.8	12.8	12.5	13.5	14.2	7.9	8.9	8.5	9.5	10.2
	6H	12.1	13.0	12.8	13.7	14.4	8.0	9.0	8.6	9.6	10.3
	8H	12.3	13.1	13.0	13.8	14.6	8.0	8.9	8.7	9.6	10.3
	12H	12.7	13.4	13.4	14.1	14.9	8.0	8.9	8.7	9.5	10.3
4H	2H	11.1	12.1	11.7	12.7	13.4	7.7	8.7	8.4	9.4	10.1
	3H	11.8	12.6	12.4	13.3	14.0	8.3	9.2	9.0	9.8	10.6
	4H	12.0	12.8	12.7	13.5	14.2	8.6	9.4	9.3	10.0	10.8
	6H	12.4	13.1	13.1	13.8	14.6	8.8	9.5	9.5	10.2	11.0
	8H	12.8	13.4	13.5	14.1	15.0	8.9	9.5	9.6	10.2	11.1
	12H	13.3	13.8	14.1	14.6	15.4	8.9	9.5	9.6	10.2	11.0
8H	4H	12.0	12.6	12.7	13.3	14.1	8.8	9.3	9.5	10.1	10.9
	6H	12.5	13.0	13.3	13.8	14.7	9.1	9.6	9.9	10.4	11.3
	8H	13.0	13.5	13.8	14.2	15.1	9.3	9.8	10.1	10.5	11.4
	12H	13.8	14.2	14.6	14.9	15.9	9.4	9.8	10.2	10.6	11.5
12H	4H	11.9	12.5	12.7	13.2	14.1	8.8	9.3	9.5	10.0	10.9
	6H	12.5	12.9	13.3	13.7	14.6	9.2	9.7	10.0	10.4	11.3
	8H	13.1	13.4	13.8	14.2	15.1	9.5	9.8	10.3	10.6	11.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:	L = 1480 B = 115	H(C0) = 36 H(C90) = 0	H(C180) = 36 H(C270) = 0
C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	1116.4	1115.2	1304.2	1528.7	920.0	648.1	628.7
50°	1038.5	969.3	943.4	1115.3	695.1	491.2	486.0
55°	983.9	879.5	726.8	776.2	534.9	398.4	407.5
60°	866.3	764.5	577.1	549.6	428.5	340.6	361.9
65°	663.4	591.6	453.4	412.9	359.6	303.5	334.1
70°	440.4	407.1	350.5	332.7	314.2	276.6	313.2
75°	355.4	332.5	294.6	288.4	285.6	251.6	288.6
80°	411.2	383.0	316.0	272.7	271.1	230.0	254.0
85°	578.3	539.3	432.4	328.5	274.9	217.4	216.3

Photometric test report

Family
Licross® 11 Performance

Order number: 51TD16DN4AXG3S
EAN: 4069025479495

LP number
58520_343

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

