

Photometric test report

Family
Licross® 11 Performance

Order number: 51TD16CN49XG
EAN: 4058352928844

LP number
58520_365



Version cover frosted, direct-/ indirect distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-Multilumen CLOi
Rated values Net luminous flux = 9190 lm
 Power consumption = 49.4 W
 Luminous efficacy = 186 lm/W

serial
documentation
12.10.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 452 cd/klm



Classifications

DIN 5040 B 5 1
 CIE N1=65 N2=88 N3=96
 N4=79 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 79.3%
 ϕ_o 20.7%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Performance	Order number: 51TD16CN49XG EAN: 4058352928844	LP number 58520_365
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	427.7	427.7	427.7	427.7	427.7	427.7	427.7	2.6	2.6
5°	424.4	422.4	420.2	422.1	424.3	424.4	424.8	20.2	22.8
10°	414.9	412.5	408.9	409.5	411.2	411.6	412.2	39.1	61.9
15°	410.8	406.7	398.1	393.2	390.9	389.7	390.1	56.3	118.2
20°	424.3	415.5	394.5	375.8	364.0	357.7	356.8	71.8	190.0
25°	451.7	439.9	403.9	360.3	329.2	311.6	307.2	85.9	275.8
30°	429.5	430.9	412.5	347.4	284.5	251.0	241.5	94.2	370.0
35°	325.6	344.5	379.3	329.0	231.5	183.8	171.0	89.9	460.0
40°	224.9	238.5	293.1	289.7	177.2	125.7	113.8	76.0	535.9
45°	176.4	174.8	199.5	224.7	128.0	84.3	75.7	60.6	596.5
50°	156.0	144.3	136.6	154.2	90.2	58.9	53.2	48.2	644.7
55°	139.0	122.9	98.4	99.7	63.9	43.4	39.8	38.7	683.4
60°	113.7	99.1	72.2	64.7	46.3	33.0	30.8	30.7	714.1
65°	79.7	70.2	51.6	43.8	34.5	25.6	24.0	23.0	737.1
70°	47.7	43.4	35.6	31.1	26.2	19.7	18.2	16.2	753.3
75°	33.9	31.2	26.1	23.2	19.9	14.4	12.7	12.2	765.5
80°	33.7	30.7	23.7	18.2	15.1	9.9	7.5	10.6	776.1
85°	39.3	35.6	26.3	17.2	11.4	6.2	3.2	10.7	786.9
90°	50.4	45.6	32.3	18.9	10.0	3.9	0.6	12.4	799.3
95°	71.3	63.5	42.3	22.5	11.4	4.6	1.0	16.4	815.7
100°	97.9	84.6	52.5	26.5	12.9	5.3	1.6	20.8	836.6
105°	120.7	101.7	62.6	30.2	14.2	6.1	2.4	24.4	860.9
110°	134.6	112.6	69.4	33.2	15.3	6.7	2.9	26.3	887.2
115°	137.8	115.5	72.0	34.6	16.0	7.2	3.2	26.1	913.3
120°	129.6	108.9	68.7	33.6	15.7	7.4	3.5	23.8	937.1
125°	109.1	92.2	59.5	30.3	14.7	7.4	3.7	19.5	956.6
130°	83.4	71.0	47.4	25.5	13.2	7.2	3.7	14.5	971.2
135°	58.6	50.3	35.1	20.5	11.4	6.8	3.7	10.0	981.2
140°	39.2	34.3	25.3	16.3	9.8	6.3	3.7	6.7	987.9
145°	26.6	23.8	18.6	13.0	8.2	5.4	3.7	4.4	992.3
150°	18.7	17.2	14.2	10.0	6.9	5.0	3.7	2.9	995.2
155°	13.8	12.8	10.8	7.8	6.8	4.4	3.6	2.0	997.2
160°	10.2	9.8	7.9	6.8	5.6	4.6	3.5	1.3	998.5
165°	8.2	7.8	6.5	5.6	5.0	4.1	3.7	0.8	999.3
170°	6.4	5.6	4.7	4.7	5.0	4.1	3.9	0.5	999.8
175°	4.2	3.7	4.1	4.1	4.1	4.2	4.2	0.2	1000.0
180°	3.7	3.7	3.7	3.7	3.7	3.7	3.7	0.0	1000.0

Photometric test report

Family Licross® 11 Performance	Order number: 51TD16CN49XG EAN: 4058352928844	LP number 58520_365
-----------------------------------	--	------------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	18.8	20.0	19.4	20.6	21.2	15.0	16.2	15.5	16.8	17.4
	3H	19.4	20.5	20.0	21.1	21.8	15.4	16.5	16.0	17.1	17.8
	4H	19.5	20.5	20.2	21.2	21.9	15.6	16.6	16.2	17.2	17.9
	6H	19.8	20.7	20.5	21.4	22.1	15.7	16.7	16.4	17.3	18.0
	8H	20.1	20.8	20.7	21.5	22.3	15.7	16.6	16.4	17.3	18.0
	12H	20.4	21.1	21.1	21.8	22.6	15.7	16.6	16.4	17.2	18.0
4H	2H	18.8	19.8	19.4	20.4	21.1	15.4	16.4	16.1	17.1	17.8
	3H	19.5	20.3	20.1	21.0	21.7	16.0	16.9	16.7	17.5	18.3
	4H	19.7	20.5	20.4	21.2	22.0	16.3	17.1	17.0	17.7	18.5
	6H	20.1	20.8	20.9	21.5	22.3	16.5	17.2	17.2	17.9	18.7
	8H	20.5	21.1	21.2	21.8	22.7	16.6	17.2	17.3	17.9	18.8
	12H	21.0	21.5	21.8	22.3	23.1	16.6	17.2	17.3	17.9	18.7
8H	4H	19.7	20.3	20.4	21.0	21.8	16.5	17.0	17.2	17.8	18.6
	6H	20.2	20.7	21.0	21.5	22.4	16.8	17.3	17.6	18.1	19.0
	8H	20.7	21.2	21.5	21.9	22.8	17.0	17.5	17.8	18.2	19.1
	12H	21.5	21.9	22.3	22.6	23.6	17.1	17.5	17.9	18.3	19.2
12H	4H	19.6	20.2	20.4	20.9	21.8	16.5	17.0	17.2	17.7	18.6
	6H	20.2	20.7	21.0	21.4	22.3	17.0	17.4	17.7	18.1	19.0
	8H	20.8	21.1	21.5	21.9	22.8	17.2	17.5	18.0	18.3	19.2

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1480 B = 115		H(C0) = 36 H(C90) = 0		H(C180) = 36 H(C270) = 0	
C-planes	γ	0°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°			
		Luminance in cd/m²									
	45°	10259.8	10248.7	11985.5	14048.8	8454.6	5955.7	5777.3			
	50°	9543.9	8907.9	8669.6	10250.0	6387.6	4514.5	4466.4			
	55°	9042.3	8082.2	6678.9	7133.0	4916.0	3661.6	3744.5			
	60°	7960.9	7025.5	5303.5	5051.1	3937.5	3129.8	3325.8			
	65°	6096.2	5437.0	4166.4	3794.8	3304.6	2789.5	3070.7			
	70°	4046.9	3741.7	3221.2	3057.4	2887.2	2542.1	2878.5			
	75°	3266.2	3055.6	2707.6	2650.6	2624.4	2312.1	2651.8			
	80°	3779.2	3519.4	2904.1	2506.1	2491.5	2113.2	2334.3			
	85°	5314.3	4956.0	3973.6	3019.3	2526.0	1997.8	1987.4			

Photometric test report

Family
Licross® 11 Performance

Order number: 51TD16CN49XG
EAN: 4058352928844

LP number
58520_365

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 11 Performance	Order number: 51TD16CN49XG EAN: 4058352928844	LP number 58520_365
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	9190	49.4	55.3	52.4
2	A	C	F	8660	46.3	51.7	49.0
3	A	D	E	8120	43.1	48.1	45.6
4	A	D	F	7670	40.5	44.5	42.5
5	B	C	E	7120	37.4	41.8	39.6
6	B	C	F	6650	34.7	38.3	36.5
7	B	D	E	6100	31.8	35.2	33.5
8	B	D	F	5620	29.2	32.2	30.7