

Photometric test report

Family
Highbay 11

Order number: 51HN12DB3KDA
EAN: 4069025424754

LP number
59710_495

serial
documentation
26.05.2025

siteco




Version primary light control with lens, PMMA, housing, white, wide distribution
Lamps LED 3000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting AC-mode
Rated values Net luminous flux = 24700 lm
Power consumption = 125.3 W
Luminous efficacy = 197.1 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 772 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=88 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN12DB3KDA EAN: 4069025424754	LP number 59710_495
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11	Order number: 51HN12DB3KDA EAN: 4069025424754	LP number 59710_495
UGR-Table	Standard room	siteco

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.3	20.5	19.6	20.8	21.2	19.0	20.2	19.3	20.5	20.9
	3H	19.2	20.4	19.6	20.7	21.1	19.0	20.1	19.4	20.4	20.8
	4H	19.2	20.3	19.6	20.6	21.0	19.0	20.0	19.4	20.4	20.8
	6H	19.2	20.1	19.6	20.5	20.9	19.0	20.0	19.4	20.3	20.7
	8H	19.3	20.1	19.7	20.5	20.9	19.1	19.9	19.5	20.3	20.7
	12H	19.3	20.0	19.7	20.4	20.8	19.1	19.8	19.5	20.2	20.6
4H	2H	19.1	20.2	19.5	20.5	20.9	18.9	19.9	19.3	20.3	20.6
	3H	19.2	20.0	19.6	20.4	20.8	18.9	19.8	19.4	20.2	20.6
	4H	19.2	19.9	19.6	20.4	20.8	19.0	19.7	19.4	20.1	20.6
	6H	19.2	19.8	19.6	20.2	20.7	19.0	19.7	19.5	20.1	20.6
	8H	19.1	19.7	19.6	20.2	20.6	19.0	19.6	19.5	20.1	20.5
	12H	19.1	19.6	19.6	20.1	20.6	19.1	19.5	19.6	20.0	20.5
8H	4H	19.1	19.7	19.6	20.1	20.6	18.9	19.5	19.4	19.9	20.4
	6H	19.1	19.6	19.6	20.0	20.5	19.0	19.4	19.5	19.9	20.4
	8H	19.0	19.5	19.6	20.0	20.5	19.0	19.4	19.5	19.9	20.4
	12H	19.0	19.4	19.6	19.9	20.4	19.0	19.3	19.5	19.8	20.4
12H	4H	19.1	19.6	19.6	20.1	20.6	18.9	19.4	19.4	19.9	20.4
	6H	19.1	19.5	19.6	20.0	20.5	19.0	19.3	19.5	19.8	20.4
	8H	19.1	19.4	19.6	19.9	20.4	19.0	19.3	19.5	19.8	20.3

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	18220.4	17841.1	18545.5	19020.9	16969.2	15932.4	15885.5
50,0°	10151.7	9911.7	9901.3	10078.1	9043.5	8622.7	8474.8
55,0°	6379.8	6209.2	6297.8	6442.4	5844.1	5493.6	5427.5
60,0°	4588.6	4429.6	4654.3	4794.0	4488.5	4156.6	4209.6
65,0°	3871.9	3522.1	3754.2	3916.0	3834.7	3546.3	3746.6
70,0°	3327.9	3036.4	3358.7	3249.6	3564.9	3245.1	3544.0
75,0°	2742.6	2540.2	2533.4	2709.5	2815.1	3013.3	3359.1
80,0°	1851.6	1727.7	1828.2	1974.9	2229.2	2621.9	2988.7
85,0°	739.6	735.8	759.8	889.5	1315.4	1752.6	2270.5

Photometric test report

Family
Highbay 11

Order number: 51HN12DB3KDA
EAN: 4069025424754

LP number
59710_495

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN12DB3KDA EAN: 4069025424754	LP number 59710_495
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	24700	125.3
95	241	252	23486	118.6
90	228	250	22263	112.1
85	215	248	21039	105.6
80	202	246	19804	99.1
75	189	243	18571	92.6
70	176	241	17331	86.1
65	163	238	16083	79.8
60	150	235	14835	73.4
55	137	231	13570	66.8
50	124	228	12307	60.6
45	112	224	11135	54.6
40	99	219	9854	48.4
35	87	215	8670	42.7
30	74	209	7376	36.5
25	62	202	6179	30.7
20	50	194	4978	25.0
15	37	183	3665	19.0
10	25	169	2452	13.3
5	13	145	1228	7.4
2	6	117	515	4.0