


Photometric test report

Family Highbay 11	Order number: 51HLA2D14FCAD EAN: 4058352341629	LP number 58922_9
	Version wide distribution, UGR≤22 Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Rated values Net luminous flux = 14400 lm Power consumption = 81.2 W Luminous efficacy = 177.3 lm/W	serial documentation 21.05.2019
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 775 cd/klm**



Classifications	
DIN 5040	A 6 0
CIE	N1=89 N2=96 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HLA2D14FCAD EAN: 4058352341629	LP number 58922_9
----------------------	---	----------------------



Table of values for luminous intensities	Maximum luminous intensity
--	----------------------------

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	775.3	775.3	775.3	775.3	775.3	775.3	775.3	4.6	4.6
5°	763.3	765.5	767.8	768.1	766.5	768.2	766.4	36.6	41.3
10°	748.7	752.6	756.7	755.9	749.0	745.7	741.9	71.5	112.7
15°	728.8	736.6	748.6	748.7	732.9	716.3	707.4	104.1	216.8
20°	722.5	731.1	745.9	741.9	711.6	682.4	668.7	134.6	351.4
25°	707.4	710.1	723.4	713.1	669.4	627.0	613.5	158.4	509.9
30°	625.1	622.7	643.6	650.9	594.8	541.3	531.4	165.9	675.7
35°	454.3	465.0	515.3	546.7	478.1	404.7	385.8	148.3	824.0
40°	194.7	222.6	276.1	324.0	261.7	198.8	171.4	86.1	910.1
45°	52.4	51.4	56.0	64.9	54.8	51.5	51.3	21.3	931.5
50°	36.0	31.0	27.7	34.1	33.7	39.2	46.8	14.5	946.0
55°	27.7	25.7	21.5	23.0	24.8	33.2	42.0	12.2	958.2
60°	24.8	27.6	25.1	19.0	18.2	24.5	32.6	11.3	969.5
65°	33.0	23.0	22.5	18.8	16.0	23.0	31.5	11.2	980.7
70°	25.9	19.0	18.9	17.8	15.3	19.4	28.1	10.1	990.8
75°	12.6	8.9	10.2	12.8	12.0	13.0	13.0	6.1	996.9
80°	3.5	3.2	4.0	5.1	6.3	6.1	5.9	2.6	999.6
85°	0.3	0.3	0.4	0.5	1.1	1.3	1.4	0.4	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11	Order number: 51HLA2D14FCAD EAN: 4058352341629	LP number 58922_9
----------------------	---	----------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	20.4	21.7	20.7	22.0	22.3	19.9	21.2	20.2	21.5	21.8
	3H	20.8	21.9	21.2	22.3	22.6	20.4	21.5	20.8	21.9	22.2
	4H	20.9	22.0	21.3	22.3	22.7	20.6	21.7	21.0	22.0	22.4
	6H	20.9	21.9	21.4	22.2	22.6	20.7	21.6	21.1	22.0	22.4
	8H	21.0	21.8	21.4	22.2	22.6	20.8	21.6	21.2	22.0	22.4
	12H	21.0	21.7	21.4	22.1	22.5	20.8	21.5	21.2	21.9	22.3
4H	2H	20.3	21.4	20.7	21.7	22.1	19.8	20.8	20.2	21.2	21.6
	3H	20.9	21.7	21.3	22.1	22.5	20.4	21.3	20.9	21.7	22.1
	4H	21.0	21.8	21.5	22.2	22.6	20.7	21.5	21.2	21.9	22.4
	6H	21.0	21.7	21.5	22.1	22.6	20.9	21.5	21.4	22.0	22.4
	8H	21.0	21.6	21.5	22.0	22.5	20.9	21.5	21.4	21.9	22.4
	12H	21.0	21.5	21.5	21.9	22.4	20.9	21.4	21.4	21.9	22.4
8H	4H	21.0	21.6	21.5	22.1	22.6	20.8	21.4	21.3	21.8	22.3
	6H	21.0	21.5	21.5	22.0	22.5	21.0	21.5	21.5	21.9	22.4
	8H	21.0	21.4	21.5	21.9	22.5	21.0	21.4	21.5	21.9	22.4
	12H	21.0	21.3	21.5	21.8	22.4	21.0	21.3	21.5	21.8	22.4
12H	4H	21.1	21.5	21.5	22.0	22.5	20.8	21.3	21.3	21.7	22.2
	6H	21.1	21.4	21.6	21.9	22.5	21.0	21.4	21.5	21.9	22.4
	8H	21.0	21.4	21.5	21.9	22.4	21.0	21.3	21.5	21.8	22.4

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 300 B = 320
-----------------	---------------------------------	-------------------------------	--------------------

C-planes	γ	Luminance in cd/m ²						
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
45°		11110.2	10907.8	11880.5	13759.5	11629.9	10932.0	10874.7
50°		8401.1	7241.6	6475.2	7965.0	7871.0	9143.0	10910.0
55°		7239.3	6717.6	5619.2	6027.7	6475.7	8675.8	10983.5
60°		7439.1	8294.1	7528.2	5711.1	5454.9	7355.4	9772.5
65°		11718.7	8148.5	7993.7	6684.0	5664.3	8151.0	11191.0
70°		11375.2	8319.2	8298.6	7817.5	6719.8	8525.8	12320.3
75°		7290.8	5129.1	5896.4	7421.8	6952.3	7523.2	7540.0
80°		3023.4	2799.6	3479.4	4400.3	5457.6	5233.9	5089.6
85°		530.1	521.5	611.0	889.8	1903.5	2208.1	2421.5


Photometric test report

Family Highbay 11	Order number: 51HLA2D14FCAD EAN: 4058352341629	LP number 58922_9
-----------------------------	---	-----------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HLA2D14FCAD EAN: 4058352341629	LP number 58922_9
----------------------	---	----------------------

Dimming levels table	environmental temperature: 25°C	sITeco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	14400	81.2
95	241	252	13680	76.8
90	227	250	12960	72.5
85	214	248	12240	68.4
80	201	245	11520	64.2
75	188	243	10800	60.0
70	175	240	10080	56.0
65	162	237	9360	51.9
60	149	234	8640	48.0
55	136	231	7920	44.1
50	124	228	7200	40.2
45	111	224	6480	36.3
40	99	219	5760	32.5
35	86	215	5040	28.8
30	74	209	4320	25.1
25	62	203	3600	21.3
20	50	195	2880	17.6
15	38	185	2160	14.0
10	26	170	1439	10.4