

Photometric test report

Family
Ecopack® 31

Order number: 51LJ12MDM20A
EAN: 4058352589533

LP number
59347_2



Version diffuser optic, frosted, polycarbonate,
adjustable color temperature: 3000K | 4000K |
5000K, extremely wide distribution

Lamps LED 3000 K | CRI ≥ 80

Controlgear ECG Multilumen

Setting individual position: colour temperature 3000K

Rated values Net luminous flux = 2340 lm
Power consumption = 20.0 W
Luminous efficacy = 117 lm/W

serial
documentation
19.08.2022


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 285 cd/klm



Classifications

DIN 5040 A 3 1
CIE N1=42 N2=71 N3=90
N4=93 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 92.9%
 ϕ_o 7.1%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Ecopack® 31	Order number: 51LJ12MDM20A EAN: 4058352589533	LP number 59347_2
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	285.0	285.0	285.0	285.0	285.0	285.0	285.0	1.7	1.7
5°	285.1	284.3	283.5	283.8	284.2	283.4	282.6	13.6	15.3
10°	282.3	281.1	279.8	280.1	280.4	279.5	278.5	26.7	41.9
15°	278.0	276.1	274.2	273.9	273.6	272.5	271.5	38.9	80.8
20°	271.6	268.6	265.6	264.9	264.2	262.9	261.6	49.8	130.6
25°	263.5	259.4	255.3	254.0	252.7	251.0	249.3	59.0	189.6
30°	254.5	248.8	243.2	241.2	239.1	237.2	235.2	66.4	256.1
35°	243.0	236.0	229.1	225.9	222.7	220.7	218.6	71.5	327.6
40°	231.0	222.5	214.1	209.5	205.0	203.0	201.1	74.6	402.2
45°	217.4	207.7	198.0	192.2	186.5	184.4	182.2	75.5	477.7
50°	202.9	191.6	180.3	173.3	166.4	166.2	165.9	74.3	552.0
55°	187.1	177.1	167.1	157.6	148.2	146.7	145.3	72.1	624.1
60°	171.9	160.5	149.2	139.1	129.1	126.5	124.0	67.4	691.5
65°	156.3	143.4	130.6	119.0	107.5	104.6	101.7	60.8	752.3
70°	145.6	129.4	113.3	99.2	85.1	82.8	80.5	53.5	805.8
75°	131.0	114.1	97.1	80.6	64.2	62.3	60.4	45.4	851.1
80°	117.2	99.5	81.9	63.3	44.7	43.0	41.2	37.0	888.1
85°	103.3	85.9	68.5	48.0	27.6	26.9	26.3	29.3	917.4
90°	88.2	72.6	57.0	36.5	15.9	15.9	15.8	22.8	940.2
95°	67.3	56.7	46.0	27.9	9.8	9.8	9.7	17.2	957.4
100°	54.0	42.2	30.4	18.3	6.1	6.1	6.0	12.0	969.4
105°	49.2	36.5	23.9	14.2	4.6	4.8	4.9	9.8	979.2
110°	42.8	31.7	20.5	12.3	4.0	4.2	4.3	8.3	987.4
115°	36.6	27.1	17.6	10.7	3.8	3.9	3.9	6.9	994.4
120°	30.8	22.8	14.8	9.2	3.7	3.7	3.7	5.6	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Ecopack® 31	Order number: 51LJ12MDM20A EAN: 4058352589533	LP number 59347_2
------------------------------	--	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	21.3	23.1	21.7	23.4	23.7	21.2	23.0	21.5	23.3	23.6
	3H	23.4	25.0	23.8	25.3	25.7	22.9	24.5	23.3	24.8	25.2
	4H	24.5	26.0	24.9	26.4	26.7	23.6	25.2	24.0	25.5	25.9
	6H	25.6	27.0	26.0	27.3	27.7	24.3	25.7	24.7	26.1	26.5
	8H	26.1	27.4	26.5	27.8	28.2	24.6	26.0	25.0	26.3	26.7
	12H	26.6	27.9	27.1	28.3	28.7	24.9	26.2	25.3	26.6	27.0
4H	2H	22.0	23.5	22.4	23.9	24.2	21.9	23.4	22.3	23.8	24.1
	3H	24.2	25.6	24.7	26.0	26.4	23.7	25.0	24.1	25.4	25.8
	4H	25.4	26.7	25.9	27.1	27.5	24.6	25.8	25.0	26.2	26.6
	6H	26.7	27.7	27.1	28.2	28.6	25.3	26.4	25.8	26.8	27.3
	8H	27.3	28.3	27.8	28.7	29.2	25.6	26.7	26.1	27.1	27.6
	12H	28.0	28.8	28.4	29.3	29.8	26.0	26.9	26.5	27.4	27.9
8H	4H	25.7	26.7	26.2	27.2	27.6	25.0	25.9	25.4	26.4	26.8
	6H	27.1	28.0	27.6	28.4	28.9	25.8	26.6	26.3	27.1	27.6
	8H	27.9	28.6	28.4	29.1	29.6	26.2	26.9	26.7	27.4	27.9
	12H	28.7	29.3	29.2	29.8	30.4	26.6	27.3	27.1	27.8	28.3
12H	4H	25.8	26.7	26.2	27.1	27.6	25.1	26.0	25.6	26.4	26.9
	6H	27.2	28.0	27.7	28.4	29.0	26.0	26.7	26.5	27.2	27.7
	8H	28.0	28.7	28.5	29.2	29.7	26.4	27.0	26.9	27.5	28.1

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 593	H(C0) = 29	H(C180) = 29
			B = 56	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		14273.8	13796.0	13620.0	14023.0	14764.5	16200.7	18156.9	
50°		13756.8	13159.2	12877.8	13229.5	13942.7	15706.7	18186.0	
55°		13210.7	12688.9	12512.3	12715.6	13289.9	15129.2	17846.1	
60°		12774.0	12122.9	11830.4	11996.1	12557.4	14471.7	17473.6	
65°		12346.3	11537.8	11098.0	11116.3	11521.9	13544.1	16954.5	
70°		12380.3	11232.1	10457.0	10187.0	10242.9	12463.1	16575.2	
75°		12162.3	10832.3	9889.0	9277.0	8884.2	11305.5	16451.9	
80°		12078.6	10526.6	9376.6	8345.3	7343.3	9904.0	16737.7	
85°		12066.1	10334.9	9036.9	7488.5	5632.3	8599.4	21244.8	


Photometric test report

Family Ecopack® 31	Order number: 51LJ12MDM20A EAN: 4058352589533	LP number 59347_2
-------------------------------------	--	------------------------------------



Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°



Photometric test report

Family Ecopack® 31	Order number: 51LJ12MDM20A EAN: 4058352589533	LP number 59347_2
------------------------------	--	-----------------------------

Multilumen Table	environmental temperature: 25°C	siteco
-------------------------	---------------------------------	---------------

DIP-Step	Switch Setting		Luminous flux [lm]	Power consumption [W]
	1	2		
3	ON	ON	2340	20.0
2	ON	OFF	2040	17.0
1	OFF	ON	1730	14.0
0	OFF	OFF	1410	11.0