

Photometric test report

Family
DL® 30 LED

Order number: 5XA5132R1B08A5
EAN: 4058352059371

LP number
57205_8



Version post-top mounting
Optic symmetric, wide distribution (PL1.2s)
Cover PMMA cover, impact resistant, IK08
Lamps LED 4000 K | CRI ≥ 70
Controlgear ECG Plus
Rated values Net luminous flux = 6990 lm
Power consumption = 52.0 W
Luminous efficacy = 134.4 lm/W

serial
documentation
18.11.2020

siteco

Luminous intensity in cd/klm


C180-0

C235-55

C240-60

C270-90

Imax: 288 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%

Luminous intensity class acc. to EN13201-2

Class:	G6
Imax 70°	198.5
Imax 80°	25.7
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0


Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family DL® 30 LED	Order number: 5XA5132R1B08A5 EAN: 4058352059371	LP number 57205_8
------------------------------------	--	------------------------------------

Envelope curve in cd/klm **KMK 55°** **KMK 52,5°** **KMK 50°** **KMK 47,5°** **siteco**



Photometric test report

Family DL® 30 LED	Order number: 5XA5132R1B08A5 EAN: 4058352059371	LP number 57205_8
Table of values for luminous intensities		Maximum luminous intensity
		sitEco

C-planes	0° 180°	5°	10°	15°	20°	25°	30°	35°	40°	45°
		175° 185° 355°	170° 190° 350°	165° 195° 345°	160° 200° 340°	155° 205° 335°	150° 210° 330°	145° 215° 325°	140° 220° 320°	135° 225° 315°
Luminous intensity in cd/klm										
γ										
0,0°	194.0	194.0	194.0	194.0	194.0	194.0	194.0	194.0	194.0	194.0
2,5°	193.2	194.0	195.2	195.5	194.4	194.4	194.5	195.8	195.8	194.7
5,0°	196.7	197.4	198.7	198.8	197.6	197.0	197.1	198.3	198.3	197.2
7,5°	204.6	205.0	206.1	205.8	203.9	202.6	201.6	202.1	201.8	200.3
10,0°	213.0	213.7	214.7	213.9	211.2	208.7	206.2	205.7	204.9	203.1
12,5°	214.4	214.8	215.5	214.8	211.7	209.4	206.5	205.9	205.2	203.1
15,0°	207.6	208.0	208.5	207.0	204.1	201.9	199.4	199.7	199.6	198.3
17,5°	206.7	206.4	205.7	202.9	197.3	193.4	190.4	190.5	189.9	187.4
20,0°	202.8	203.1	202.6	200.2	194.5	189.2	184.1	181.3	177.6	174.4
22,5°	200.7	199.8	198.8	197.0	192.9	189.5	184.0	177.0	169.8	165.3
25,0°	197.4	195.6	193.2	193.0	191.2	189.4	184.6	177.9	170.9	166.0
27,5°	196.3	195.5	192.9	191.7	191.7	192.5	186.1	179.5	178.0	175.6
30,0°	206.7	205.5	203.1	199.7	197.6	196.8	191.4	185.6	184.4	187.3
32,5°	210.3	207.5	204.9	206.2	207.6	204.5	198.5	195.4	194.2	194.7
35,0°	219.3	218.0	211.7	209.6	212.6	211.8	210.0	206.7	206.5	203.1
37,5°	233.4	231.9	224.9	220.5	221.4	216.0	217.1	220.5	215.8	218.9
40,0°	239.0	235.6	227.7	224.7	230.4	227.9	225.0	228.3	229.8	232.9
42,5°	246.0	243.2	233.1	228.2	231.6	230.9	238.3	238.4	241.6	245.4
45,0°	251.5	253.0	244.9	236.5	234.7	231.6	239.9	254.4	255.4	254.2
47,5°	254.4	259.3	256.7	249.2	240.2	235.4	250.7	262.3	267.6	259.8
50,0°	253.0	260.1	264.6	253.1	244.0	239.8	261.0	271.2	268.6	264.3
52,5°	251.7	256.4	256.2	248.8	244.5	250.0	267.9	279.0	272.1	266.2
55,0°	248.3	251.0	245.7	245.8	247.4	257.8	273.2	278.6	274.5	266.7
57,5°	235.8	239.9	235.0	235.0	250.3	266.2	272.4	276.2	271.3	263.0
60,0°	203.7	207.7	213.2	218.9	241.5	258.6	261.4	271.1	268.4	257.5
62,5°	160.7	168.0	181.1	192.6	219.8	246.0	254.2	264.2	261.2	252.2
65,0°	123.0	132.0	150.1	155.1	187.9	237.8	246.8	246.7	245.6	240.6
67,5°	106.7	116.0	130.7	135.4	162.8	215.4	226.6	221.9	221.5	214.6
70,0°	104.7	109.4	119.7	127.2	146.9	182.2	196.9	192.8	179.2	177.4
72,5°	54.5	74.3	94.6	104.6	123.1	146.1	166.9	148.0	126.5	123.4
75,0°	36.9	41.4	52.0	62.3	74.0	82.9	103.7	95.0	89.7	83.0
77,5°	18.6	20.4	22.0	25.2	26.0	29.1	43.9	56.1	50.1	47.8
80,0°	11.8	11.6	12.0	12.5	13.2	14.1	17.8	24.6	23.4	22.7
82,5°	8.4	8.5	8.9	9.5	9.9	10.6	11.1	12.4	12.7	12.8
85,0°	6.1	6.0	6.3	6.8	7.3	7.7	8.0	8.2	8.0	8.2
87,5°	4.1	4.2	4.5	4.9	5.4	5.9	6.2	6.3	6.2	6.3
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family DL® 30 LED	Order number: 5XA5132R1B08A5 EAN: 4058352059371	LP number 57205_8
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	50°	55°	60°	65°	70°	75°	80°	85°	90°	Phi-zone	Total Phi-zone
	130°	125°	120°	115°	110°	105°	100°	95°			
	230°	235°	240°	245°	250°	255°	260°	265°			
	310°	305°	300°	295°	290°	285°	280°	275°			
γ	Luminous intensity in cd/klm									Luminous flux in lm/klm	
0,0°	194.0	194.0	194.0	194.0	194.0	194.0	194.0	194.0	194.0	0.3	0.3
2,5°	193.3	194.0	196.5	196.4	194.7	195.5	196.6	196.4	195.8	2.3	2.6
5,0°	195.6	196.7	199.2	199.2	197.6	198.9	200.1	199.9	199.6	4.7	7.4
7,5°	198.8	200.5	204.0	204.9	204.3	206.4	208.2	208.3	207.8	7.3	14.7
10,0°	201.5	204.5	208.7	210.8	211.4	214.0	216.2	216.6	216.1	10.0	24.7
12,5°	201.3	204.4	208.9	211.0	212.0	214.3	216.4	216.5	216.0	12.5	37.1
15,0°	196.9	199.7	202.6	204.2	205.6	208.4	211.1	212.0	211.8	14.5	51.6
17,5°	186.2	189.4	192.9	195.4	198.3	202.3	205.8	206.9	206.4	16.2	67.9
20,0°	175.4	181.3	186.1	189.9	196.0	201.6	204.8	205.3	204.2	18.0	85.8
22,5°	169.1	177.5	184.0	190.2	196.7	200.5	201.7	201.5	200.6	19.8	105.6
25,0°	168.3	178.2	185.4	190.4	194.2	193.8	193.8	196.2	196.7	21.6	127.3
27,5°	175.9	180.9	186.1	191.3	194.1	192.9	195.2	198.9	199.9	23.9	151.1
30,0°	185.6	183.7	189.3	197.4	200.3	201.0	205.4	208.5	207.1	26.9	178.0
32,5°	194.8	192.6	195.6	205.3	207.1	204.7	205.5	210.2	211.1	29.8	207.8
35,0°	206.2	206.4	203.5	208.7	209.6	208.1	211.8	220.9	222.6	33.1	240.9
37,5°	217.0	217.4	209.0	212.3	218.2	219.3	225.7	235.0	233.3	36.8	277.7
40,0°	230.4	224.3	221.2	222.4	225.2	222.9	227.6	238.0	239.8	40.3	318.0
42,5°	239.8	237.7	233.2	224.8	224.3	226.5	230.9	244.6	247.0	43.6	361.6
45,0°	256.0	250.1	235.5	226.8	226.2	233.4	239.8	251.8	251.6	47.1	408.7
47,5°	266.7	259.0	249.4	231.1	232.5	244.2	249.9	253.6	251.7	50.8	459.5
50,0°	269.1	274.3	263.2	235.9	236.5	247.6	256.7	252.0	247.7	53.8	513.3
52,5°	277.5	286.9	270.1	246.4	238.6	242.2	248.0	247.9	245.5	56.1	569.5
55,0°	280.7	288.0	274.5	255.3	243.3	239.9	238.9	244.5	241.7	58.0	627.5
57,5°	276.7	282.5	274.2	266.4	250.7	228.2	227.9	236.2	232.9	58.9	686.4
60,0°	272.9	274.6	262.7	262.9	241.2	215.8	210.3	202.8	199.0	57.3	743.7
62,5°	268.9	266.7	252.4	248.9	220.9	193.1	178.0	162.6	155.9	53.9	797.6
65,0°	246.5	250.8	247.6	237.4	185.5	157.8	147.1	128.6	118.2	49.2	846.8
67,5°	223.9	224.1	232.2	216.1	161.4	136.6	127.2	108.5	101.9	44.7	891.5
70,0°	182.2	193.8	198.5	178.9	142.2	124.3	114.5	98.0	91.5	39.5	931.0
72,5°	135.6	156.0	162.2	139.2	112.5	94.1	76.8	59.6	50.1	30.4	961.5
75,0°	79.8	91.9	97.4	75.9	67.8	52.5	45.6	33.8	29.7	18.6	980.0
77,5°	40.8	43.4	39.2	29.8	26.7	25.1	21.3	19.1	18.1	8.7	988.7
80,0°	25.4	25.7	19.5	16.3	15.5	14.7	13.8	13.3	13.1	4.6	993.4
82,5°	12.3	13.1	12.4	12.1	11.8	11.2	10.4	9.9	9.8	3.0	996.4
85,0°	8.4	8.8	9.1	8.9	8.5	7.9	7.3	6.9	6.8	2.1	998.5
87,5°	6.5	6.7	6.7	6.5	6.0	5.5	5.0	4.7	4.5	1.6	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family DL® 30 LED	Order number: 5XA5132R1B08A5 EAN: 4058352059371	LP number 57205_8
------------------------------------	--	------------------------------------

Dimming levels table	environmental temperature: 25°C	sITeco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Luminous flux [lm]	Power consumption [W] start of lifetime	Power consumption [W] end of lifetime	Power consumption [W] average
100	254	6990	52.0	54.0	53.0
95	241	6632	48.7	50.6	49.7
90	229	6302	45.8	47.6	46.7
85	216	5944	42.7	44.4	43.6
80	203	5586	39.8	41.3	40.6
75	190	5229	36.9	38.4	37.6
70	178	4899	34.4	35.7	35.0
65	165	4541	31.6	32.8	32.2
60	152	4183	29.0	30.1	29.6
55	140	3853	26.6	27.5	27.0
50	127	3495	24.1	24.9	24.5
45	114	3137	21.6	22.4	22.0
40	102	2807	19.4	20.1	19.8
35	89	2449	17.0	17.6	17.3
30	76	2091	14.6	15.1	14.8
25	63	1734	12.3	12.7	12.5
20	51	1404	10.2	10.6	10.4
15	38	1046	8.0	8.2	8.1